

**NORTH 1/16 CORNER OF THE NORTHEAST 1/4 SECTION 23, TOWNSHIP 17 SOUTH,
RANGE 10 EAST**

1) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 26, 2010 FOR PROJECT NUMBER 10065-02, SURVEY F23003 IN THE SURVEY FILE FOR TOWNSHIP 17-10 FOR A SURVEY FOR KERMIT GROTHER TO SURVEY THE WEST LINE OF THE NORTHEAST 1/4 OF THE NORTHEAST 1/4 OF SECTION 23-17-10, SAID THAT **HE SET A 1/2" X 24" REBAR WITH "LS 752" CAP** FOR THE NORTH 1/16TH CORNER OF THE NORTHEAST 1/4 OF SECTION 23-17-10 ON TRUE LINE AND HALF WAY BETWEEN THE NORTH 1/4 CORNER AND THE NORTHEAST CORNER OF SECTION 23-17-10. HE SAID TO SEE A PRIOR SURVEY BY J. H. HIBBEN DATED 1880 IN BOOK 3 AT PAGE 561 IN THE REGISTER OF DEEDS OFFICE.

- 1) 20.00' SOUTH TO A 1/2" X 24" REBAR WITH HIS "LS 752" CAP SET
- 2) 28.30' NORTH TO A SPIKE & BOTTLECAP IN THE EAST FACE OF A POWER POLE
- 3) 29.45' NW TO A SPIKE & BOTTLECAP IN THE TOP OF A FENCE POST
- 4) 2.0' WEST TO A CROP LINE TO THE SOUTH EXTENDED
- 5) 1.0' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 280 EAST-WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,333.71' WEST TO THE HIBBEN LIMESTONE HE FOUND AT THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 23-17-10
- 2) 1,333.71' EAST TO THE 5/8" REBAR HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 23-17-10
- 3) 1,326.36' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE NE1/4 OF THE NE1/4 OF SECTION 23-17-10
- 4) 2,652.72' SOUTH TO THE THEORETICAL POSITION FOR THE SOUTH 1/16TH CORNER OF THE NE1/4 OF SECTION 23-17-10

NORTH SIXTEENTH CORNER NORTHEAST QUARTER 23-17-10