

WEST 1/16 CORNER OF THE SOUTHEAST 1/4 SECTION 24, TOWNSHIP 17 SOUTH, RANGE 10 EAST

1) AARON C. DAVIS, L.S. 1368, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 13, 2003, FOR PROJECT NUMBER 03088-02, SURVEY F24001 IN THE SURVEY FILE FOR TOWNSHIP 17-10 FOR A SURVEY OF THE SOUTHWEST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 24-17-10, SAID THAT **HE SET A 1/2" X 24" REBAR WITH A "LS 752" CAP** FOR THE WEST 1/16TH CORNER OF THE SOUTHEAST 1/4 OF SECTION 24-17-10 ON TRUE LINE AND AT HALF THE DISTANCE BETWEEN THE CENTER CORNER OF SECTION 24-17-10 AND THE SOUTH 1/4 CORNER OF SECTION 24-17-10.

- 1) 1.6' SOUTH TO A FENCE LINE TO THE WEST EXTENDED
- 2) 2.0' WEST TO A FENCE LINE RUNNING NORTH & SOUTH
- 3) 2.4' SW TO A CONCRETE NAIL & WASHER IN A CORNER POST
- 4) 11.8' SW TO A CONCRETE NAIL & WASHER IN A BRACE POST
- 5) 13.25' WEST TO A CONCRETE NAIL & WASHER IN A BRACE POST

THE SURVEY DRAWING SIGNED BY STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, SHOWS THE FOLLOWING INFORMATION:

- 1) 1,324.92' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 24-17-10
- 2) 1,324.92' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY HE SET FOR THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 24-17-10
- 3) 1,311.14' EAST TO THE 1/2" REBAR WITH "LS 752" CAP HE SET FOR THE CENTER CORNER OF THE SOUTHEAST 1/4 OF SECTION 24-17-10
- 4) 2,622.28' EAST TO THE THEORETICAL POSITION FOR THE EAST 1/16TH CORNER OF THE SOUTHEAST 1/4 OF SECTION 24-17-10

WEST SIXTEENTH CORNER SOUTHEAST QUARTER 24-17-10