

**NORTH 1/4 CORNER SECTION 28, TOWNSHIP 17 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 157 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 21 & 28-17-10.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 39.68 CHAINS WEST TO THE 20" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 20, 21, 28 & 29
  - 2) 39.69 CHAINS EAST TO THE 16" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 21, 22, 27 & 28
  
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 86 RECORDED IN SURVEY BOOK "A" ON PAGE 181 DATED FEBRUARY 8, 1869 FOR A SURVEY OF LAND OWNED BY A. G. EDMISTON, BEING THE SOUTHWEST 1/4 AND THE WEST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 28-17-10, SAID THAT THE NORTH 1/4 CORNER OF SECTION 28-17-10 WAS **LOST**. **HE SET A STONE** FOR THE NORTH 1/4 CORNER OF SECTION 28-17-10 EQUIDISTANT BETWEEN THE STONE THAT HE SET FOR THE NORTHWEST CORNER OF SECTION 28-17-10 AND THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 28-17-10 ON THIS SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 157 RODS, 4 LINKS WEST TO THE STONE HE SET FOR THE NORTHWEST CORNER OF SECTION 28-17-10
  - 2) 157 RODS, 4 LINKS EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 28-17-10
  
- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A **PERMANENT SURVEY** RECORDED IN VOLUME 3 ON PAGE 555 IN THE REGISTER OF DEEDS OFFICE ON MAY 29, 1880 AND SURVEY F21001 IN THE SURVEY FILE FOR TOWNSHIP 17-10 TO PERMANENTLY ESTABLISH THE CORNERS OF THE NORTH 1/2 OF THE NORTHWEST 1/4, AND THE NORTHEAST 1/4, AND THE NORTH 1/2 OF THE SOUTHEAST 1/4, AND THE SOUTH 1/2 OF THE SOUTHWEST 1/4, AND THE NORTH 1/2 OF THE SOUTHWEST 1/4, AND THE SOUTH 1/2 OF THE NORTHWEST 1/4 OF SECTION 21-17-10, SAID THAT HE BEGAN THIS SURVEY ON APRIL 22, 1880. **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 21-17-10 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 39.76 CHAINS WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 21-17-10
  - 2) 39.97 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 21-17-10
  - 3) 19.96 CHAINS NORTH TO THE ROCK SET FOR THE PERMANENT WEST 1/16<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 21-17-10
  - 4) 39.92 CHAINS NORTH TO THE LIMESTONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 21-17-10
  - 5) 59.89-1/8 CHAINS NORTH TO THE LIMESTONE HE SET FOR THE PERMANENT EAST 1/16<sup>TH</sup> CORNER OF THE NW1/4 OF SECTION 21-17-10
  - 6) 79.86-1/4 CHAINS NORTH TO THE LIMESTONE HE SET FOR THE NORTH 1/4 CORNER OF SECTION 21-17-10
  
- 4) REA BOOK 30 ON PAGE 16 SAYS THAT **THEY DROVE AN IRON PIN** FOR THE NORTH 1/4 CORNER OF SECTION 28-17-10 AT 4 FEET EAST OF A CORNER OF A FENCE ON THE NORTH SIDE OF THE ROAD. **SEE THE NOTE ON PAGE 57.5 ABOUT THE STONE HE FOUND AT 5 FEET WEST OF THIS PIN – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**

CONTINUED ON PAGE 2

- 5) THE KRETSINGER REFERENCE TIE BOOK FOR THIS TOWNSHIP SHOWS A **REA PIN** AT THE “NE CORNER NW1/4 SECTION 28-17-10”. **SEE THE NOTE ON PAGE 57.5 ABOUT THE STONE HE FOUND AT 5 FEET WEST OF THIS PIN – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
- 1) 27.25’ EAST TO A WITNESS [REA]
- 6) REA BOOK 30 ON PAGE 57.5 SAYS: “JUNE 30, 1939. O. D. HENRY SENT ME UP WITH GENTZ & TWO LABORERS TO S. 1/4 21-17-10 [N. 1/4 28-17-10] TO DIG FOR CORNER STONE SAID TO BE 20’ S. OF WIRE FENCE ON N. SIDE OF ROAD. AT A DEPTH OF PERHAPS 3-1/2 FEET & 20’ S. OF SAID FENCE, ON LINE WITH WIRE FENCE N. THROUGH FIELDS **WE FOUND A STONE** FLAT ON ITS SIDE APPROXIMATELY 18 X 10 X 3 INCHES NO MARKS, IS 4’ N. OF LINE O. D. HENRY LOCATED FOR HIGHWAY & I AFTERWARD LOCATED FOR REA, **5’ WEST FROM MY PIN TO CENTER OF STONE** AS IS LIES. [6’ NW TO EAST END OF STONE WHICH I BELIEVE TO BE THE TRUE LOCATION OF CORNER, 29’ NORTH OF MY WITNESS PIN]. MOVED HENRY’S R. W. STAKES 25’ N. & S. OF STONE.”

NORTH QUARTER CORNER 28-17-10