

NORTH 1/16 CORNER OF THE SOUTHEAST 1/4 SECTION 28 TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 86 RECORDED IN SURVEY BOOK "A" ON PAGE 181 DATED FEBRUARY 8, 1869 FOR A SURVEY OF LAND OWNED BY A. G. EDMISTON, BEING THE SOUTHWEST 1/4 AND THE WEST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 28-17-10, SAID THAT **HE SET A STONE** FOR THE NORTH 1/2/4 CORNER OF THE SOUTHEAST 1/4 OF SECTION 28-17-10 EQUIDISTANT BETWEEN THE STONES THAT HE SET FOR THE EAST 1/4 CORNER OF SECTION 28-16-10 AND AT THE CENTER CORNER OF SECTION 28-16-10 ON THIS SURVEY.

- 2) STEVEN S. BROSEMER, L.S. 752, IN HIS *REPORT OF SURVEY* DATED MARCH 11, 1985 FOR A SURVEY OF A 18.92 ACRE TRACT IN THE EAST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 28-17-10, RECORDED IN VOLUME 413 ON PAGE 885 IN THE REGISTER OF DEEDS OFFICE ON MARCH 18, 1885, SURVEY F28001 IN THE SURVEY FILE FOR TOWNSHIP 17-10, SAID THAT HE SEARCHED FOR THE STONE AT THE NORTHEAST CORNER OF THE EAST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 28-16-10, BUT HE DETERMINED THAT THE STONE HAD BEEN DOZED OUT. HE SAID THAT THE CORNER WAS **NOT** REESTABLISHED IN THE FIELD, BUT THE POSITION WAS DETERMINED TO BE ON TRUE LINE AND HALFWAY BETWEEN THE EAST 1/4 CORNER OF SECTION 28-17-10 AND THE CENTER CORNER OF SECTION 28-17-10.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,318.25' WEST TO THE STONE HE FOUND AT THE CENTER CORNER OF SECTION 28-17-10
 - 2) 1,318.25' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE EAST 1/4 CORNER OF SECTION 28-17-10
 - 3) 2,663.06' SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 28-17-10

NORTH SIXTEENTH CORNER SOUTHEAST QUARTER 28-17-10