

WEST 1/4 CORNER SECTION 28, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) ON PAGE 157 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 28 & 29-17-10.
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 86 RECORDED IN SURVEY BOOK "A" ON PAGE 181 DATED FEBRUARY 8, 1869 FOR A SURVEY OF LAND OWNED BY A. G. EDMISTON, BEING THE SOUTHWEST 1/4 AND THE WEST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 28-17-10, SAID THAT THE WEST 1/4 CORNER OF SECTION 28-17-10 WAS **LOST**. **HE SET A STONE** FOR THE WEST 1/4 CORNER OF SECTION 28-17-10 EQUIDISTANT BETWEEN THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 28-17-10 AND THE STONE THAT HE SET FOR THE NORTHWEST CORNER OF SECTION 28-17-10 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 160 RODS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 28-17-10
 - 2) 160 RODS NORTH TO THE STONE HE SET FOR THE NORTHWEST CORNER OF SECTION 28-17-10
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 203 [PACKET 46 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] ON THE PETITION BY JESSE HEAD AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 15-10, 16-10 AND 17-10 THAT HE SURVEYED ON APRIL 22-24, 1872, AND WAS ORDERED AS A 50 FOOT WIDE ROAD AT A MEETING OF THE COUNTY BOARD HELD MAY 20, 1872 AS ATTESTED BY DAVID S. GILMORE, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 28-17-10 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES TO THE NORTHEAST CORNER OF THE SE1/4 OF THE NE1/4 OF SECTION 8-17-10 AT A TURN TO THE WEST
 - 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 27-2/10 RODS TO INTERSECT THE AMERICUS AND COUNCIL GROVE ROAD FOR THE END OF THIS ROAD SURVEY
- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 48 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 105 DATED OCTOBER 28, 1874 TO SUBDIVIDE SECTION 29-17-10, SAID THAT **HE FOUND THE STONE IN PLACE** AT THE WEST 1/4 CORNER OF SECTION 28-17-10 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 1,343-1/2' SOUTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/8TH CORNER OF THE SE1/4 OF SECTION 29-17-10
 - 2) 2,687' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 29-17-10
 - 3) 2004' WEST TO THE STONE HE SET ON THE EAST BOUNDARY OF THE KAW DIMINISHED RESERVE
- 5) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 81, A **PERMANENT SURVEY** ORDERED BY J. J. DOTY TO SURVEY SECTION 29-17-10 RECORDED IN SURVEY BOOK "E" ON PAGE 81 DATED DECEMBER 22-27, 1884 AND RECORDED IN VOLUME 41 ON PAGE 29 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 27, 1887, SURVEY F29001 IN THE SURVEY FILE FOR TOWNSHIP 17-10, SAID THAT **HE SET A TEMPORARY STAKE** FOR THE EAST 1/4 CORNER OF SECTION 29-17-10 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,332.5' WEST TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/4/4 CORNER ON THE SOUTH SIDE OF THE NE1/4 OF SECTION 29-17-10
 - 2) 2,004' WEST TO THE 6" X 10" X 14" STONE HE SET FOR THE PERMANENT CORNER ON THE INDIAN RESERVE LINE
 - 3) 2,665' WEST TO THE 4" X 8" X 30" STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 29-17-10
 - 4) 3,988.5' WEST TO THE 2" X 3" X 16" STONE HE SET FOR A REFERENCE CORNER TO THE SOUTH 1/4/4 CORNER OF THE NW1/4 OF SECTION 29-17-10 AS THE TRUE CORNER FALLS IN THE NEOSHO RIVER
 - 5) 3,989' WEST TO THE THEORETICAL LOCATION FOR THE SOUTH 1/4/4 CORNER ON THE SOUTH SIDE OF THE NW1/4 OF SECTION 29-17-10—FALLS IN THE NEOSHO RIVER
 - 6) 5,313' WEST TO THE 5" X 5" X 14" STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 29-17-10
- 6) **REA PIN—MUST VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING; THIS IRON PIN WAS PROBABLY JUST “HEELED—IN” FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 6-3, COUNTY SURVEYOR** REA BOOK 30 ON PAGE 17 SAYS THAT **THEY SET AN IRON PIN** FOR THE WEST 1/4 CORNER OF SECTION 28-17-10.
- 1) 25' WEST TO A WITNESS PIN
- 7) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 17-10 SHOWS A **REA PIN** AT THE “SW CORNER NW1/4 SECTION 28-17-10”. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING; THIS IRON PIN WAS PROBABLY “HEELED-IN FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
- 1) 25' WEST TO A WITNESS [REA]

WEST QUARTER CORNER 28-17-10