

INDIAN RESERVE CORNER ON THE NORTH LINE OF THE NORTHEAST QUARTER OF SECTION 29, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) ON PAGE 162 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT AT 30.27 CHAINS WEST OF THE NORTHWEST CORNER OF SECTION 28-17-10 THEY INTERSECTED EAST BOUNDARY OF THE KANSAS INDIAN DIMINISHED RESERVE AT 10.40 CHAINS SOUTH OF THE 2-1/2 MILE CORNER, WHERE THEY SET A LIMESTONE 20" X 14" X 3" FOR THE FRACTIONAL CORNER TO SECTIONS 20 & 29-17-10 ON THE NORTH LINE OF THE NORTHEAST 1/4 OF SECTION 29-17-10 ON MARCH 3, 1861.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 9.98 CHAINS WEST TO THE 18" X 14" X 6" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 20 & 29
 - 2) 50.23 CHAINS WEST TO THE 14" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20, 29 & 30
 - 3) 30.27 CHAINS EAST TO THE 20" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 20, 21, 28 & 29
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 48 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 105 DATED OCTOBER 28, 1874 TO SUBDIVIDE SECTION 29-17-10, SAID THAT **HE SET A STONE** FOR THE PERMANENT CORNER ON THE EAST BOUNDARY OF THE KAW DIMINISHED RESERVE AND THE NORTH LINE OF THE NORTHEAST 1/4 OF SECTION 29-17-10 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 633' WEST TO THE STONE HE SET FOR THE PERMANENT 1/4 CORNER BETWEEN SECTIONS 20 & 29-17-10
 - 2) 1,959-1/2' WEST TO THE STONE HE SET FOR THE PERMANENT 1/8TH CORNER ON THE NORTH LINE OF THE NW1/4 OF SECTION 29-17-10
 - 3) 3,286' WEST TO THE STONE HE FOUND AT THE CORNER TO SECTIONS 19, 20, 29 & 30-17-10
 - 4) 2,020' EAST TO THE STONE HE FOUND AT THE CORNER TO SECTIONS 29-17-10
- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER EIGHTY-ONE, A **PERMANENT SURVEY** ORDERED BY J. J. DOTY TO SURVEY SECTION 29-17-10 RECORDED IN SURVEY BOOK "E" ON PAGE 81 DATED DECEMBER 22-27, 1884 AND RECORDED IN VOLUME 41 ON PAGE 29 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 27, 1887, SURVEY F29001 IN THE SURVEY FILE FOR TOWNSHIP 17-10, SAID THAT **HE FOUND THE STONE** AT THE INTERSECTION OF THE INDIAN RESERVE LINE AND THE NORTH LINE OF THE NORTHEAST 1/4 OF SECTION 29-17-10 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 666.5' EAST TO THE TEMPORARY STAKE HE SET FOR THE NORTH 1/4 OF 1/4 CORNER OF THE NE1/4 OF SECTION 29-17-10
 - 2) 1,999.5' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 29-17-10
 - 3) 666.5' WEST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 29-17-10
- 4) STEVEN S. BROSEMER, P.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 1, 2016 FOR PROJECT NUMBER 16203-02, A SURVEY OF THE SOUTH LINE OF SECTION 20, TOWNSHIP 17 SOUTH, RANGE 10 EAST FOR THE LYON COUNTY HIGHWAY DEPARTMENT PROJECT NUMBER 16-47, SURVEY F20002 IN THE SURVEY FILE FOR TOWNSHIP 17-10, THE CONSTRUCTION OF A 14' X 6' X 24' PRECAST CONCRETE BOX CULVERT 927.9-500.0 ON COUNTY ROAD

270, SAID THAT HE DUG WITH A COUNTY BACKHOE FOR THE STONE AT THE INDIAN RESERVE CORNER ON THE SOUTH BOUNDARY OF SECTION 20-17-10. **HE FOUND THE EXISTING RECORD 17" X 8" X 9" POST ROCK AT 30" DEEP ON THE EAST BOUNDARY OF THE KANSAS INDIAN RESERVE. HE SET A 5/8" X 25" REBAR WITH A LYON COUNTY CAP ON THE NORTH SIDE OF THE STONE, A 1/2" X 24" REBAR WITH HIS "PS 752 S. BROSEMER" CAP ON THE SOUTH SIDE OF THE STONE, AND A 5/8" X 24" REBAR WITH A LYON COUNTY CAP OVER THE STONE.** HE NOTED THAT THIS STONE WAS FOUND BY EDMISTON IN 1884 AS RECORDED IN SURVEY BOOK "E" ON PAGE 29. THIS CORNER IS LOCATED AT LYON COUNTY PROJECT NUMBER 16-47 STATION 19+99.10.

- 1) UN-ADJUSTED STATE PLANE COORDINATES, KANSAS SOUTH ZONE
NORTH = 2005613.577000 EAST = 1934601.714000
- 2) 32.20' SE TO A CONCRETE NAIL & BOTTLECAP IN A DEADMAN'S POLE
- 3) 92.20' WEST TO THE CENTER OF A CONCRETE BRIDGE [HORIZONTAL]
- 4) 1.00' NOT TO THE TRAVELED WAY OF COUNTY ROAD 270 EAST-WEST
- 5) 673.73' WEST TO A 5/8" IRON BARA WITH A LYON COUNTY CAP OVER THE STONE AT THE N1/4 CORNER OF SECTION 29-17-10

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 673.75' WEST TO THE 5/8" X 24" REBAR WITH A LYON COUNTY CAP OVER THE LIMESTONE HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 20-17-10 AT P.O.T. STATION 26+72.85
- 2) 3,317.95' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP BENT OVER THE LIMESTONE HE FOUND FROM REFERENCE TIES AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 20-17-10 AT P.O.T. STATION 53+17.05
- 3) 1,237.10' EAST TO THE 1/2" X 24" REBAR WITH HIS "PS 752" CAP HE SET FOR P.O.T. STATION 7+62.00
- 4) 1,837.10' EAST TO THE 1/2" X 24" REBAR WITH HIS "PS 752" CAP HE SET FOR P.O.T. STATION 1+62.00
- 5) 1,991.00' FEET EAST TO THE 5/8" X 6" REBAR WITH A LYON COUNTY CAP HE SET OVER THE LIMESTONE HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 20-17-10

IR CORNER ON NORTH LINE NORTHEAST QUARTER 29-17-10