

**NORTH 1/16 CORNER OF THE NORTHWEST 1/4 SECTION 29 TOWNSHIP 17 SOUTH,
RANGE 10 EAST**

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 48 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 105 DATED OCTOBER 28, 1874 TO SUBDIVIDE SECTION 29-17-10, SAID THAT **HE SET A STONE** FOR THE PERMANENT NORTH 1/8TH CORNER OF THE NORTHWEST 1/4 OF SECTION 29-17-10 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 29-17-10 AND THE STONE THAT HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 29-17-10 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 1,326-1/2' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 29-17-10
 - 2) 1,326-1/2' EAST TO THE STONE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 29-17-10
 - 3) 1,959-1/2' EAST TO THE STONE THAT HE SET ON THE EAST BOUNDARY OF THE KAW DIMINISHED RESERVE
 - 4) 3,979-1/2' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 29-17-10
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 67 OF THE 8TH TERM, A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON PAGE 124 DATED MARCH 8, 1875 FOR A COUNTY ROAD PETITIONED BY F. RAYMOND, ET. AL, SAID THAT HE INTERSECTED THE LINE BETWEEN SECTIONS 20 & 29-17-10 AT A POINT 28 FEET EAST OF THE SOUTH 1/2/4 OF THE SOUTHWEST 1/4 OF SECTION 20-17-10 ON THIS ROAD SURVEY.

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, BY C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 125 DATED APRIL 11, 1882 AT THE REQUEST OF J. E. ROBERTS TO SURVEY AND ESTABLISH IN TOWNSHIP 17, RANGE 10, THE CENTER CORNER OF SECTION 20 AND THE 18TH CORNER BETWEEN THE CENTER AND THE 1/4 CORNER ON THE WEST, THE 1/8TH CORNER BETWEEN THE SOUTHWEST CORNER OF THE SECTION AND THE 1/4 CORNER ON THE SOUTH, AND THE 1/16TH CORNER IN THE CENTER OF THE SOUTHWEST 1/4, AND SUCH OTHER LINES AND CORNERS AS MAY BE NECESSARY TO COMPLETE THE WORK, SAID THAT **HE SET A STONE** FOR THE PERMANENT SOUTH 1/8TH CORNER OF THE SOUTHWEST 1/4 OF SECTION 20-17-10 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 20-17-10 AND THE STONE THAT HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 20-17-10 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 20.10 CHAINS WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 20-17-10
 - 2) 20.10 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 20-17-10
- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 81, A **PERMANENT SURVEY** ORDERED BY J. J. DOTY TO SURVEY SECTION 29-17-10 RECORDED IN SURVEY BOOK "E" ON PAGE 81 DATED DECEMBER 22-27, 1884 AND RECORDED IN VOLUME 41 ON PAGE 29 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 27, 1887, SURVEY F29001 IN THE SURVEY FILE FOR TOWNSHIP 17-10, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4/4 CORNER OF THE NORTHWEST 1/4 OF SECTION 29-17-10 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,321' SOUTH TO THE 3" X 9" X 24" STONE HE SET FOR THE PERMANENT CENTER CORNER OF THE NW1/4 OF SECTION 29-17-10
 - 2) 2,642' SOUTH TO THE TRUE POSITION FOR THE SOUTH 1/4/4 CORNER OF THE NW1/4 OF SECTION 29-17-10, AS THE TRUE POSITION FALLS IN THE NEOSHO RIVER
 - 3) 2,709' SOUTH TO THE 4" X 6" X 15" **REFERENCE STONE** HE SET FOR THE SOUTH 1/4/4 CORNER OF THE NW1/4 OF SECTION 29-17-10, AS THE TRUE POSITION FALLS IN THE NEOSHO RIVER
- 5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 141, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 222 DATED JANUARY 23-30, 1906 AT THE ORDER OF JOHN GUTHRIE FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THAT PORTION OF THE SOUTHEAST 1/4 OF SECTION 17-17-10 WHICH LIES EAST OF THE EAST LINE OF THE DIMINISHED KANSAS INDIAN RESERVATION, EXCEPTING THOSE ON THE NORTH LINE, AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE SOUTH 1/2/4 CORNER OF THE SOUTHWEST 1/4 OF SECTION 20-17-10 ON THIS **PERMANENT SURVEY**. SEE BOOK "E" IN THE KRETSINGER COLLECTION ON PAGES 14 & 15, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 14" IN MISCELLANEOUS DRAWER NUMBER 1 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

NORTH SIXTEENTH CORNER NORTHWEST QUARTER 29-17-10