

**NORTH 1/16 CORNER OF THE SOUTHWEST 1/4 SECTION 29 TOWNSHIP 17 SOUTH,
RANGE 10 EAST**

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 48 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 105 DATED OCTOBER 28, 1874 TO SUBDIVIDE SECTION 29-17-10, SAID THAT HE DETERMINED THE **TRUE POSITION** FOR THE SOUTH 1/8TH CORNER OF THE NORTHWEST 1/4 OF SECTION 29-17-10 TO BE ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE WEST 1/4 CORNER OF SECTION 29-17-10 AND THE STONE THAT HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 29-17-10, AND THIS POSITION FELL IN THE RIVER. **HE SET WITNESS STONES AT 50 FEET SOUTH AND 90 FEET EAST OF THE TRUE POSITION ON THIS PERMANENT SURVEY.**

- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 81, A **PERMANENT SURVEY** ORDERED BY J. J. DOTY TO SURVEY SECTION 29-17-10 RECORDED IN SURVEY BOOK "E" ON PAGE 81 DATED DECEMBER 22-27, 1884 AND RECORDED IN VOLUME 41 ON PAGE 29 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 27, 1887, SURVEY F29001 IN THE SURVEY FILE FOR TOWNSHIP 17-10, SAID THAT HE DETERMINED THE **TRUE POSITION** FOR THE SOUTH 1/4 OF 1/4 OF THE NORTHWEST 1/4 OF SECTION 29-17-10 TO BE ON LINE AND HALFWAY BETWEEN THE STONE THAT HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 29-17-10 AND THE STONE THAT HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 29-17-10. **HE SET REFERENCE STONES** FOR THE SOUTH 1/4 OF 1/4 CORNER OF THE NORTHWEST 1/4 OF SECTION 29-17-10 AS THE **TRUE POSITION** FALLS IN THE NEOSHO RIVER ON THIS **PERMANENT SURVEY.**
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION FROM THE TRUE POSITION:
 - 1) 1,324' WEST TO THE 5" X 5" X 15" STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 29-17-10
 - 2) 88.5' EAST TO THE 2" X 5" X 16" **REFERENCE STONE** HE SET ON THE 1/2 SECTION LINE
 - 3) 1,324' EAST TO THE 4" X 5" X 30" STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 29-17-10
 - 4) 1,985' EAST TO THE 6" X 10" X 14" STONE HE SET ON THE INDIAN RESERVE LINE
 - 5) 2,656.5' EAST TO THE 4" X 15" X 18" STONE HE SET FOR THE PERMANENT SOUTH 1/4 OF 1/4 CORNER OF THE NE1/4 OF SECTION 29-17-10
 - 6) 3,989' EAST TO THE TEMPORARY STAKE HE SET FOR THE EAST 1/4 CORNER OF SECTION 29-17-10
 - 7) 67' SOUTH TO A 4" X 6" X 16" **REFERENCE STONE** HE SET

NORTH SIXTEENTH CORNER SOUTHWEST QUARTER 29-17-10