

WEST 1/16 CORNER OF THE SOUTHWEST 1/4 SECTION 29, TOWNSHIP 17 SOUTH, RANGE 10 EAST

1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 47 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 104 AND DATED OCTOBER 16, 1874 FOR THE SUBDIVISION OF SECTION 19-17-10, SAID THAT AFTER HE RAN THE SECTION LINES FROM THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 19-17-10 TO THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 32-17-10, **HE RESET THE STONE** THAT HE FOUND "AT THE CORRESPONDING CORRECTION OF 1/4 AND 1/8 CORNERS ON BOTH LINES AND SET UP THE OLD OR MARKED STONES I FOUND LYING NEAR THEIR RESPECTIVE PLACES" FOR THE EAST 1/8TH CORNER OF THE SOUTHWEST 1/4 OF SECTION 29-17-10 ON THIS **PERMANENT SURVEY**.

2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A **PERMANENT SURVEY** RECORDED IN THE REGISTER OF DEEDS OFFICE, SURVEY F30001 IN THE SURVEY FILE FOR TOWNSHIP 17-10 DATED APRIL 26-30, 1880 TO ESTABLISH THE NORTHEAST CORNER OF THE SOUTHWEST 1/4, THE NORTH CORNER OF THE SOUTHWEST 1/4, THE NORTHWEST CORNER OF THE SOUTHWEST 1/4, THE NORTHWEST CORNER OF THE NORTHWEST 1/4, AND THE NORTH CORNER OF THE NORTHWEST 1/4 IN SECTION 31-17-10, AND ALSO THE SOUTH CORNER OF THE NORTHWEST 1/4 AND THE NORTHEAST CORNER AND THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 30-17-10, SAID THAT **HE SET A TEMPORARY 1/16TH CORNER** ON THE EAST SIDE OF THE SOUTHWEST 1/4 OF SECTION 30-17-10 EQUIDISTANT BETWEEN THE STONES THAT HE FOUND AT THE EAST 1/4 CORNER AND THE SOUTHWEST CORNER OF SECTION 30-17-10 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 20.05-1/2 CHAINS NORTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 30-17-10
- 2) 20.05-1/2 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 30-17-10

3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 81, A **PERMANENT SURVEY** ORDERED BY J. J. DOTY TO SURVEY SECTION 29-17-10 RECORDED IN SURVEY BOOK "E" ON PAGE 81 DATED DECEMBER 22-27, 1884 AND RECORDED IN VOLUME 41 ON PAGE 29 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 27, 1887, SURVEY F29001 IN THE SURVEY FILE FOR TOWNSHIP 17-10, SAID THAT **HE SET A 5" X 9" X 16" STONE** FOR THE PERMANENT 1/4/4 CORNER ON THE WEST SIDE OF THE SOUTHWEST 1/4 OF SECTION 29-17-10 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-17-10 AND THE STONE THAT HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 29-17-10 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,317.5' SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-17-10
- 2) 1,317.5' NORTH TO THE 5" X 5" X 14" STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 29-17-10
- 3) 2,565' NORTH TO THE 5" X 5" X 14" REFERENCE STONE HE SET FOR THE WEST 1/4/4 CORNER OF THE NW1/4 OF SECTION 29-17-10 AS THE TRUE POSITION FALLS IN THE NEOSHO RIVER
- 4) 2,635' NORTH TO THE TRUE POSITION FOR THE WEST 1/4/4 CORNER OF THE NW1/4 OF SECTION 29-17-10 AS THE TRUE POSITION FALLS IN THE NEOSHO RIVER

CONTINUED ON PAGE 2

- 5) 2,735' NORTH TO THE 4" X 6" X 14" REFERENCE STONE HE FOR THE WEST 1/4/4 CORNER OF THE NW1/4 OF SECTION 29-17-10 AS THE TRUE POSITION FALLS IN THE NEOSHO RIVER
 - 6) 3,952.5' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 29-17-10
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 12, 2005, FOR PROJECT NUMBER 05261-02 FOR THE LYON COUNTY HIGHWAY DEPARTMENT PROJECT NUMBER 05-HQ FOR A DRAINAGE PROBLEM ON COUNTY ROAD "B" SOUTH OF ROAD 265, SAID THAT HE EXCAVATED FOR THE STONE AT THE WEST 1/16TH CORNER OF THE SOUTHWEST 1/4 OF SECTION 29-17-10 WITH A COUNTY MAINTAINER. **HE FOUND THE 5" X 9" X 16" STONE** AT THE WEST 1/16TH CORNER OF THE SOUTHWEST 1/4 OF SECTION 29-17-10 THAT WAS SET BY R. H. EDMISTON IN SURVEY BOOK "E" ON PAGE 81 IN THE COUNTY ENGINEER'S OFFICE.
- 1) A 1/2" X 24" REBAR WITH HIS "LS 752" CAP WAS SET UNDER THE CENTER OF THE STONE
 - 2) 0.30' EAST TO A 5/8" X 24" REBAR WITH A LYON COUNTY CAP SET ON THE EAST SIDE OF THE STONE
 - 3) 1,316.38' NORTH TO THE WEST QUARTER CORNER OF SECTION 29
 - 4) 1,313.86' SOUTH TO THE SOUTHWEST CORNER OF SECTION 29
 - 5) 1.12' EAST TO A STRAIGHT LINE BETWEEN THE WEST 1/4 CORNER AND THE SOUTHWEST CORNER OF SECTION 29

WEST SIXTEENTH CORNER SOUTHWEST QUARTER 29-17-10