

**NORTH 1/4 CORNER SECTION 30, TOWNSHIP 17 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 162 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 19 & 30-17-10, FROM WHICH:
  - 1) A BUR OAK TREE 14" IN DIAMETER BEARS N. 6-1/2° W. AT 47 LINKS DISTANCE
  - 2) A BUR OAK TREE 16" IN DIAMETER BEARS S. 44° W. AT 56 LINKS DISTANCE

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

  - 1) 38.25 CHAINS WEST TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 24, 25 & 30 ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE
  - 2) 40.00 CHAINS EAST TO THE 14" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20, 29 & 30
  
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 47 OF THE 8<sup>TH</sup> TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 104 AND DATED OCTOBER 16, 1874 TO FOR THE SUBDIVISION OF SECTION 19-17-10, SAID THAT **HE SET A 16" X 12" X 6" STONE** FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 30-17-10 ON LINE BETWEEN THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 30-17-10 ON THE WEST LINE OF THE COUNTY AND THE STONE THAT HE FOUND AND HE RESET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 30-17-10, AND AT 2,640' WEST OF THE NORTHEAST CORNER OF SECTION 30-17-10 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

  - 1) 2,640' EAST TO THE STONE HE FOUND THAT **HE RESET** FOR THE PERMANENT NORTHEAST CORNER OF SECTION 30-17-10
  - 2) 2,561' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 30-17-10 ON THE WEST LINE OF THE COUNTY
  
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, BY C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 126 DATED APRIL 12, 1882 AT THE REQUEST OF P. BOSTIAN TO SURVEY AND ESTABLISH IN TOWNSHIP 17, RANGE 10, THE 1/4 CORNER AND THE 1/8<sup>TH</sup> CORNER ON THE WEST LINE OF SECTION 19 AND THE 1/8<sup>TH</sup> CORNER BETWEEN THE CENTER CORNER AND THE 1/4 CORNER ON THE SOUTH LINE, AND SUCH OTHER LINES AND CORNERS AS NECESSARY TO COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 19-17-10 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

  - 1) 20.00 CHAINS WEST TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/8<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 19-17-10
  - 2) 37.71-1/2 CHAINS WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 19-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE
  - 3) 20.10-1/2 CHAINS NORTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/8<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 19-17-10
  - 4) 40.21 CHAINS NORTH TO THE STONE HE FOUND AT THE CENTER CORNER OF SECTION 19-17-10
  
- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 176 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 290 TO 292 PETITIONED BY P. BOSTIAN AN OTHERS FOR THE VACATION AND RELOCATION OF A COUNTY ROAD IN SECTION 19-17-10 [PACKED 414 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE] THAT HE SURVEYED ON JUNE 8, 1882, WAS ESTABLISHED AS A 40 FOOT ROAD ON JULY 14, 1882 AS NOTED

BY HUGH F. HOLMES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JULY 22, 1882 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 19-17-10 AT THE TERMINUS OF THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

1) 10.77 CHAINS WEST TO THE STONE HE SET FOR AN ANGLE N. 73° W. FOR 1.97 CHAINS TO AN ANGLE STONE HE SET; THENCE N. 81°0 W. FOR 3 CHAINS TO AN ANGLE STONE HE SET; THENCE S. 35° W. TO AN ANGLE STONE HE SET ON THE SECTION LINE TO BEGIN THIS ROAD SURVEY AT 86 RODS EAST OF THE STONE AT THE SOUTHWEST CORNER OF SECTION 19-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE

- 5) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 14 FOR A ROAD IN TOWNSHIP 17, RANGE 10, DATED JUNE 8, 1882, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 19-17-10 TO END THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

1) THIS ROAD EXTENDS WEST ON THE SECTION LINE FOR 10.77 CHAINS TO A ROAD STONE HE SET FOR A DEVIATION TO THE NORTH, THEN INTERSECTS THE SECTION LINE AT A STONE HE SET TO COMMENCE THIS ROAD SURVEY AT 86 RODS EAST OF THE SOUTHWEST CORNER OF SECTION 19-17-10 ON THE RANGE LINE AND LYON AND MORRIS COUNTY LINE

- 6) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 124, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 124 DATED SEPTEMBER 23 & 24, 1885 ORDERED BY HIRAM DRIGGS TO LOCATE THE CENTER CORNER OF SECTION 19-17-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 19-17-10 ON THIS **PERMANENT SURVEY**.

- 7) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 2, A **PERMANENT SURVEY** WITH THE MORRIS COUNTY SURVEYOR RECORDED IN SURVEY BOOK "E" ON PAGE 182 DATED MARCH 27, 1900 AT THE ORDER OF W. H. ROBINSON TO SURVEY GOVERNMENT LOT 2 IN THE NORTHWEST 1/4 OF SECTION 30-17-10, SAID THAT AFTER HE RAN THE SECTION LINES FROM THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 30-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE TO THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 29-17-10, **HE SET A 5" X 9" X 16" STONE** FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 30-17-10 ON THIS **PERMANENT SURVEY**. HE NOTED THAT ANOTHER STONE BEARS **NORTH ABOUT 45° EAST AT 30 FEET DISTANCE**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 20.34 CHAINS WEST TO THE 4" X 8" X 16" STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF GOVERNMENT LOT 2
- 2) 38.65 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 30-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE
- 3) 39.87 CHAINS EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 30-17-10

- 8) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 28, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 209 DATED AUGUST 20, 1901 ORDERED BY JOHN GUTHRIE TO MAKE SUCH A SURVEY AS MAY BE NECESSARY TO LOCATE AND PERMANENTLY ESTABLISH THE LINE BETWEEN THE NORTH 1/2 AND THE SOUTH 1/2 OF SECTION 19-17-10, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 19-17-10 ON THIS **PERMANENT SURVEY**. THERE IS

ADDITIONAL INFORMATION IN PACKET "M 54" IN MISCELLANEOUS DRAWER NUMBER 2 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

- 9) COMMISSIONER'S ROAD JOURNAL BOOK "A", PAGE 46  
ON AUGUST 2, 1915 A PETITION SIGNED BY JOHN P. BAIN AND OTHERS FOR THE VACATION AND RELOCATION OF A ROAD IN TOWNSHIP 17-10 WAS PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS. THE ROAD WAS VIEWED ON SEPTEMBER 1, 1915, AND THE FINAL ORDER WAS ISSUED ON SEPTEMBER 10, 1915.
- 1) THE ROAD VACATED: BEGINNING AT A POINT WHERE THE PRESENT ROAD LEAVES THE SECTION LINE BETWEEN SECTIONS 19 & 30-17-10 AND VACATING ALL OF SAID ROAD ABOVE SAID POINT TO THE PLACE WHERE ROAD AGAIN ENTERS THE SECTION LINE BETWEEN SECTIONS 19 & 30 AND THERE ENDING
  - 2) RELOCATING THE ROAD ON THE SECTION LINE AS NEAR AS PRACTICAL BETWEEN SECTIONS 19 & 30-17-10 IN ORDER THAT THE ROAD WILL BE ON THE SECTION LINE AS NEAR AS PRACTICAL FROM THE POINT OF BEGINNING TO THE POINT OF ENDING
  - 3) ROAD WAS GRANTED AT 40 FEET IN WIDTH
- 10) W. G. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN A ROAD SURVEY FOR ROAD NUMBER 696 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 53 PETITIONED BY JOHN P. BAIN AND OTHERS FOR THE VACATION AND RELOCATION OF A ROAD IN TOWNSHIP 17-10 [PACKET 787 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE], THAT WAS VIEWED BY THE COUNTY COMMISSIONERS ON SEPTEMBER 1, 1915 APPARENTLY **FOUND THE STONE** AT THE SOUTHEAST CORNER OF THE SOUTHWEST CORNER OF SECTION 19-17-10 TO BEGIN THIS ROAD SURVEY. IT WAS ORDERED ON SEPTEMBER 10, 1915 THAT BEGINNING WHERE THE PRESENT ROAD LEAVES THE SECTION LINE BETWEEN SECTIONS 19 & 30-17-10, AND VACATING ALL OF SAID ROAD FROM ABOVE SAID POINT TO THE PLACE WHERE THE ROAD AGAIN ENTERS THE SECTION LINE BETWEEN SAID SECTIONS 19 & 30, AND RELOCATING THE ROAD ON THE SECTION LINE OR AS NEAR AS PRACTICABLE BETWEEN SAID SECTIONS 19 & 30 IN ORDER THAT SAID ROAD WILL BE ON THE SECTION LINE AS NEAR AS PRACTICABLE FROM THE PLACE OF BEGINNING TO THE PLACE OF ENDING AT A WIDTH OF 40 FEET, AS NOTED BY N. S. WENDLING, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS. THE ROAD WAS RECORDED ON JANUARY 1, 1916 BY W. G. RUGGLES, COUNTY SURVEYOR.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) BEGINNING AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 19-17-10; THENCE WESTWARD ON THE SECTION LINE TO THE NEOSHO RIVER; THENCE SWERVING AROUND SAID RIVER TO THE NORTH AND BACK TO THE SECTION LINE AFTER CROSSING WRIGHTS CREEK
- 11) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 6, 2006, FOR PROJECT NUMBER 06161-02, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE SET BY ALVA J. SMITH IN 1900 AT THE NORTH 1/4 CORNER OF SECTION 30-17-10 AS RECORDED IN SURVEY BOOK "E" ON PAGE 182, BUT HE DID **NOT** FIND THE STONE. HE DEEMED THAT THE NORTH 1/4 CORNER OF SECTION 30-17-10 WAS **LOST**. HE DID **NOT** REMONUMENT THE POSITION AT THIS TIME AS THE LOCATION FOR THIS CORNER FALLS IN CULTIVATION. HE DETERMINED A **THEORETICAL POSITION** FOR THE NORTH 1/4 CORNER OF SECTION 30-17-10.  
THE DRAWING ON HIS REFERENCE REPORT SHOWS THE FOLLOWING:
- 1) N. 89°57'48" W. AT 2,640.00' TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 30-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE
  - 2) S. 89°57'48" E. AT 2,541.23' TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 30-17-10
- NORTH QUARTER CORNER 30-17-10