

**NORTHWEST CORNER SECTION 30, TOWNSHIP 17 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 36 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 12" X 3"** FOR THE CORNER TO SECTIONS 19 & 30-17-10 ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 38.25 CHAINS EAST TO THE 18" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19 & 30-17-10
- 2) 78.25 CHAINS EAST TO THE 14" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-17-10
- 3) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE TO THE 18" X 12" X 3" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 30-17-10
- 4) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE TO THE 14" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 30 & 31-17-10

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 47 OF THE 8<sup>TH</sup> TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 104 AND DATED OCTOBER 16, 1874 TO FOR THE SUBDIVISION OF SECTION 19-17-10, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 30-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 2,561' EAST TO THE 16" X 12" X 6" STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 30-17-10
- 2) 5,201' EAST TO THE STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 30-17-10

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 119 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 62 TO 64 PETITIONED BY J. A. STANLEY AND OTHERS FOR A COUNTY ROAD ON THE LYON/MORRIS COUNTY LINE BETWEEN TOWNSHIPS 17-9 AND 17-10 [PACKET 380 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 23, 1878, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD, **EXCEPT** AT THE CROSSING OF THE NEOSHO RIVER [IN SECTION 25-17-9] WHERE IT WILL BE 100 FEET WIDE, ON JULY 8, 1881 AS NOTED BY J. M. GRIFFITH, CHAIRMAN OF THE LYON COUNTY BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JULY 13, 1881 BY WILLIAM F. EWING, LYON COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 19-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE ON THIS ROAD SURVEY ON THE COUNTY LINE.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE COUNTY LINE TO THE NORTHWEST CORNER OF SECTION 18-17-10 AT THE TERMINUS OF THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS WEST ON THE SECTION LINE INTO CHASE COUNTY FOR 1,320 FEET; THEN EXTENDS SOUTH ON THE 1/4/4 SECTION LINE FOR 2,640 FEET [SURVEY NOTE CALLS FOR 5,280 FEET]; THEN EXTENDS EAST ON THE 1/2 SECTION LINE FOR 1,320 FEET TO THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 30-17-10 ON THE COUNTY LINE; THEN EXTENDS SOUTH ON THE COUNTY LINE TO THE SOUTHWEST CORNER OF SECTION 31-17-10 AT THE TOWNSHIP CORNER TO COMMENCE THIS ROAD SURVEY

CONTINUED ON PAGE 2

- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A **PERMANENT SURVEY** RECORDED IN THE REGISTER OF DEEDS OFFICE, SURVEY F30001 IN THE SURVEY FILE FOR TOWNSHIP 17-10 DATED APRIL 26-30, 1880 TO ESTABLISH THE NORTHEAST CORNER OF THE SOUTHEAST 1/4, THE NORTH CORNER OF THE SOUTHEAST 1/4, THE NORTHWEST CORNER OF THE SOUTHWEST 1/4, THE NORTHWEST CORNER OF THE NORTHWEST 1/4, AND THE NORTH CORNER OF THE NORTHWEST 1/4 IN SECTION 31-17-10, AND ALSO THE SOUTH CORNER OF THE NORTHWEST 1/4 AND THE NORTHEAST CORNER AND THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 30-17-10, SAID THAT **HE PLANTED A STAKE** FOR THE PERMANENT NORTHWEST CORNER OF SECTION 30-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 20.00 CHAINS SOUTH ON THE RANGE LINE AND THE COUNTY LINE TO THE GOVERNMENT 1/16<sup>TH</sup> ROCK HE PLANTED ON THIS PERMANENT SURVEY
  - 2) 40.00 CHAINS SOUTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STAKE HE SET FOR THE TEMPORARY WEST 1/4 CORNER OF SECTION 30-17-10
  - 3) 80.00 CHAINS SOUTH ON THE RANGE LINE AND THE COUNTY LINE TO THE SOUTHWEST CORNER OF SECTION 30-17-10 THAT HE ESTABLISHED FROM WITNESS TREES
- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, BY C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 126 DATED APRIL 12, 1882 AT THE REQUEST OF P. BOSTIAN TO SURVEY AND ESTABLISH IN TOWNSHIP 17, RANGE 10, THE 1/4 CORNER AND THE 1/8<sup>TH</sup> CORNER ON THE WEST LINE OF SECTION 19 AND THE 1/8<sup>TH</sup> CORNER BETWEEN THE CENTER CORNER AND THE 1/4 CORNER ON THE SOUTH LINE, AND SUCH OTHER LINES AND CORNERS AS NECESSARY TO COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 19-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
- 1) 17.71-1/2 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/8<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 19-17-10
  - 2) 37.71-1/2 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 19-17-10
  - 3) 20.05 CHAINS NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE SET FOR THE PERMANENT WEST 1/8<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 19-17-10
  - 4) 40.10 CHAINS NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 19-17-10
  - 5) 60.15 CHAINS NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE SET FOR THE PERMANENT WEST 1/8<sup>TH</sup> CORNER OF THE NW1/4 OF SECTION 19-17-10
  - 6) 80.20 CHAINS NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 19-17-10
- 6) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 126 AND DATED APRIL 1882, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 30-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE ON THIS **PERMANENT SURVEY**.
- 7) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 14 FOR A ROAD IN TOWNSHIP 17, RANGE 10, DATED JUNE 8, 1882, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF

SECTION 19-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE ON THIS ROAD SURVEY.

HIS NOTES SHOWS THE FOLLOWING INFORMATION:

1) 86 RODS EAST ON THE SECTION LINES TO THE STONE HE SET TO COMMENCE THIS ROAD SURVEY AND TO BEGIN A DEVIATION TO THE NORTH, AND THEN INTERSECTS THE SECTION LINE AT THE STONE HE SET AT 10.77 CHAINS WEST OF THE STONE THAT HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 19-17-10, AND THEN CONTINUE EAST ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 19-17-10 TO END THIS ROAD SURVEY

- 8) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 176 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 290 TO 292 PETITIONED BY P. BOSTIAN AN OTHERS FOR THE VACATION AND RELOCATION OF A COUNTY ROAD IN SECTION 19-17-10 [PACKED 414 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE] THAT HE SURVEYED ON JUNE 8, 1882, WAS ESTABLISHED AS A 40 FOOT ROAD ON JULY 14, 1882 AS NOTED BY HUGH F. HOLMES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JULY 22, 1882 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 19-17-10 ON THE RANGE LINE AND LYON AND MORRIS COUNTY LINE AS HE BEGAN THIS ROAD SURVEY AT **86 RODS WEST** OF THIS CORNER.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

1) EAST ON THE SECTION LINES FOR 86 RODS TO THE STONE HE SET TO BEGIN THIS ROAD SURVEY; THENCE N. 35° E. FOR 2,40 CHAINS TO AN ANGLE STONE HE SET; THENCE S. 81° E. FOR 3 CHAINS TO AN ANGLE STONE HE SET; THENCE S. 73° E. FOR 1.97 CHAINS TO THE STONE HE SET ON THE SECTION LINE; THENCE EAST ON THE SECTION LINE FOR 10.77 CHAINS TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 19-17-10 AT THE TERMINUS OF THIS ROAD SURVEY

- 9) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 2, A **PERMANENT SURVEY** WITH THE MORRIS COUNTY SURVEYOR RECORDED IN SURVEY BOOK "E" ON PAGE 182 DATED MARCH 27, 1900 AT THE ORDER OF W. H. ROBINSON TO SURVEY GOVERNMENT LOT 2 IN THE NORTHWEST 1/4 OF SECTION 30-17-10, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 30-178-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 19.97-1/2 CHAINS SOUTH ON THE RANGE LINE AND THE COUNTY LINE TO THE 2-1/2" X 4" X 20" STONE HE SET FOR THE PERMANENT WEST 1/8<sup>TH</sup> CORNER OF THE NW1/4 OF SECTION 30-17-10
- 2) 39.95 CHAINS SOUTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 30-17-10
- 3) 18.31 CHAINS EAST TO THE 4" X 8" X 16" STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF GOVERNMENT LOT 2
- 4) 38.65 CHAINS EAST TO THE 5" X 9" X 16" STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 30-17-10
- 5) 78.52 CHAINS EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 30-17-10

- 10) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 28, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 209 DATED AUGUST 20, 1901 ORDERED BY JOHN GUTHRIE TO MAKE SUCH A SURVEY AS MAY BE NECESSARY TO LOCATE AND PERMANENTLY ESTABLISH THE LINE BETWEEN THE NORTH 1/2 AND THE SOUTH 1/2 OF SECTION 19-17-10, SHOWS

ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 19-19-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE ON THIS **PERMANENT SURVEY**. THERE IS ADDITIONAL INFORMATION IN PACKET "M 54" IN MISCELLANEOUS DRAWER NUMBER 2 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

- 11) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 61 IN A NOTICE FROM ARTHUR SMITH, MORRIS COUNTY SURVEYOR, FOR A SURVEY TO ESTABLISH THE SOUTHEAST CORNER OF SECTION 36-17-9, IT HAVING BEEN CLAIMED THAT THE GOVERNMENT STONE HAD BEEN MOVED WEST OF ITS ORIGINAL POSITION SAID THAT HE MET WITH THE MORRIS COUNTY AND CHASE COUNTY SURVEYORS ON APRIL 26, 1910 TO BEGIN THIS SURVEY ON THE LYON-MORRIS-CHASE COUNTY LINE. **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 30-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE ON THIS **PERMANENT SURVEY**. HE USED THIS STONE TO VERIFY THE ORIGINAL POSITION OF THE GOVERNMENT STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 31-17-10. THE SURVEY WAS COMPLETED ON MAY 13, 1910 AND ENTERED ON MAY 17, 1910.
  
- 12) W. S. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN LARGE SURVEY SR #18001 IN THE SURVEY DRAWER FOR TOWNSHIP 17-10, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 19-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE. HIS NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,646' NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE SET FOR THE WEST 1/4 CORNER OF SECTION 19-17-10
  - 2) 5,292' NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE SET FOR THE NORTHWEST CORNER OF SECTION 19-17-10
  
- 13) W. S. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 92 BY NOTICE FROM DAVID WATERS TO PERMANENTLY ESTABLISH THE WEST LINE OF SECTIONS 18 & 19, TOWNSHIP 17 SOUTH, RANGE 10 EAST ON THE MORRIS COUNTY LINE SAID THAT **HE FOUND THE STONE IN PLACE** AT THE SOUTHWEST CORNER OF SECTION 19-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE ON THIS **PERMANENT SURVEY**. THE FIELD SURVEY WAS ON APRIL 14 & 15, 1915. HIS NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,646' NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 19-17-10
  - 2) 5,292' NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 19-17-10
  - 3) 7,938' NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 18-17-10
  - 4) 9,261' NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE FOUND IN PLACE AT THE WEST 1/8<sup>TH</sup> CORNER OF THE NW1/4 OF SEC. 18-17-10
  - 5) 10,584' NORTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 18-17-10
  
- 14) COMMISSIONER'S ROAD JOURNAL BOOK "A", PAGE 120  
ON JANUARY 29, 1930 A PETITION SIGNED BY C. F. HARRIS AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 17-10 WAS PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS. THE ROAD WAS VIEWED ON FEBRUARY 24, 1930, AND THE FINAL ORDER WAS ISSUED ON MARCH 29, 1930 THAT THE ROAD BE **VACATED** AS PETITIONED FOR:

- 1) BEGINNING ON THE SECTION LINE AT 925 FEET WEST OF THE SOUTHEAST CORNER OF SECTION 19-17-10; FROM THENCE WEST ON THE SECTION LINE OF SAID SECTION 19 TO THE NEOSHO RIVER; THENCE SWERVING AROUND SAID RIVER TO THE NORTH AND BACK TO THE SECTION LINE AFTER CROSSING WRIGHTS CREEK; THENCE WEST ON THE SOUTH LINE OF SAID SECTION 19 TO THE SOUTHWEST CORNER OF SAID SECTION 19-17-10 AND ENDING THERE
  - 2) SAID ROAD SHOULD BE VACATED
  - 3) THE ABOVE ROAD IS NOT USED AND WOULD BE SELDOM BE USED IF IT WERE MADE PASSABLE.
  - 4) THE EXPENSE TO THE TOWNSHIP AND COUNTY WOULD BE VERY HEAVY TO MAKE IT PASSABLE
- 15) O. D. HENRY, COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 737 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 96 PETITIONED BY C. F. HARRIS AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 17-10 THAT WAS VIEWED BY THE COUNTY COMMISSIONERS AND THE COUNTY SURVEYOR ON MARCH 29, 1930 AND THE VIEWERS RECOMMENDED THAT THE ROAD SHOULD BE **VACATED** AS THE ROAD IS NOT USED AND WOULD BE SELDOM USED IF IT WERE MADE PASSABLE. THE EXPENSE TO THE TOWNSHIP AND THE COUNTY WOULD BE VERY HEAVY TO MAKE IT PASSABLE;  
**THE FOLLOWING ROAD WAS VACATED:**  
BEGINNING ON THE SECTION LINE AT 925 FEET WEST OF THE SOUTHEAST CORNER OF SECTION 19-17-10; FROM THENCE WEST ON THE SECTION LINE OF SAID SECTION 19 TO THE NEOSHO RIVER; THENCE SWERVING AROUND SAID RIVER TO THE NORTH AND BACK TO THE SECTION LINE AFTER CROSSING WRIGHTS CREEK; THENCE WEST ON THE SOUTH LINE OF SAID SECTION 19 TO THE SOUTHWEST CORNER OF SAID SECTION 19-17-10 AND ENDING THERE.
- 16) IN A BROWN FIELD BOOK LABELED "MJH MISC. 1966-1967" IN THE VAULT IN THE COUNTY ENGINEERS OFFICE FOR THE HARRIS SURVEY DATED APRIL 4, 1967 ON PAGE 66, IT SAID THAT **THEY FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 30-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE **AT 20 FEET EAST OF A STONE POST.**
- 17) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 15, 1983, SAID THAT **HE FOUND THE 3" X 12" GLO LIMESTONE AT 8" DEEP** AT THE NORTHWEST CORNER OF SECTION 30-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE. **HE SET A 1/2" REBAR ON THE WEST SIDE OF THE STONE, BENT OVER THE CENTER OF THE STONE, AND HE SET A 5/8" REBAR ON THE EAST SIDE AT THE CENTER OF THE STONE.**
- 1) 19.4' WEST TO THE BASE OF A STONE CORNER POST
  - 2) 50.0' EAST TO A 1/2" REBAR IN THE TRAVELED WAY OF A TRAIL TO THE EAST
  - 3) 50.0' NNE TO A 1/2" REBAR IN THE TRAVELED WAY OF A TRAIL NORTH-SOUTH
- HIS DRAWING ON HIS REFERENCE REPORT SHOWS THE FOLLOWING:**
- 1) 2,636.5' SOUTH ON THE RANGE LINE AND THE COUNTY LINE TO THE 5/8" SQUARE IRON PIN HE FOUND AT THE WEST 1/4 CORNER OF SECTION 30-17-10
  - 2) 5,284.75' SOUTH ON THE RANGE LINE AND THE COUNTY LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 30-17-10
- 18) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 8, 1985, FOR PROJECT NUMBER 85142, SAID THAT **HE FOUND THE 3" X 12" GLO LIMESTONE WITH A REBAR BENT OVER THE STONE** AT THE SOUTHWEST CORNER OF SECTION 19-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE FROM HIS EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE DATED MARCH 1983.

HIS TIES ARE ON PAGE 6

- 1) 19.4' WEST TO THE BASE OF A STONE CORNER POST
  - 2) 50.0' EAST TO #4 REBAR IN A TRAIL TO THE EAST
  - 3) 50.0' NNE TO #4 REBAR IN A TRAIL TO THE NORTH-SOUTH
  - 4) IN LINE WITH A TREE ROW TO THE WEST
- 19) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 6, 2006, FOR PROJECT NUMBER 06061-02, SAID THAT **HE FOUND THE 3" X 12" GLO STONE** AT THE NORTHWEST CORNER OF SECTION 30-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE IN NOVEMBER 1985.
- 1) 1/2" REBAR ON THE WEST SIDE AND BENT OVER THE TOP OF THE STONE
  - 2) 16.0' WEST TO A 40 D NAIL & WASHER IN A 14" HACKBERRY TREE
  - 3) 50.0' EAST TO A 1/2" REBAR
  - 4) 50.0' NORTH TO A 1/2" REBAR IN THE DIRT ROAD NORTH-SOUTH
  - 5) 5,181.23' EAST TO THE STONE FOUND AT THE NORTHEAST CORNER OF SEC. 30
- HIS DRAWING ON THE REFERENCE REPORT SHOWS THE FOLLOWING:
- 1) 2,640.00' EAST TO THE LOCATION FOR THE NORTH 1/4 CORNER OF SECTION 30-17-10 – **NOT MONUMENTED** AS IT FALLS IN CULTIVATION
  - 2) 5,181.23' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 30-17-10

NORTHWEST CORNER 30-17-10