

WEST 1/4 CORNER SECTION 32, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) ON PAGE 160 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 16" X 2-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 31 & 32-17-10.

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A **PERMANENT SURVEY** RECORDED IN THE REGISTER OF DEEDS OFFICE, SURVEY F30001 IN THE SURVEY FILE FOR TOWNSHIP 17-10 DATED APRIL 26-30, 1880 TO ESTABLISH THE NORTHEAST CORNER OF THE SOUTHWEST 1/4, THE NORTH CORNER OF THE SOUTHWEST 1/4, THE NORTHWEST CORNER OF THE SOUTHWEST 1/4, THE NORTHWEST CORNER OF THE NORTHWEST 1/4, AND THE NORTH CORNER OF THE NORTHWEST 1/4 IN SECTION 31-17-10, AND ALSO THE SOUTH CORNER OF THE NORTHWEST 1/4 AND THE NORTHEAST CORNER AND THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 30-17-10, SAID THAT **HE SET A STONE** FOR THE EAST 1/4 CORNER OF SECTION 31-17-10 EQUIDISTANT BETWEEN THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 31-17-10 AND THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 31-17-10 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.09-1/2 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 31-17-10 ON THE TOWNSHIP LINE
 - 2) 40.09-1/2 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 31-17-10
 - 3) 60.15 CHAIN NORTH TO THE TEMPORARY STAKE HE SET FOR THE EAST 1/16TH CORNER OF THE SE1/4 OF SECTION 30-17-10
 - 4) 80.20-1/2 CHAINS NORTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 30-17-10
 - 5) 79.92 CHAINS WEST TO THE STONE SET FOR THE WEST 1/4 CORNER OF SECTION 30-17-10

- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 158, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 158 DATED FEBRUARY 7, 1887 ORDERED BY H. P. HOOD TO PERMANENTLY ESTABLISH THE 1/8TH CORNER ON THE NORTH SIDE OF THE SOUTHWEST 1/4 OF SECTION 32-17-10, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 32-17-10 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,312' EAST TO THE 5" X 6" X 18" YELLOW LIMESTONE MARKED "1/8" HE SET FOR THE PERMANENT NORTH 1/8TH CORNER OF THE SW1/4 OF SECTION 32-17-10
 - 2) 2,624' EAST TO THE STONE HE FOUND AT THE CENTER CORNER OF SECTION 32-17-10

- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 159, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 159 DATED FEBRUARY 9-12, 1887 ORDERED BY J. J. DOTY AND SAMUEL HASSINGER TO LOCATE THE LINES AND CORNERS FOR ALL PARTIES OWNING LAND IN THE NORTHWEST 1/4 OF SECTION 32-17-10, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 32-17-10 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,321' NORTH TO THE TEMPORARY STAKE HE SET FOR THE WEST 1/8TH CORNER ON THE WEST SIDE OF THE NW1/4 OF SECTION 32-17-10
 - 2) 2,312' NORTH TO THE 7" X 4" X 20" LIMESTONE HE SET FOR A PERMANENT PROPERTY CORNER

HIS INFORMATION IS CONTINUED ON PAGE 2

- 3) 2,642' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 32-17-10
 - 4) 1,312' EAST TO THE LIMESTONE HE FOUND AT THE SOUTH 1/8TH CORNER OF THE NW1/4 OF SECTION 32-17-10
 - 5) 2,624' EAST TO THE STONE HE FOUND AT THE CENTER CORNER OF SECTION 32-17-10
- 5) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 5, 1983, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER OVER A WIDE AREA FOR THE STONE AT THE WEST 1/4 CORNER OF SECTION 32-17-10, BUT HE DID **NOT** FIND THE STONE. HE DID **NOT** RESET THE WEST 1/4 CORNER OF SECTION 32-17-10 AT THIS TIME, BUT HE NOTED THAT THE LINE OF FENCE TO THE WEST APPEARS TO BE "REASONABLE".

WEST QUARTER CORNER 32-17-10