

CENTER CORNER SECTION 33, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) TIM SLOAN, L.S. 783, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 7, 1992, FOR LARGE SURVEY SR #3302 IN THE SURVEY DRAWER FOR TOWNSHIP 17-10, SAID THAT **HE SET A 1/2" X 24" REBAR WITH HIS CAP AT 6" DEEP** FOR THE CENTER CORNER OF SECTION 33-17-10. HIS FIELD NOTES ATTACHED TO THE SURVEY SAID: "I COULDN'T FIND ANY EVIDENCE OF ANY RECORDS SHOWING THIS CORNER HAD BEEN SET. I SET THIS CORNER BY THE STANDARD PROCEDURE AT THE INTERSECTION OF LINES BETWEEN OPPOSING QUARTER CORNERS. THE PHYSICAL EVIDENCE IN THE FIELD CORRESPONDS WITH THIS LOCATION."

- 1) 3.3' SSE TO A SPIKE IN A 30" HEDGE TREE
- 2) 8.8' SSW TO A SPIKE IN A 50" HEDGE TREE
- 3) 6.8' WNW TO A SPIKE IN A 30" ELM TREE

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,324.94' WEST TO THE 1/2" CAPPED REBAR HE SET FOR THE NORTH 1/16TH CORNER OF THE SW1/4 OF SECTION 33-17-10
- 2) 2,649.88' WEST TO THE 1/2" CAPPED REBAR HE SET FOR THE WEST 1/4 CORNER OF SECTION 33-17-10
- 3) 2,641.30' NORTH TO THE 1/2" SQUARE REBAR HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 33-17-10
- 4) 2,642.74' EAST TO THE 1/2" SQUARE REBAR HE FOUND AT THE EAST 1/4 CORNER OF SECTION 33-17-10
- 5) 1,306.17' SOUTH TO THE THEORETICAL LOCATION FOR THE EAST 1/16TH CORNER OF THE SW1/4 OF SECTION 33-17-10
- 6) 2,612.34' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 33-17-10 ON THE TOWNSHIP LINE

CENTER CORNER 33-17-10