

CENTER CORNER OF SOUTHWEST 1/4 SECTION 33, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) EDWIN J. COOK, IN LARGE SURVEY SR #33001 IN THE SURVEY FILE FOR TOWNSHIP 17-10, BUT NOT DATED, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND A STONE** AT THE CENTER CORNER OF THE NORTHWEST 1/4 OF SECTION 33-17-10.
HIS DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,321.6' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/16TH CORNER OF THE SW1/4 OF SECTION 33-17-10 ON THE TOWNSHIP LINE

- 2) TIM SLOAN, L.S. 783, IN LARGE SURVEY SR #33002 IN THE SURVEY DRAWER FOR TOWNSHIP 17-10 DATED FEBRUARY 1992, SAID THAT **HE SET A 1/2" X 24" REBAR WITH HIS CAP** FOR THE CENTER CORNER OF THE SOUTHWEST 1/4 OF SECTION 33-17-10 AT THE INTERSECTION OF THE LINES FROM THE OPPOSITE 1/16TH CORNERS OF THE SOUTHWEST 1/4 OF SECTION 33-17-10. HIS FIELD NOTES ATTACHED TO THE SURVEY SAID: "I CHAINED NORTH FROM THE SW COR. SE1/4 SW1/4 A DISTANCE OF 1321' TO SEARCH FOR THIS CORNER. WE SEARCHED AND DUG FOR THIS CORNER BUT COULD NOT FIND IT. WHEN THE TRAVERSE WAS COMPLETED AND THIS CORNER WAS SET IN THE FIELD, WE MADE ANOTHER SEARCH FOR THIS CORNER. WE DUG FOR THE STONE IN THE AREA WE SET THIS CORNER AND NORTH OF THIS POSITION. NOTHING WAS FOUND. THIS CORNER WAS SET BY THE STANDARD METHOD USED TO SUBDIVIDE A SECTION."
HIS DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,327.86' WEST TO THE 1/2" CAPPED REBAR HE SET FOR THE WEST 1/16TH CORNER OF THE SW1/4 OF SECTION 33-17-10
 - 2) 1,311.52' NORTH TO THE 1/2" CAPPED REBAR HE SET FOR THE NORTH 1/16TH CORNER OF THE SW1/4 OF SECTION 33-17-10
 - 3) 1,327.86' EAST TO THE THEORETICAL LOCATION FOR THE EAST 1/16TH CORNER OF THE SE1/4 OF SECTION 33-17-10
 - 4) 1,311.52' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/16TH CORNER OF THE SW1/4 OF SECTION 33-17-10 ON THE TOWNSHIP LINE

CENTER CORNER SOUTHWEST QUARTER 33-17-10