

**NORTH 1/16 CORNER OF THE NORTHEAST 1/4 SECTION 33, TOWNSHIP 17 SOUTH,
RANGE 10 EAST**

- 1) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 86 RECORDED IN SURVEY BOOK "A" ON PAGE 181 DATED FEBRUARY 8, 1869 FOR A SURVEY OF LAND OWNED BY A. G. EDMISTON, BEING THE SOUTHWEST 1/4 AND THE WEST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 28-17-10, SAID THAT **HE SET A STONE FOR THE SOUTH 1/2/4 CORNER OF THE SOUTHEAST 1/4 OF SECTION 28-17-10 EQUIDISTANT BETWEEN THE STONE THAT HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 28-17-10 AND THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 28-17-10 ON THIS SURVEY.**

- 2) STEVEN S. BROSEMER, L.S. 752, IN A SURVEY DATED MARCH 11, 1985 FOR A SURVEY OF A 18.92 ACRE TRACT IN THE EAST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 28-17-10, RECORDED IN VOLUME 413 ON PAGE 885 IN THE REGISTER OF DEEDS OFFICE ON MARCH 18, 1885, AND SURVEY F28001 IN THE SURVEY FILE FOR TOWNSHIP 17-10, SAID THAT **HE FOUND A 5" X 15" X 12" LIMESTONE AT 12" DEEP WITH A NOTCH CUT ON THE EAST SIDE ATTRIBUTABLE TO COUNTY SURVEYOR D. T. McAULEY IN 1869 AT THE SOUTH 1/16TH CORNER OF THE SOUTHEAST 1/4 OF SECTION 28-17-10. HE PLACED CAPPED REBARS ON THE NORTH AND SOUTH SIDES OF THE STONE AND AT THE CENTER OF THE STONE.**
 - 1) 22.0' NORTH TO A CORNER FENCE POST
 - 2) 2.0' SOUTH TO THE TRAVELED WAY OF THE ROAD EAST-WEST
 - 3) 1.0' WEST TO A LINE OF FENCE TO THE NORTH-EXTENDED

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 2,663.06' NORTH TO THE CALCULATED POSITION FOR THE NORTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 28-17-10
 - 2) 1,316.15' EAST TO THE #5 SQUARE REBAR HE FOUND AT THE SOUTHEAST CORNER OF SECTION 28-17-10

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 14, 1989, SAID THAT **HE FOUND THE 5" X 15" X 12" LIMESTONE ATTRIBUTABLE TO COUNTY SURVEYOR D. T. McAULEY WITH REBARS ON THE NORTH AND SOUTH SIDES AT THE NORTH 1/16TH CORNER OF THE NORTHEAST 1/4 OF SECTION 33-17-10 FROM HIS EXISTING TIES DATED MARCH 1985.**
 - 1) 22.0' NORTH TO A CORNER FENCE POST
 - 2) 2.0' SOUTH TO THE TRAVELED WAY OF THE ROAD EAST-WEST
 - 3) 1.0' WEST TO A LINE OF FENCE TO THE NORTH-EXTENDED

NORTH SIXTEENTH CORNER NORTHEAST QUARTER 33-17-10