

NORTHWEST CORNER SECTION 33, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) ON PAGE 156 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 12" X 5"** FOR THE CORNER TO SECTIONS 28, 29, 32 & 33-17-10.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 39.87 CHAINS EAST TO THE 24" X 14" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 28 & 33-17-10
- 2) 79.75 CHAINS EAST TO THE 16" X 12" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 27, 28, 33 & 34-17-10
- 3) 30.30 CHAINS WEST TO THE 18" X 14" X 4" LIMESTONE THEY SET ON THE EAST BOUNDARY OF THE KANSAS INDIAN DIMINISHED RESERVE
- 4) 40.13 CHAINS WEST TO THE 16" X 14" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 29 & 32-17-10
- 5) 80.26 CHAINS WEST TO THE 16" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 29, 30, 31 & 32-17-10

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 86 RECORDED IN SURVEY BOOK "A" ON PAGE 181 DATED FEBRUARY 8, 1869 FOR A SURVEY OF LAND OWNED BY A. G. EDMISTON, BEING THE SOUTHWEST 1/4 AND THE WEST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 28-17-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 28-17-10 ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 160 RODS NORTH TO THE STONE HE SET FOR THE WEST 1/4 CORNER OF SECTION 28-17-10
- 2) 320 RODS NORTH TO THE STONE HE SET FOR THE NORTHWEST CORNER OF SECTION 28-17-10
- 3) 314 RODS, 4 LINKS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 28-17-10

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 48 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 105 DATED OCTOBER 28, 1874 TO SUBDIVIDE SECTION 29-17-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 29-17-10 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 2,630' WEST TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 29-17-10-17-10
- 2) 3,945' WEST TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/8TH CORNER OF THE SW1/4 OF SECTION 29-17-10
- 3) 5,260' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-17-10
- 4) 1,343-1/2' NORTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/8TH CORNER OF THE SE1/4 OF SECTION 29-17-10
- 5) 2,687' NORTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 29-17-10

- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 236 & 237 FOR A PETITION BY R. K. STEVENSON AND OTHERS FOR THREE ROADS IN TOWNSHIP 17-10 [PACKET 185 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MAY 15 & 23, 1876, AND WERE ESTABLISHED AS 50 FEET WIDE ON JULY 5, 1876, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 29-17-10 TO COMMENCE THE SECOND ROAD ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) THE SECOND ROAD EXTENDS NORTH ON THE SECTION LINES FOR 2,279 FEET TO INTERSECT THE AMERICUS AND COUNCIL GROVE ROAD AT THE TERMINUS OF THE SECOND ROAD ON THIS ROAD SURVEY
 - 2) THE FIRST ROAD EXTENDS WEST ON THE SECTION LINES FOR 2,661' TO A TURN TO THE NORTHERLY DUE TO THE NEOSHO RIVER
 - 3) THE FIRST ROAD EXTENDS EAST ON THE SECTION LINES FOR 2,670' TO INTERSECT THE AMERICUS AND COUNCIL GROVE ROAD AT THE TERMINUS OF THE FIRST ROAD ON THIS ROAD SURVEY
- 5) REA BOOK 30 ON PAGE 17 SAYS THAT **THEY DROVE AN IRON PIN** FOR THE SOUTHWEST CORNER OF SECTION 28-17-10 IN THE CENTER OF THE INTERSECTION. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
- 1) 33' NW TO A WITNESS PIN
 - 2) 37' SW TO A WITNESS PIN
- 6) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 17-10 SHOWS A **REA PIN** AT THE "SW CORNER SECTION 28-17-10". **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
- 1) 33' NORTH TO A WITNESS
 - 2) 37' SW TO A WITNESS
- 7) EDWIN J. COOK, IN LARGE SURVEY SR #33001 IN THE SURVEY FILE FOR TOWNSHIP 17-10, BUT NOT DATED, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND AN IRON PIN** AT THE NORTHWEST CORNER OF SECTION 33-17-10. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,321.19' EAST TO THE IRON PIN AT THE NORTH 1/16TH CORNER OF THE NW1/4 OF SECTION 33-17-10
 - 2) 5,287.5' EAST TO THE IRON PIN AT THE NORTHEAST CORNER OF SEC. 33-17-10
 - 3) 1,320' SOUTH TO THE IRON PIN AT THE WEST 1/16TH CORNER OF THE NW1/4 OF SECTION 33-17-10
 - 4) 3,960' SOUTH TO THE STONE HE FOUND AT THE WEST 1/16TH CORNER OF THE SW1/4 OF SECTION 33-17-10
 - 5) 5,280' SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 33-17-10 ON THE TOWNSHIP LINE
- 8) TIM SLOAN, L.S. 783, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 7, 1992, LARGE SURVEY SR #33002 IN THE SURVEY DRAWER FOR TOWNSHIP 17-10, SAID THAT **HE FOUND A 1/2" SQUARE REBAR** AT THE NORTHWEST CORNER OF SECTION 33-17-10. HIS FIELD NOTES ATTACHED TO THE SURVEY SAID THAT: "I FOUND REFERENCES FOR THIS CORNER IN THE CO. ENG. OFFICE. I THOUGHT I HAD A COPY OF THEM UNTIL I BEGAN MY FIELD RESEARCH WHEN I DISCOVERED THAT I DID NOT. I MADE A RATHER EXHAUSTIVE SEARCH FOR THIS CORNER, BUT COULD NOT FIND ANY EVIDENCE. I DID NOT THINK THE GLO STONE WAS STILL IN PLACE BECAUSE THERE ARE TWO CULVERTS CROSSING THE INTERSECTION AT THIS LOCATION. WHEN I RETURNED TO THE OFFICE I CONTACTED THE LYON CO. ENG. OFFICE BY PHONE AND THEY GAVE ME THE REFERENCES OVER THE PHONE. WHEN WE RETURNED TO TRAVERSE THE SECTION, WE FOUND BOTH REFERENCES AND THE MONUMENT OF RECORD. AFTER REDUCING THE TRAVERSE AND JUDGING THE SUPPORTING EVIDENCE FROM THE OTHER CORNERS, I ACCEPTED THIS MONUMENT AS THE NW CORNER S. 33."

HIS TIES ARE ON PAGE 3

- 1) 22.6' NE TO THE NORTH SIDE OF A 24" NORTH-SOUTH CORRUGATED METAL PIPE CULVERT
- 2) 33.0' NW TO A 1/2" SQUARE IRON PIN
- 3) 37.0' SW TO A 1/2" SQUARE IRON PIN

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,637.95' EAST TO THE 1/2" SQUARE REBAR HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 33-17-10
- 2) 5,276.13' EAST TO THE 1/2" SQUARE REBAR HE FOUND AT THE NORTHEAST CORNER OF SECTION 33-17-10
- 3) 2,633.77' SOUTH TO THE 1/2" CAPPED REBAR HE SET FOR THE WEST 1/4 CORNER OF SECTION 33-17-10
- 4) 3,950.66' SOUTH TO THE 1/2" CAPPED REBAR HE SET FOR THE WEST 1/16TH CORNER OF THE SW1/4 OF SECTION 33-17-10
- 5) 5,267.55' SOUTH TO THE 1/2" CAPPED REBAR HE SET FOR THE SOUTHWEST CORNER OF SECTION 33-17-10 ON THE TOWNSHIP LINE

NORTHWEST CORNER 33-17-10