

WEST 1/4 CORNER SECTION 33, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) ON PAGE 156 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 12" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 32 & 33-17-10, FROM WHICH:
 - 1) A HICKORY TREE 12" IN DIAMETER BEARS S. 73-1/2° W. AT 11 LINKS DISTANCE
 - 2) NO OTHER TREES CONVENIENT TO MARK

- 2) TIM SLOAN, L.S. 783, IN A LAND SURVEY REFERENCE DATED FEBRUARY 7, 1992, LARGE SURVEY SR #33002 IN THE SURVEY DRAWER FOR TOWNSHIP 17-10, SAID THAT HE DEEMED THAT THE WEST 1/4 CORNER OF SECTION 33-17-10 WAS **LOST**. **HE SET A 1/2" X 24" REBAR WITH HIS CAP AT 1 FOOT DEEP** FOR THE WEST 1/4 CORNER OF SECTION 33-17-10 ON TRUE LINE AND HALFWAY BETWEEN THE NORTHWEST AND SOUTHWEST CORNERS OF SECTION 33-17-10. HIS FIELD NOTES ATTACHED TO THE SURVEY SAID: "WE CHAINED SOUTH FROM THE NW COR. S 33 AD DISTANCE OF 2,640 AND BEGAN OUR SEARCH IN THIS AREA. WE DUG AND SEARCHED IN THIS AREA, BUT WE FOUND NOTHING. THERE WASN'T ANY VISIBLE EVIDENCE OF THIS CORNER'S LOCATION. MR. COOK'S SURVEY MAKES NO MENTION OF THIS CORNER'S LOCATION. I DETERMINED THIS CORNER TO BE **LOST** AND SET IT ON TRUE LINE AND ONE-HALF DISTANCE BETWEEN THE NW CORNER AND THE SW CORNER S. 33. WE SEARCHED THE AREA AGAIN AT THE TIME WE SET THE REBAR AT THE W1/4 CORNER."
 - 1) 12.4' NE TO A SPIKE & WASHER IN A 50" ASH TREE
 - 2) 31.6' SOUTH TO A SPIKE & 2 WASHERS IN A 30" HACKBERRY TREE
 - 3) 31.6' EAST TO A SPIKE & 3 WASHERS IN A 50" HACKBERRY TREE

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 1,316.89' SOUTH TO THE 1/2" CAPPED REBAR HE SET FOR THE WEST 1/16TH CORNER OF THE SW1/4 OF SECTION 33-17-10
 - 2) 2,633.78' SOUTH TO THE 1/2" CAPPED REBAR HE SET FOR THE SOUTHWEST CORNER OF SECTION 33-17-10 ON THE TOWNSHIP LINE
 - 3) 2,633.77' NORTH TO THE 1/2" SQUARE REBAR HE FOUND AT THE NORTHWEST CORNER OF SECTION 33-17-10
 - 4) 1,324.94' EAST TO THE 1/2" CAPPED REBAR HE SET FOR THE NORTH 1/16TH CORNER OF THE SW1/4 OF SECTION 33-17-10
 - 5) 2,649.88' EAST TO THE 1/2" CAPPED REBAR HE SET FOR THE CENTER CORNER OF SECTION 33-17-10
 - 6) 5,292.62' EAST TO THE 1/2" SQUARE REBAR HE FOUND AT THE EAST 1/4 CORNER OF SECTION 33-17-10

WEST QUARTER CORNER 33-17-10