

WEST 1/4 CORNER SECTION 34, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) ON PAGE 152 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 14" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 33 & 34-17-10.
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 81 RECORDED IN SURVEY BOOK "A" ON PAGE 175 & 178 DATED JANUARY 26 & 27, 1869 FOR A SURVEY OF LAND OWNED BY G. ANDERSON AND J. McCAIN SITUATED IN SECTION 34-17-10, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 34-17-10 ON THIS SURVEY.
- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 135 RECORDED IN SURVEY BOOK "A" ON PAGE 218 AND DATED OCTOBER 1869, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 34-17-10 ON THIS SURVEY.
- 4) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 138 RECORDED IN SURVEY BOOK "A" ON PAGE 219 DATED NOVEMBER 24, 1869 FOR THE SURVEY OF A COUNTY ROAD PETITIONED BY JOHN ANDERSON AND OTHERS, SAID THAT HE ENDED THIS ROAD SURVEY AT A POINT 46 RODS NORTH OF THE WEST 1/4 CORNER OF SECTION 34-17-10.
- 5) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 142 & 143 [PACKET 314 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY JOHN ANDERSON AND OTHERS IN CONTEMPLATION TO VACATE A PORTION OF THE "AMERICUS TO COUNTY GROVE ROAD" THAT WAS SURVEYED ON NOVEMBER 22, 1869 AND RECORDED ON JANUARY 3, 1870 BY J. L. WILLIAMS, COUNTY CLERK, SAID THAT HE ENDED THIS ROAD SURVEY AT A POINT 46 RODS NORTH OF THE WEST 1/4 CORNER OF SECTION 34-17-10.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION FROM THE END POINT OF THIS ROAD VACATION SURVEY:
 - 1) FROM THE END POINT THIS ROAD EXTENDS SOUTHEASTERLY FOR 1 MILE AND 282 RODS TO THE NORTHWEST CORNER OF AMERICUS TOWNSITE, BEING THE CENTER CORNER OF SECTION 2-18-10, TO COMMENCE THIS ROAD SURVEY
- 6) REA BOOK 30 ON PAGE 18 SAYS THAT **THEY SET AN IRON PIN** FOR THE WEST 1/4 CORNER OF SECTION 34-17-10.
 - 1) 25' WEST TO A WITNESS PIN
- 7) THE KRETSINGER REFERENCE TIE BOOK FOR THIS TOWNSHIP SHOWS A **REA PIN** AT THE "SW CORNER NW1/4 SECTION 34-17-10"
 - 1) 25' WEST TO A WITNESS [REA] UNDER A WIRE FENCE
- 8) TIM SLOAN, L.S. 783, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 7, 1992, LARGE SURVEY SR #33002 IN THE SURVEY FILE FOR TOWNSHIP 17-10, SAID THAT **HE FOUND A 1/2" SQUARE IRON PIN** AT THE EAST 1/4 CORNER OF SECTION 33-17-10.
 - 1) 25.0' WEST TO A 1/2" SQUARE REBAR
 - 2) IN THE TRAVELED WAY OF THE ROAD NORTH-SOUTH
HIS DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,650.97' NORTH TO THE 1/2" SQUARE REBAR HE FOUND AT THE NORTHEAST CORNER OF SECTION 33-17-10

HIS INFORMATION IS CONTINUED ON PAGE 2

- 2) 2,651.80' SOUTH TO THE 1/2" SQUARE REBAR HE FOUND AT THE SOUTHEAST CORNER OF SECTION 33-17-10 ON THE TOWNSHIP LINE
 - 3) 2,642.74' WEST TO THE 1/2" CAPPED REBAR HE SET FOR THE CENTER CORNER OF SECTION 33-17-10
 - 4) 3,967.68' WEST TO THE 1/2" CAPPED REBAR HE SET FOR THE NORTH 1/16TH CORNER OF THE SW1/4 OF SECTION 33-17-10
 - 5) 5,296.62' WEST TO THE 1/2" CAPPED REBAR HE SET FOR THE WEST 1/4 CORNER OF SECTION 33-17-10
- 9) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 16, 1994, FOR JOB NUMBER 94391-04, SURVEY F33005 IN THE SURVEY FILE FOR TOWNSHIP 17-10 FOR A 1.0 ACRE TRACT IN THE SOUTHEAST 1/4 OF SECTION 33-17-10, SAID THAT **SHE FOUND THE 1/2" SQUARE REBAR** AT THE EAST 1/4 CORNER OF SECTION 33-17-10 FROM EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE.
- 1) 25.0' WEST TO A 1/2" SQUARE REBAR
 - 2) IN THE CENTERLINE TRAVELED WAY OF THE ROAD NORTH-SOUTH
HER DRAWING ON HER REFERENCE REPORT SHOWS THE FOLLOWING DISTANCES:
 - 1) 2,147.57' SOUTH TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE NORTHEAST CORNER OF THE 1.0 ACRE TRACT
 - 2) 2,372.57' SOUTH TO THE NAIL SHE FOUND AT THE SOUTHEAST CORNER OF THE 1.0 ACRE TRACT ATTRIBUTABLE TO L. M. GOULD, L.S. 142
 - 3) 2,492.50' SOUTH TO THE NAIL SHE FOUND ATTRIBUTABLE TO L. M. GOULD, L.S. 142
 - 4) 2,651.55' SOUTH TO THE 1/2" REBAR SHE FOUND AT THE SOUTHEAST CORNER OF SECTION 33-17-10 ON THE TOWNSHIP LINE

WEST QUARTER CORNER 34-17-10