

NORTHWEST CORNER SECTION 36, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) ON PAGE 145 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 12" X 4"** FOR THE CORNER TO SECTIONS 25, 26, 35 & 36.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 39.93 CHAINS EAST TO THE 14" X 12" X 5" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN 25 & 36
- 2) 79.86 CHAINS EAST TO THE 20" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 25, 30, 31 & 36 ON THE RANGE LINE

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A **PERMANENT SURVEY** RECORDED IN VOLUME 3 ON PAGE 561 IN THE REGISTER OF DEEDS OFFICE FOR A SURVEY DATED APRIL 12-14, 1880 AND SURVEY F23001 IN THE SURVEY FILE FOR TOWNSHIP 17-10 TO ESTABLISH THE CORNERS TO THE NORTHEAST 1/4 OF SECTION 26, THE SOUTH CORNERS OF THE NORTHEAST 1/4 OF SECTION 24, ALSO THE NORTH & WEST & SOUTH CORNERS OF THE NORTHWEST 1/4, AND THE NORTHWEST AND SOUTH CORNERS OF THE SOUTHWEST 1/4, AND THE NORTH AND SOUTH CORNERS OF THE NORTH 1/2, AND THE NORTH & WEST CORNERS OF THE SOUTHWEST 1/4 OF SECTION 25, ALSO THE EAST & SOUTH CORNERS OF THE SOUTHEAST 1/4 OF SECTION 24, AND ALSO THE EAST CORNERS TO THE SOUTHEAST 1/4 OF SECTION 23, ALL IN TOWNSHIP 17-10, SAID THAT **HE FOUND THE STONE AT THE SOUTHEAST CORNER OF SECTION 26-17-10 ON THIS PERMANENT SURVEY.**

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 40.22 CHAINS WEST TO THE STONE HE FOUND AND **HE RESET** FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 26-17-10
- 2) 80.44 CHAINS WEST TO THE 22" X 8-1'2" X 8-1/2" ROCK HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 26-17-10
- 3) 40.22 CHAINS EAST TO THE 1/4 STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 25-17-10
- 4) 80.24 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 25-17-10 ON THE RANGE LINE
- 5) 20.01 CHAINS NORTH TO THE ROCK HE SET FOR THE PERMANENT EAST 1/16TH CORNER OF THE SE1/4 OF SECTION 26-17-10
- 6) 40.02 CHAINS NORTH TO THE 17" X 13-1/2" X 3-1/2" ROCK HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 26-17-10
- 7) 80.04 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 26-17-10
- 8) 120.11 CHAINS NORTH TO THE 18" X 10" X 8" ROCK HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 24-17-10
- 9) 160.18 CHAINS NORTH TO THE 25" X 8" X 5" ROCK HE SET FOR THE NORTHWEST CORNER OF SECTION 24-17-10

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 459 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 101 THROUGH 104 PETITIONED BY CHRIS HAHN AND OTHERS FOR A ROAD IN TOWNSHIP 17-10 [PACKET 693 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON NOVEMBER 13, 1900, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD, 20 FEET EACH SIDE OF THE SECTION LINE. ON DECEMBER 7, 1900 AS NOTED BY W. H. MAYES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY H. E. PEACH, COUNTY CLERK, AND RECORDED ON DECEMBER 10, 1900 BY ALVA J. SMITH, COUNTY SURVEYOR SAID THAT HE DID **NOT** FIND THE STONE AT THE NORTHWEST CORNER OF SECTION 36-17-10 ON THIS ROAD SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 2,665 FEET TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 35-17-10, THEN WEST ON THE SECTION LINES FOR 2,666 FEET TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 35-17-10 TO END THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 2,601 FEET TO A STONE HE FOUND, THEN EAST ON THE SECTION LINES FOR 2,655 FEET TO THE STAKE AT THE NORTHEAST CORNER OF SECTION 36-17-10 ON THE RANGE LINE TO BEGIN THIS ROAD SURVEY
- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 15, A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 195 DATED NOVEMBER 13, 1900 FOR A ROAD IN TOWNSHIP 17, RANGE 10 FOR CHRIS HAHN, PRINCIPAL PETITIONER, SAID THAT HE DID **NOT** FIND THE STONE AT THE NORTHWEST CORNER OF SECTION 36 ON THIS ROAD SURVEY.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING DISTANCES:
- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 2,665 FEET TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 35-17-10, THEN EXTENDS WEST ON THE SECTION LINES FOR 2,666 FEET TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 35-17-10 AT THE TERMINUS OF THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 2,601 FEET TO A STONE HE FOUND, THEN EAST ON THE SECTION LINES FOR 2,655 FEET TO THE STAKE AT THE NORTHEAST CORNER OF SECTION 36-17-10 ON THE RANGE LINE TO BEGIN THIS ROAD SURVEY
- 5) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "D" ON PAGE 8 DATED APRIL 28, 1913 BY THE ORDER OF THE BOARD OF COUNTY COMMISSIONERS TO RETRACE THE ROAD BETWEEN SECTIONS 35 & 36-17-10 AND MARK THE SAME, SAID HE BEGAN THIS ROAD SURVEY AT THE NORTHWEST CORNER OF SECTION 36-17-10 "AT A **STAKE** FOUND IN THE CENTER OF THE ROAD" THAT HE HAD DROVE ON A FORMER SURVEY.
- 6) IN A BLACK LOOSE LEAF FIELD BOOK IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE FOR THE "ALIGNMENT OF THE AMERICUS-BUSHONG ROAD" IT SHOWS AN **IRON PIN** AT THE NORTHWEST CORNER OF SECTION 36-17-10.
- 1) 45.1' SW TO A SPIKE IN A CORNER FENCE POST
 - 2) 59.4' SE TO A CORNER FENCE POST
 - 3) 38.1' NE TO A SPIKE IN A CORNER FENCE POST
- 7) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 1, 2009 FOR PROJECT NUMBER 09227-02 AND SURVEY F36002 IN THE SURVEY FILE FOR TOWNSHIP 17-10 FOR A SURVEY OF THE NORTH 1/2 OF THE SOUTHWEST 1/4 AND A 7 ACRE TRACT IN THE NORTH HALF OF THE SOUTHWEST 1/4 OF SECTION 36-17-10 FOR HANLINE, SAID THAT **HE FOUND A 1/2" REBAR** AT THE NORTHWEST CORNER OF SECTION 36-17-10 FROM EXISTING REFERENCE TIES ON A PREVIOUS SURVEY THAT HE DID IN 1987.
- 1) 45.3' WEST TO A PK NAIL IN A POWER POLE
 - 2) 81.15' ESE TO A PK NAIL IN A POWER POLE
 - 3) 46.0' ENE TO A 40 D NAIL & WASHER IN THE TOP OF A CORNER FENCE POST
 - 4) 57.95' NW TO A 40 D NAIL & WASHER IN THE TOP OF A GATE POST
 - 5) 71.95' SSE TO THE TOP CENTERLINE OF A WATER LINE "T" POST
 - 6) 0.3' WEST TO THE CENTERLINE TRAVELED WAY OF ROAD "F" NORTH-SOUTH
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) 2,604.76' EAST TO THE 5/8" REBAR HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 36-17-10
 - 2) 5,304.94' EAST TO THE 1/2" REBAR HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-17-10 ON THE RANGE LINE
 - 3) 2,645.89' SOUTH TO THE 1/2" REBAR HE FOUND AT THE WEST 1/4 CORNER OF SECTION 36-17-10
 - 4) 3,369.51' SOUTH TO THE NORTHWEST CORNER OF THE 7 ACRE TRACT AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 25.00' EAST
 - 5) 3,965.81' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE WEST 1/16TH CORNER OF THE SW1/4 OF SECTION 36-17-10
 - 6) 5,293.12' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF SECTION 36-17-10
- 8) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 5, 2010 FOR PROJECT NUMBER 10263-02, SURVEY F26002 IN THE SURVEY FILE FOR TOWNSHIP 17-10, FOR A SURVEY OF A 9.33 ACRE TRACT IN THE NORTHEAST 1/4 OF SECTION 26-17-10 FOR CLARENCE KAYSER, SAID THAT **HE FOUND THE 1/2" REBAR** AT THE SOUTHEAST CORNER OF SECTION 26-17-10 FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE IN SEPTEMBER 2009.
- 1) 45.3' WEST TO A PK NAIL IN A POWER POLE
 - 2) 81.15' ESE TO A PK NAIL IN A POWER POLE
 - 3) 46' ENE TO A 40 D NAIL & WASHER IN THE TOP OF A CORNER FENCE POST
 - 4) 57.95' NW TO A 40 D NAIL & WASHER IN THE TOP OF A GATE POST
 - 5) 71.95' SSE TO THE TOP CENTER OF A WATER LINE "T" POST
 - 6) IN THE CENTERLINE TRAVELED WAY OF ASPHALT ROAD "F" NORTH-SOUTH
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,657.61' NORTH TO THE COTTON GIN SPINDLE HE SET FOR THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 26-17-10
 - 2) 3,493.61' NORTH TO THE NORTHEAST CORNER OF THE 9.33 ACRE TRACT AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 40.00' WEST
 - 3) 5,315.22' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 26-17-10

NORTHWEST CORNER 36-17-10