

WEST 1/16 CORNER OF THE SOUTHEAST 1/4 SECTION 36, TOWNSHIP 17 SOUTH, RANGE 10 EAST

- 1) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED SEPTEMBER 1, 2009 FOR PROJECT NUMBER 09227-02 AND SURVEY F36002 IN THE SURVEY FILE FOR TOWNSHIP 17-10 FOR A SURVEY OF THE NORTH 1/2 OF THE SOUTHWEST 1/4 AND A 7 ACRE TRACT IN THE NORTH HALF OF THE SOUTHWEST 1/4 OF SECTION 36-17-10 FOR HANLINE, SAID THAT **HE SET A 1/2" X 24" REBAR WITH HIS CAP** FOR THE EAST 1/16TH CORNER OF THE SOUTHWEST 1/4 OF SECTION 36-17-10 ON TRUE LINE AND HALFWAY BETWEEN THE CENTER CORNER OF SECTION 36-17-10 AND THE THEORETICAL POSITION FOR THE SOUTH 1/4 CORNER OF SECTION 36-17-10 ON THE TOWNSHIP LINE ON THIS SURVEY.
- 1) CORNER FALLS ON THE SOUTHEAST CORNER OF A CORNER FENCE POST
 - 2) IN LINE WITH A FENCE NORTH-SOUTH
 - 3) IN LINE WITH A FENCE TO THE WEST
 - 4) 10.8' NORTH TO A CONCRETE NAIL & BOTTLECAP IN THE EAST FACE OF A FENCE POST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,322.82' SOUTH TO THE THEORETICAL LOCATION FOR THE SOUTH 1/4 CORNER OF SECTION 36-17-10 ON THE TOWNSHIP LINE
- 2) 1,322.82' NORTH TO THE 5/8" REBAR HE FOUND AT THE CENTER CORNER OF SECTION 36-17-10
- 3) 3,972.08' NORTH TO THE 5/8" REBAR HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 36-17-10
- 4) 2,143.30' WEST TO THE 1/2" REBAR WITH HIS "LS 752" HE SET FOR THE SOUTHEAST CORNER OF THE 7 ACRE TRACT
- 5) 2,653.30' WEST TO THE 1/2" CAPPED REBAR SET FOR THE WEST 1/16TH CORNER OF THE SW1/4 OF SECTION 36-17-10

WEST SIXTEENTH CORNER SOUTHEAST QUARTER 36-17-10