

**NORTH 1/4 CORNER SECTION 01, TOWNSHIP 17 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 79 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 11" X 5"** AT THE NORTH 1/4 CORNER OF SECTIONS 1-17-11 ON THE TOWNSHIP LINE ON DECEMBER 16, 1856.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS WEST ON THE TOWNSHIP LINE TO THE 15" X 10" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 1 & 2-17-11
  - 2) 40.00 CHAINS EAST ON THE TOWNSHIP LINE TO THE 19" X 8" X 5" LIMESTONE WITH A MOUND OF ROCK THEY SET FOR THE CORNER TO TOWNSHIPS 16 & 17 SOUTH, RANGES 10 & 11 EAST AT THE NORTHEAST CORNER OF SEC. 1-17-11
- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEYS NUMBER 38 AND 105 RECORDED IN SURVEY BOOK "F" ON PAGE 96 DATED MAY 3, 4, 5 & 12, 1886, FOR A SURVEY TO ESTABLISH THE CENTER CORNER OF SECTION 6-17-12 AND THE CORNERS TO THE NORTHEAST 1/4 AND THE SOUTHWEST 1/4 OF SECTION 1-17-11, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 1-17-11 ON THE TOWNSHIP LINE ON THIS SURVEY. HE USED THIS STONE TO SET THE CENTER CORNER OF SECTION 1-17-11. THIS SURVEY WAS RECORDED IN VOLUME 36 ON PAGE 497 IN THE REGISTER OF DEEDS OFFICE ON SEPTEMBER 2, 1886 AND SURVEY F01001 IN THE SURVEY FILE FOR TOWNSHIP 17-11.

- 3) **REA PIN—MUST VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED—IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR** REA BOOK 30 ON PAGE 20.5 SAYS THAT **THEY DROVE A PIN** FOR THE NORTH 1/4 CORNER OF SECTION 1-17-11 ON THE TOWNSHIP LINE AT 2,657.5' EAST OF THE NORTHWEST CORNER OF SECTION 1-17-11.

- 1) 22' SOUTH TO A WITNESS PIN

- 4) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 17-11 SHOWS A **REA PIN** AT THE "NW CORNER NE1/4 SECTION 1-17-11" ON THE TOWNSHIP LINE. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED—IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**

- 1) 22' SOUTH TO A WITNESS [REA]

- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 12, 2008, FOR PROJECT NUMBER 07415-02, SURVEY F36001 IN THE SURVEY FILE FOR TOWNSHIP 16-11, FOR A SURVEY OF TWO TRACTS IN THE SOUTHWEST 1/4 OF SECTION 36-16-11 FOR MARK & TAMMY DENTON, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 36-16-11 ON THE TOWNSHIP LINE, BUT HE DID **NOT** FIND THE STONE. **HE FOUND A 3/4" SQUARE REBAR** WITH A MAGNETIC LOCATER, **THE REA PIN**, AND HE USED THE POSITION OF THIS REBAR AS IT AGREED WITH THE PHYSICAL EVIDENCE THAT HE FOUND AT THIS CORNER. **HE REPLACED THE 3/4" SQUARE REBAR WITH A 5/8" X 30" REBAR WITH A LYON COUNTY CAP** FOR THE SOUTH 1/4 CORNER OF SECTION 36-16-11 ON THE TOWNSHIP LINE.

- 1) 27.30' NORTH TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
- 2) 25.95' SOUTH TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
- 3) 32.90' SSE TO A CONCRETE NAIL & WASHER IN A BRACE POST
- 4) IN LINE WITH A FENCE TO THE SOUTH EXTENDED

HIS TIES ARE CONTINUED ON PAGE 2

5) IN THE CENTERLINE TRAVELED-WAY OF COUNTY ROAD 310

6) 2.0' WEST TO A LINE OF FENCE TO THE NORTH EXTENDED

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,650.50' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 36-16-11
- 2) 5,308.09' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 36-17-10
- 3) 1,014.78' WEST ON THE TOWNSHIP LINE TO THE POINT OF BEGINNING FOR THE WEST TRACT
- 4) 2,657.55' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 36-17-10
- 5) 2,639.57' EAST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 36-17-10

NORTH QUARTER CORNER SECTION 01-17-11