

NORTH 1/4 CORNER SECTION 02, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) ON PAGE 79 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT THE NORTH 1/4 CORNER OF SECTION 2-17-11 ON THE TOWNSHIP LINE FALLS IN A RAVINE RUNNING SOUTH. **THEY THEREFORE SET A WITNESS LIMESTONE 19" X 13" X 5" AT A DISTANCE OF 25 LINKS EAST OF THE POINT FOR THE TRUE CORNER** ON DECEMBER 16, 1856.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION FROM THE WITNESS CORNER:
 - 1) 40.25 CHAINS WEST ON THE TOWNSHIP LINE TO THE 15" X 10" X 6" LIMESTONE THE SET FOR THE CORNER TO SECTIONS 2 & 3-17-11
 - 2) 39.75 CHAINS EAST ON THE TOWNSHIP LINE TO THE 15" X 10" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 1 & 2-17-11

- 2) **REA PIN—MUST VERIFY AND CHECK FOR THE WITNESS STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED—IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR** REA BOOK 30 ON PAGE 20.5 SAYS THAT **THEY DROVE AN IRON PIN** FOR THE NORTH 1/4 CORNER OF SECTION 2-17-11 ON THE TOWNSHIP LINE AT 2,635 FEET EAST OF THE NORTHWEST CORNER OF SECTION 2-17-11, AND IN LINE WITH A WIRE FENCE TO THE SOUTH AND A ROW OF TREES TO THE NORTH.
 - 1) 20' NORTH TO A WITNESS PIN

- 3) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 17-11 SHOWS A **REA PIN** AT THE "NW CORNER NE1/4 SECTION 2-17-11" ON THE TOWNSHIP LINE. **VERIFY AND CHECK FOR THE WITNESS STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED—IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 20' NORTH TO A WITNESS [REA]

NORTH QUARTER CORNER SECTION 02-17-11