

CENTER CORNER SECTION 03, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 13, 2001, FOR PROJECT NUMBER 99480-02, SURVEY F03001 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR A SURVEY OF A 54.76 ACRE TRACT OF LAND IN THE SOUTHEAST 1/4 OF SECTION 3-17-11 FOR EK REALTY, SAID THAT **SHE SET A 1/2" REBAR WITH HER "LS 1130" CAP** FOR THE CENTER CORNER OF SECTION 3-17-11 AT THE INTERSECTION OF THE LINES FROM THE OPPOSITE 1/4 CORNERS.
 - 1) 46.70' SW TO A MASONRY NAIL & BOTTLE CAP IN A FENCE POST IN A NORTH-SOUTH FENCE LINE
 - 2) 42.60' WEST TO A FENCE RUNNING NORTH AND SOUTH
 - 3) 26.65' WNW TO A MASONRY NAIL & BOTTLE CAP IN AN 8" LOCUST TREE
 - 4) 13.15' EAST TO A MASONRY NAIL & BOTTLE CAP IN A FENCE POST
 - 5) 0.5' SOUTH TO A FENCE RUNNING EAST FROM A CORNER POST

HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 2,630.52' WEST TO THE 5/8" CAPPED REBAR DRIVEN THROUGH THE CENTER OF TWO HALVES OF THE STONE SHE FOUND AT THE WEST 1/4 CORNER OF SECTION 3-17-11
 - 2) 2,507.12' NORTH TO THE SQUARE 3/4" REBAR SHE FOUND AT THE NORTH 1/4 CORNER OF SECTION 3-17-11 ON THE TOWNSHIP LINE
 - 3) 912.37' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP SHE SET FOR THE NORTHEAST CORNER OF THE 54.76 ACRE TRACT
 - 4) 2,632.42' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 3-17-11
 - 5) 2,640.95' SOUTH TO THE CONCRETE NAIL IN A DRILL HOLE WITH HER "LS 1130" CAP SHE SET IN A CONCRETE LOW WATER CROSSING FOR THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 3-17-11

CENTER CORNER 03-17-11