

**NORTH 1/4 CORNER SECTION 05, TOWNSHIP 17 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 56 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 14" X 3"** AT THE NORTH 1/4 CORNER OF SECTIONS 5-17-11 ON THE TOWNSHIP LINE. THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.00 CHAINS WEST ON THE TOWNSHIP LINE TO THE 18" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5 & 6-17-11
  - 2) 16.60 CHAINS EAST ON THE TOWNSHIP LINE TO THE 20" X 10" X 3" LIMESTONE THEY SET ON THE EAST BOUNDARY OF THE KANSAS INDIAN RESERVATION FOR THE FRACTIONAL SECTION CORNER
  - 3) 40.00 CHAINS EAST ON THE TOWNSHIP LINE TO THE 19" X 10" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4 & 5-17-11
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 8 OF THE 8<sup>TH</sup> TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 63 DATED MARCH 6, 1874 TO ESTABLISH THE CORNERS TO THE FRACTIONAL PART OF THE SOUTHEAST 1/4 OF SECTION 33-16-11 EAST OF THE EASTERN BOUNDARY OF THE KANSAS INDIAN TRUST LANDS, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 32-16-11 ON THE TOWNSHIP LINE ON THIS **PERMANENT SURVEY**.
- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN AN **AGREEMENT SURVEY** FOR HORACE D. CURTIS, RICHARD KORKLAUS, RICHARD H. DUNCAN, AND EDWIN MOREHEAD, TO ESTABLISH THE CENTER CORNER OF SECTION 32-16-11 DATED APRIL 15 & 16, 1880, SURVEY F32001 IN THE SURVEY FILE FOR TOWNSHIP 16-11, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 32-16-11 ON THE TOWNSHIP LINE ON THIS **AGREEMENT SURVEY**. THIS SURVEY IS FILED IN THE REGISTER OF DEEDS OFFICE.
- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT PAGE 193 DATED AUGUST 7, 1880, FOR A ROAD SURVEY IN TOWNSHIP 16-11 APPARENTLY **FOUND THE STONE** AT THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 32-16-11 ON THE TOWNSHIP LINE TO COMMENCE THIS ROAD SURVEY. HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS ROAD EXTENDS NORTH ON THE 1/2 SECTION LINE TO THE STONE HE FOUND AT THE CENTER CORNER OF SECTION 29-16-11
- 5) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 94 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 378 TO 380 PETITIONED BY EDWIN MOORHEAD AND OTHERS TO LOCATE AND VACATE A ROAD IN TOWNSHIP 16-11 [PACKET 348 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON NOVEMBER 26, 1880, WAS ESTABLISHED AS A 60' WIDE ROAD **EXCEPT** THAT PORTION RUNNING EAST ON THE 1/2 SECTION LINE [FROM THE NORTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 29-16-11 TO THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF SECTION 27-16-11] ON JANUARY 5, 1881, AND WAS RECORDED ON JANUARY 5, 1881 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 32-16-11 ON THE TOWNSHIP LINE TO COMMENCE THE ROAD ALLOWED ON THIS ROAD SURVEY. THE ROAD TO BE **VACATED** IS THAT PORTION OF THE AMERICUS AND ALLEN ROAD COMMENCING AT THE NORTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 26-16-11, THEN ANGLING IN A NORTHEAST DIRECTION TO 142 CREEK, A DISTANCE OF SIX (6) MILES.

HIS INFORMATION IS CONTINUED ON PAGE 2

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THE ROAD ALLOWED EXTENDS NORTH ON THE 1/4 SECTION LINE TO THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 29-16-11 AT THE TERMINUS OF THE ROAD ALLOWED

- 6) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 130 DATED MAY 2 & 3, 1882 AT THE REQUEST OF H. T. SWARNER TO SURVEY AND ESTABLISH IN TOWNSHIP 17, RANGE 11, THE CENTER OF SECTION 5, THE CORNER ON THE INDIAN RESERVE LINE, AND THE SOUTH LINE OF SECTION 5, AND THE 1/2 MILE CORNER ON THE INDIAN RESERVE LINE IN SECTION 5, AND SUCH OTHER LINES AND CORNERS AS MAY BE NECESSARY TO COMPLETE THE SURVEY, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 5-17-11 ON THE TOWNSHIP LINE ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 77.39 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 5-17-11
- 7) REA BOOK 30 ON PAGE 19.5 SAYS THAT **THEY SET AN IRON PIN** FOR THE NORTH 1/4 CORNER OF SECTION 5-17-11 ON THE TOWNSHIP LINE. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
  - 1) 24' NORTH TO A WITNESS PIN

- 8) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 17-11 SHOWS A **REA PIN** AT THE "NW CORNER NE1/4 SECTION 5-17-11" ON THE TOWNSHIP LINE. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
  - 1) 24' SOUTH TO A WITNESS [REA]

- 9) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 12, 2010 FOR PROJECT NUMBER 10112-02, SURVEY F05001 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR A SURVEY OF THE WEST HALF OF THE FRACTIONAL NORTHWEST 1/4 AND THE EAST HALF OF THE FRACTIONAL NORTHWEST 1/4; [AKA GOVERNMENT LOT 7 AND THE WEST HALF OF GOVERNMENT LOT 8 AND GOVERNMENT LOT 6 AND THE EAST HALF OF GOVERNMENT LOT 8] ALL IN SECTION 5-17-11 FOR EK REALTY, SAID THAT HE HAD EXCAVATED FOR THE STONE AT THE NORTH 1/4 CORNER OF SECTION 5-17-11 ON THE TOWNSHIP LINE PREVIOUSLY, BUT HE DID **NOT** FIND THE STONE. **HE FOUND A #5 SQUARE REBAR ATTRIBUTABLE TO AI CHAMNESS AND HE ACCEPTED THIS #5 REBAR AS THE NORTH 1/4 CORNER OF SECTION 5-17-11 [AKA THE NORTHEAST CORNER OF GOVERNMENT LOT 6 IN THE FRACTIONAL NORTHWEST 1/4 OF SECTION 5-17-11].**
  - 1) 43.0' SE TO A CONCRETE NAIL & BOTTLECAP IN THE TOP OF A CORNER FENCE POST
  - 2) 30.7' SSE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
  - 3) 37.4' NW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
  - 4) IN THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "H5" TO THE NORTH
  - 5) 5.6' SOUTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 310-EAST-WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,320.81' WEST ON THE TOWNSHIP LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTH 1/16TH CORNER OF THE FRACTIONAL NW1/4 OF

SECTION 5-17-11 [AKA NORTHWEST CORNER OF GOVERNMENT LOT 6 AND THE NORTHEAST CORNER OF GOVERNMENT LOT 7]

- 2) 2,641.62' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP AT THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE FRACTIONAL NW1/4 OF SECTION 5-17-11 [AKA NORTHWEST CORNER OF GOVERNMENT LOT 7]
- 3) 2,464.36' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE FRACTIONAL NW1/4 OF SECTION 5-17-11 [AKA THE CORNER COMMON TO GOVERNMENT LOTS 8, 9, 10 & 12]
- 4) 5,111.84' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHEAST CORNER OF THE FRACTIONAL SW1/4 OF SECTION 5-17-11 [AKA SOUTHEAST CORNER OF GOVERNMENT LOT 12]

NORTH QUARTER CORNER SECTION 05-17-11