

WEST 1/4 CORNER SECTION 05, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) ON PAGE 328 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 10" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 5 & 6-17-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 38.90 CHAINS NORTH TO THE 18" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5, 6, 31 & 32 ON THE TOWNSHIP LINE
 - 2) 40.00 CHAINS SOUTH TO THE 18" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTION S5, 6, 7 & 8

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 7 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 62 DATED MARCH 5, 1874 TO ESTABLISH THE CENTER CORNER, TO SUBDIVIDE THE SOUTHWEST 1/4 BY A LINE NORTH & SOUTH, THE SOUTHEAST 1/4 BY A LINE NORTH & SOUTH, THE EAST 1/2 OF THE NORTHWEST 1/4 BY A LINE EAST & WEST, THE NORTHEAST 1/4 BY A LINE NORTH & SOUTH, AND THE WEST 1/2 BY A LINE EAST & WEST, ALL IN SECTION 6-17-11, STATES THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 6-17-11 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 1,307-1/2' WEST TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE NE1/4 OF SECTION 6-16-11
 - 2) 2,615' WEST TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 6-16-11
 - 3) 3,935' WEST TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE NW1/4 OF SECTION 6-17-11
 - 4) 4,938' WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 6-17-11 ON THE RANGE LINE

- 3) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 130 DATED MAY 2 & 3, 1882 AT THE REQUEST OF H. T. SWARNER TO SURVEY AND ESTABLISH IN TOWNSHIP 17, RANGE 11, THE CENTER OF SECTION 5, THE CORNER ON THE INDIAN RESERVE LINE, AND THE SOUTH LINE OF SECTION 5, AND THE 1/2 MILE CORNER ON THE INDIAN RESERVE LINE IN SECTION 5, AND SUCH OTHER LINES AND CORNERS AS MAY BE NECESSARY TO COMPLETE THE SURVEY, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 5-17-11 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 57.10 CHAINS EAST TO THE PERMANENT STONE HE SET FOR THE 1/2 MILE CORNER ON THE INDIAN RESERVE LINE IN SECTION 5-16-11

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 37, A **ROAD/PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 218 DATED FEBRUARY 18, 1902 FOR A COUNTY ROAD IN TOWNSHIP 17-11 PETITIONED BY W. B. DeBAUN AND OTHERS TO ESTABLISH THE ROAD BETWEEN SECTIONS 5 & 6 IN 17-11, AND ORDERED BY THE BOARD OF COUNTY COMMISSIONERS TO LOCATE THE SECTION LINE BETWEEN SECTIONS 5 & 6 IN 17-11 ON OCTOBER 2, 1902, SAID THAT THERE IS A DISCREPANCY OF ABOUT 11 RODS IN THE GOVERNMENT FIELD NOTES ON THE NORTH LINES OF SECTIONS 6 & 7 IN TOWNSHIP 17-11, AND THAT IT WOULD BE IMPRACTICAL TO LOCATE THE NORTHWEST CORNER OF SECTION 5-17-11 BY MEASUREMENT. **HE FOUND THE GOVERNMENT STONE** AT THE WEST 1/4 CORNER OF SECTION 5-17-11 ON THIS **ROAD/PERMANENT SURVEY**. HE SAID THAT THE ROAD IS 40 FEET WIDE, 20 FEET EACH SIDE OF THE LINE SURVEYED.

- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 12, 2010 FOR PROJECT NUMBER 10112-02, SURVEY F05001 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR A SURVEY OF THE WEST HALF OF THE FRACTIONAL NORTHWEST 1/4 AND THE EAST HALF OF THE FRACTIONAL NORTHWEST 1/4 [AKA GOVERNMENT LOT 7 AND THE WEST HALF OF GOVERNMENT LOT 8 AND GOVERNMENT LOT 6 AND THE EAST HALF OF GOVERNMENT LOT 8] ALL IN SECTION 5-17-11 FOR EK REALTY, SAID THAT HE SEARCHED FOR THE STONE OF RECORD AT THE WEST 1/4 CORNER OF SECTION 5-17-11, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **OBLITERATED**. HE SAID THAT THE POSITION OF THE CORNER POST WAS DEEMED TO BE THE BEST EVIDENCE OF THE STONE'S ORIGINAL POSITION AS THE POSITION FIT THE FENCE AND HEDGE TO THE EAST TOWARD THE INDIAN RESERVE LINE STONE HE FOUND FROM RICE IN 1882. **HE SET A 5/8" REBAR WITH A LYON COUNTY CAP** FOR THE WEST 1/4 CORNER OF SECTION 5-17-11 [AKA THE SOUTHWEST CORNER OF GOVERNMENT LOT 8 AND THE NORTHWEST CORNER OF GOVERNMENT LOT 12 IN FRACTIONAL SECTION 5-17-11].
- 1) ON THE SOUTH SIDE OF A LONE CORNER POST [HEDGE]
 - 2) IN A LARGE AREA OF BRUSHES AND SHRUBS BUT NO TREES
 - 3) 1,320.24' EAST TO A 1/2" CAPPED REBAR AT THE SOUTHEAST CORNER OF THE W1/2 OF GOVERNMENT LOT 8
 - 4) 2,554.84' NORTH TO A 5/8" REBAR AT THE STONE'S POSITION AT THE NORTHWEST CORNER OF SECTION 5
 - 5) 2,650.56' SOUTH TO THE STONE & REBARS AT THE SOUTHWEST CORNER OF SECTION 5

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,320.24' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTH 1/16TH CORNER OF THE FRACTIONAL NW1/4 OF SECTION 5-17-11 [AKA SOUTHWEST CORNER OF THE E1/2 OF GOVERNMENT LOT 8]
- 2) 2,640.48' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE FRACTIONAL NW1/4 OF SECTION 5-17-11 [AKA NORTHEAST CORNER OF GOVERNMENT LOT 12 AND NORTHWEST CORNER OF GOVERNMENT LOT 10]
- 3) 3,760.39' EAST TO THE STONE HE FOUND ON THE EAST BOUNDARY OF THE KANSAS INDIAN RESERVATION AT THE SOUTHEAST CORNER OF GOVERNMENT LOT 9
- 4) 2,554.84' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP AT THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE FRACTIONAL NW1/4 OF SECTION 5-17-11 ON THE TOWNSHIP LINE [AKA NORTHWEST CORNER OF GOVERNMENT LOT 7]
- 5) 2,650.56' SOUTH TO THE LIMESTONE HE FOUND, WITH 1/2" REBARS WITH HIS "LS 752" CAPS HE FOUND ON THE NORTH AND SOUTH SIDES OF THE LIMESTONE, AT THE SOUTHWEST CORNER OF THE FRACTIONAL SW1/4 OF SECTION 5-17-11 [AKA SOUTHWEST CORNER OF GOVERNMENT LOT 12]

WEST QUARTER CORNER 05-17-11