

NORTH 1/4 CORNER SECTION 06, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) ON PAGE 57 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 14" X 3"** AT THE NORTH 1/4 CORNER OF SECTION 6-17-11 ON THE TOWNSHIP LINE ON JANUARY 9, 1861.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 35.86 CHAINS WEST ON THE TOWNSHIP LINE TO THE 20" X 10" X 8" LIMESTONE THEY SET FOR THE CORNER TO TOWNSHIPS 16 & 17 SOUTH, RANGES 10 & 11 EAST AT THE NORTHWEST CORNER OF SECTION 6-17-11
- 2) 40.00 CHAINS EAST ON THE TOWNSHIP LINE TO THE 18" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5 & 6-17-11
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 7 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 62 DATED MARCH 5, 1874 TO ESTABLISH THE CENTER CORNER, TO SUBDIVIDE THE SOUTHWEST 1/4 BY A LINE NORTH & SOUTH, THE SOUTHEAST 1/4 BY A LINE NORTH & SOUTH, THE EAST 1/2 OF THE NORTHWEST 1/4 BY A LINE EAST & WEST, THE NORTHEAST 1/4 BY A LINE NORTH & SOUTH, AND THE WEST 1/2 BY A LINE EAST & WEST, ALL IN SECTION 6-17-11, STATES THAT **HE FOUND THE STONE LYING DOWN** AT THE NORTH 1/4 CORNER OF SECTION 6-17-11 ON THE TOWNSHIP LINE ON THIS **PERMANENT SURVEY**. **HE RESET THE STONE FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 6-17-11 ON THE TOWNSHIP LINE** AND AT THE "PROPER DISTANCE" BETWEEN THE STONE THAT HE RESET FOR THE NORTHEAST CORNER OF SECTION 6-17-11 AND THE STONE THAT HE FOUND AT THE TOWNSHIP CORNER AT THE NORTHWEST CORNER OF SECTION 6-17-11.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 1,320' WEST ON THE TOWNSHIP LINE TO THE STONE HE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE NW1/4 OF SECTION 6-17-11
- 2) 2,340' WEST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE TOWNSHIP CORNER AT THE NORTHWEST CORNER OF SECTION 6-17-11
- 3) 1,320' EAST ON THE TOWNSHIP LINE TO THE STONE HE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE NE1/4 OF SECTION 6-17-11
- 4) 2,640' EAST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AND **HE RESET** FOR THE PERMANENT NORTHEAST CORNER OF SECTION 6-17-11
- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN AN **AGREEMENT SURVEY** DATED APRIL 15, 1880 FILED IN THE REGISTER OF SEEDS OFFICE ON PAGE 553 FOR HORN R. MAYS, JESSE FOSTER, AND REBECCA M. CURTIS TO ESTABLISH THE LINE BETWEEN THE EAST 1/2 OF THE SOUTHEAST 1/4 AND THE WEST 1/2 OF THE SOUTHEAST 1/4, ALSO THE SOUTHEAST CORNER OF THE WEST 1/2 OF THE SOUTHEAST 1/4, AND THE NORTHEAST CORNER OF THE WEST 1/2 OF THE SOUTHEAST 1/4, ALSO THE NORTHWEST CORNER OF THE SOUTHEAST 1/4, ALSO THE NORTHWEST CORNER OF THE SOUTHWEST 1/4, ALL IN SECTION 31-16-11, SAID THAT **HE FOUND THE STONE** AT THE SOUTH CORNER OF SECTION 31-16-11 ON THE TOWNSHIP LINE ON THIS **AGREEMENT SURVEY**. THIS SURVEY IS FILED AT SURVEY F31001 IN THE SURVEY FILE FOR TOWNSHIP 16-11.
- 4) **REA PIN—VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR** REA BOOK 30 ON PAGE 16 SAYS THAT **THEY SET AN IRON PIN** FOR THE NORTH 1/4 CORNER OF SECTION 6-17-11 ON THE TOWNSHIP LINE.

- 1) 30' NORTH TO A WITNESS PIN

CONTINUED ON PAGE 2

- 5) KRETSINGER REFERENCE TIE BOOKS FOR THIS TOWNSHIP SHOW A **"REA PIN"** AT THE "NW CORNER NE1/4 SECTION 6-17-11" ON THE TOWNSHIP LINE. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
- 1) 30' NORTH TO A WITNESS [REA]
- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 12, 2009 FOR PROJECT NUMBER 09119-02 TO ESTABLISH THE NORTH LINE OF THE NORTHEAST 1/4 OF FRACTIONAL SECTION 6-17-11 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT FOR BRIDGE REPLACEMENT PROJECT NUMBER 04-EP, SURVEY F06003 IN THE SURVEY FILE FOR TOWNSHIP 17-11, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE AT THE NORTH 1/4 CORNER OF SECTION 6-17-11 ON THE TOWNSHIP LINE, BUT HE DID **NOT** FIND THE STONE. HE DEEMED THAT THIS CORNER WAS **LOST**. HE RESET THIS CORNER BY SINGLE PROPORTION BETWEEN THE NORTHEAST CORNER AND THE NORTHWEST CORNER OF SECTION 6-17-11 ON THE TOWNSHIP LINE BASED ON A SURVEY BY ROBERT MILLIKEN IN 1874 AS RECORDED IN SURVEY BOOK "C" ON PAGE 62 IN THE OFFICE OF THE COUNTY SURVEYOR. THE REA PIN WAS REMOVED DURING EXCAVATION AND WAS NOT REPLACED AT THE REQUEST OF THE LYON COUNTY SURVEYOR. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE NORTH 1/4 CORNER OF SECTION 6-17-11 ON THE TOWNSHIP LINE.
- 1) 41.2' SW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 2) 33.9' SE TO A COTTON GIN SPINDLE IN THE NORTH FACE OF A POWER POLE
 - 3) 75.5' ENE TO A MAG NAIL & WASHER IN THE TOP OF A CORNER FENCE POST
 - 4) 1' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 310 EAST-WEST
 - 5) 1' WEST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "G5" TO THE SOUTH
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,346.53' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP OVER THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 6-17-11
 - 2) 2,647.37' EAST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET AT THE LOCATION OF THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 6-17-11
- 7) RICHARD J. IMAN, L.S. 1450, OF BG CONSULTANTS, INC. IN A LAND SURVEY REFERENCE REPORT DATED JUNE 5, 2009 FOR PROJECT NUMBER 09-1119E FOR THE LYON COUNTY HIGHWAY DEPARTMENT FOR LYON COUNTY BRIDGE REPLACEMENT PROJECT NUMBER 04-EP, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE SOUTH 1/4 CORNER OF SECTION 31-16-11 ON THE TOWNSHIP LINE FROM THE TIES BY STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, DATED MAY 6, 2009.
- 1) 41.2' SW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 2) 38.9' SE TO A COTTON GIN SPINDLE IN THE NORTH FACE OF A POWER POLE
 - 3) 75.5' ENE TO A MAG NAIL & WASHER IN THE TOP OF A CORNER FENCE POST
 - 4) 1' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 310 EAST-WEST
 - 5) 1' WEST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "G5" TO THE SOUTH
- 8) AARON C. DAVIS, L.S. 1368, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 2, 2010 FOR PROJECT NUMBER 10011-02, SURVEY F31003 IN THE SURVEY FILE FOR TOWNSHIP 16-11 AND SURVEY NUMBER

F06004 IN THE SURVEY FILE FOR TOWNSHIP 17-11, TO STAKE THE RIGHT-OF-WAY TRACTS IN THE NORTHEAST 1/4 OF SECTION 6-17-11 AND THE SOUTHEAST 1/4 OF SECTION 31-16-11 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT PROJECT 04-EP, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE SOUTH 1/4 CORNER OF SECTION 31-16-11/NORTH 1/4 CORNER SECTION 6-17-11 ON THE TOWNSHIP LINE FROM EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE.

- 1) 41.20' SW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
- 2) 38.85' SE TO A COTTON GIN SPINDLE IN THE NORTH FACE OF A POWER POLE
- 3) 75.50' ENE TO A MAG NAIL & WASHER IN THE NORTH FACE OF A POWER POLE
- 4) 1' NORTH TO THE CENTERLINE TRAVELED WAY FOR COUNTY ROAD 310 EAST-WEST
- 5) 2' WEST TO THE CENTERLINE TRAVELED WAY FOR ROAD "G5" TO THE SOUTH EXTENDED

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,647.09' EAST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON CAP HE FOUND AT THE NORTHEAST CORNER OF SECTION 6-17-11

- 9) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 3, 2010 FOR PROJECT NUMBER 10164-02 TO ESTABLISH THE NORTHWEST CORNER OF THE EAST 1/2 OF THE NORTHWEST 1/4 AND THE NORTHWEST CORNER OF THE EAST 1/2 OF THE NORTHEAST 1/4 OF SECTION 6-17-11 FOR THE LYON COUNTY HIGHWAY DEPARTMENT FOR BRIDGE REPLACEMENT PROJECT NUMBER 04-EP, SURVEY F06005 IN THE SURVEY FILE FOR TOWNSHIP 17-11, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE NORTH 1/4 CORNER OF SECTION 6-17-11 ON THE TOWNSHIP LINE FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE DATED MAY 2009. HE NOTED ON HIS SURVEY THAT THE 1/16TH CORNERS WERE RESET BY RETRACING A SURVEY BY MILLIKEN RECORDED IN PERMANENT SURVEY BOOK "C" ON PGE 62 (1874).

- 1) 41.2' SW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
- 2) 33.9' SE TO A COTTON GIN SPINDLE IN THE NORTH FACE OF A POWER POLE
- 3) 75.5' ENE TO A MAG NAIL & WASHER IN THE TOP OF A CORNER FENCE POST
- 4) 1' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 310 EAST-WEST
- 5) 1' WEST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "G5" TO THE SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,323.88' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE E1/2 OF THE NW1/4 OF SECTION 6-17-11 [MILLIKEN = 1,320']
- 2) 2,346.90' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP OVER THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 6-17-11 AT THE TOWNSHIP CORNER [MILLIKEN = 2,340']
- 3) 1,323.54' EAST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 6-17-11 [MILLIKEN = 1,320']
- 4) 2,647.08' EAST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 6-17-11 [MILLIKEN = 2,640']

NORTH QUARTER CORNER SECTION 06-17-11