

NORTH 1/16TH CORNER OF NORTHEAST 1/4 SECTION 06, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 7 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 62 DATED MARCH 5, 1874 TO ESTABLISH THE CENTER CORNER, TO SUBDIVIDE THE SOUTHWEST 1/4 BY A LINE NORTH & SOUTH, THE SOUTHEAST 1/4 BY A LINE NORTH & SOUTH, THE EAST 1/2 OF THE NORTHWEST 1/4 BY A LINE EAST & WEST, THE NORTHEAST 1/4 BY A LINE NORTH & SOUTH, AND THE WEST 1/2 BY A LINE EAST & WEST, ALL IN SECTION 6-17-11, STATES THAT **HE SET A STONE** FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE NORTHEAST 1/4 OF SECTION 6-17-11 ON THE TOWNSHIP LINE ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 1,242' SOUTH TO THE STONE HE SET FOR THE PERMANENT 1/4/4 CORNER OF THE CENTER OF THE NE1/4 OF SECTION 6-17-11
 - 2) 2,562' SOUTH TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE NE1/4 OF SECTION 6-17-11
 - 3) 1,320' EAST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AND **HE RESET** FOR THE PERMANENT NORTHEAST CORNER OF SECTION 6-17-11
 - 4) 1,320' WEST ON THE TOWNSHIP LINE TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 6-17-11
 - 5) 2,640' WEST ON THE TOWNSHIP LINE TO THE STONE HE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE NW1/4 OF SECTION 6-17-11
 - 6) 3,660' WEST TO THE STONE HE FOUND AT THE TOWNSHIP CORNER AT THE NORTHWEST CORNER OF SECTION 6-17-11
- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN AN **AGREEMENT SURVEY** DATED APRIL 15, 1880 FILED IN THE REGISTER OF SEEDS OFFICE ON PAGE 553 FOR HORN R. MAYS, JESSE FOSTER, AND REBECCA M. CURTIS TO ESTABLISH THE LINE BETWEEN THE EAST 1/2 OF THE SOUTHEAST 1/4 AND THE WEST 1/2 OF THE SOUTHEAST 1/4, ALSO THE SOUTHEAST CORNER OF THE WEST 1/2 OF THE SOUTHEAST 1/4, AND THE NORTHEAST CORNER OF THE WEST 1/2 OF THE SOUTHEAST 1/4, ALSO THE NORTHWEST CORNER OF THE SOUTHEAST 1/4 , ALSO THE NORTHWEST CORNER OF THE SOUTHWEST 1/4, ALL IN SECTION 31-16-11, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/16TH CORNER OF THE SOUTHEAST 1/4 OF SECTION 31-16-11 ON THE TOWNSHIP LINE ON THIS **AGREEMENT SURVEY**. THIS SURVEY IS FILED AT SURVEY F31001 IN THE SURVEY FILE FOR TOWNSHIP 16-11.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 40.17 CHAINS NORTH TO THE STONE HE SET FOR THE NORTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 31-16-11
- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 3, 2010 FOR PROJECT NUMBER 10164-02 TO ESTABLISH THE NORTHWEST CORNER OF THE EAST 1/2 OF THE NORTHWEST 1/4 AND THE NORTHWEST CORNER OF THE EAST 1/2 OF THE NORTHEAST 1/4 OF SECTION 6-17-11 FOR THE LYON COUNTY HIGHWAY DEPARTMENT OR BRIDGE REPLACEMENT PROJECT NUMBER 04-EP, SURVEY F06005 IN THE SURVEY FILE FOR TOWNSHIP 17-11, SAID THAT HE DID **NOT** DIG FOR THE STONE THAT WAS SET BY MILLIKEN IN 1874 AT THE NORTH 1/16TH CORNER OF THE NORTHEAST 1/4 OF SECTION 6-17-11 ON THE TOWNSHIP LINE AS IT FALLS IN A LARGE FILL AREA. HE CONSIDERED THAT THIS 1/16TH CORNER WAS **LOST**. **HE SET A 5/8" X 30" REBAR WITH A LYON COUNTY CAP** FOR THE NORTH 1/16TH CORNER OF THE NORTHEAST 1/4 OF SECTION 6-17-11 ON TRUE LINE AND HALFWAY BETWEEN THE NORTH

QUARTER CORNER AND THE NORTHEAST CORNER OF SECTION 6-17-11 AS PER THE MILLIKEN SURVEY.

- 1) 1.0' NORTH TO THE CENTERLINE TRAVELED WAY OF ROAD 310 EAST-WEST
- 2) 5' EAST TO A LINE OF FENCE TO THE SOUTH EXTENDED
- 3) 229.5' EAST TO THE WEST EDGE OF WEARING SURFACE OF THE BRIDGE

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION

- 1) 1,323.54' EAST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 6-17-11 [MILLIKEN = 1,320']
- 2) 1,323.54' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 6-17-11 [MILLIKEN = 1,320']
- 3) 2,647.42' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE E1/2 OF THE NW1/4 OF SECTION 6-19-11 [MILLIKEN = 2,640']
- 4) 3,670.44' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP OVER THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 6 -17-11 AT THE TOWNSHIP CORNER [MILLIKEN = 3,660']

NORTH SIXTEENTH CORNER NORTHEAST QUARTER 06-17-11