

NORTH 1/16TH CORNER OF NORTHWEST 1/4 SECTION 06, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 7 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 62 DATED MARCH 5, 1874 TO ESTABLISH THE CENTER CORNER, TO SUBDIVIDE THE SOUTHWEST 1/4 BY A LINE NORTH & SOUTH, THE SOUTHEAST 1/4 BY A LINE NORTH & SOUTH, THE EAST 1/2 OF THE NORTHWEST 1/4 BY A LINE EAST & WEST, THE NORTHEAST 1/4 BY A LINE NORTH & SOUTH, AND THE WEST 1/2 BY A LINE EAST & WEST, ALL IN SECTION 6-17-11, STATES THAT **HE SET A STONE** FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE NORTHWEST 1/4 CORNER OF SECTION 6-17-11 ON THE TOWNSHIP LINE ON **THIS PERMANENT SURVEY.**

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 1,020' WEST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE TOWNSHIP CORNER AT NORTHWEST CORNER OF SECTION 6-17-11
 - 2) 1,320' EAST ON THE TOWNSHIP LINE TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 6-17-11
 - 3) 2,640' EAST ON THE TOWNSHIP LINE TO THE STONE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE NE1/4 OF SECTION 6-17-11
 - 4) 3,960' EAST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AND **HE RESET** FOR THE PERMANENT NORTHEAST CORNER OF SECTION 6-17-11
 - 5) 1,300' SOUTH TO THE STONE HE SET FOR THE PERMANENT 1/4/4 CORNER IN THE CENTER OF THE NW1/4 OF SECTION 6-17-11
 - 6) 2,620' SOUTH TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE NW1/4 OF SECTION 6-17-11
- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 3, 2010 FOR PROJECT NUMBER 10164-02 TO ESTABLISH THE NORTHWEST CORNER OF THE EAST 1/2 OF THE NORTHWEST 1/4 AND THE NORTHWEST CORNER OF THE EAST 1/2 OF THE NORTHEAST 1/4 OF SECTION 6-17-11 FOR THE LYON COUNTY HIGHWAY DEPARTMENT FOR BRIDGE REPLACEMENT PROJECT NUMBER 04-EP, SURVEY F06005 IN THE SURVEY FILE FOR TOWNSHIP 17-11, SAID THAT HE EXCAVATED FOR THE STONE THAT WAS SET BY MILLIKEN IN 1874 AT THE NORTH 1/16TH CORNER OF THE NORTHWEST 1/4 OF SECTION 6-17-11 ON THE TOWNSHIP LINE, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS 1/16TH CORNER WAS **LOST**. **HE SET A 5/8" X 30" REBAR WITH A LYON COUNTY CAP** FOR THE NORTH 1/16TH CORNER OF THE NORTHWEST 1/4 OF SECTION 6-17-11 ON THE TOWNSHIP LINE AT THE PROPORTIONATE DISTANCE BETWEEN THE NORTHWEST CORNER OF SECTION 6-17-11 AND THE NORTH QUARTER CORNER OF SECTION 6-17-11 AS PER THE MILLIKEN SURVEY.

- 1) 32.8' NNE TO A 40 D NAIL & BOTTLECAP IN THE EAST FACE OF A POWER POLE
- 2) 40.25' ESE TO THE NORTHWEST CORNER OF A CULVERT HUBGUARD
- 3) 44.85' ENE TO THE SOUTHWEST CORNER OF A CULVERT HUBGUARD
- 4) IN LINE WITH A FENCE TO THE SOUTH EXTENDED
- 5) 2.0' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 310 EAST-WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,023.02' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP OVER THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 6-17-11 AT THE TOWNSHIP CORNER [MILLIKEN = 1,020']
- 2) 1,323.88' EAST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 6-17-11 [MILLIKEN = 1,320']

HIS INFORMATION IS CONTINUED ON PAGE 2

- 3) 2,647.42' EAST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 6-17-11 [MILLIKEN = 2,640']
- 4) 3,970.96' EAST ON THE TOWNSHIP LINE TO A 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 6-17-11 [MILLIKEN = 3,960']

NORTH SIXTEENTH CORNER NORTHWEST QUARTER 06-17-11