

**NORTHWEST CORNER SECTION 06, TOWNSHIP 17 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 54 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 10" X 8"** FOR THE CORNER TO TOWNSHIPS 16 & 17 SOUTH, RANGES 10 & 11 EAST ON JANUARY 7, 1861 AT THE NORTHWEST CORNER OF SECTION 6-17-11.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 35.86 CHAINS EAST ON THE TOWNSHIP LINE TO THE 16" X 14" X 3" LIMESTONE THEY SET FOR THE NORTH 1/4 CORNER OF SECTION 6-17-11
  - 2) 75.86 CHAINS EAST ON THE TOWNSHIP LINE TO THE 18' X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5 & 6-17-11
  - 3) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 16" X 13" X 3" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 6-17-11
  - 4) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDRY TO THE 24" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 6 & 7-17-11
  
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 7 OF THE 8<sup>TH</sup> TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 62 DATED MARCH 5, 1874 TO ESTABLISH THE CENTER CORNER, TO SUBDIVIDE THE SOUTHWEST 1/4 BY A LINE NORTH & SOUTH, THE SOUTHEAST 1/4 BY A LINE NORTH & SOUTH, THE EAST 1/2 OF THE NORTHWEST 1/4 BY A LINE EAST & WEST, THE NORTHEAST 1/4 BY A LINE NORTH & SOUTH, AND THE WEST 1/2 BY A LINE EAST & WEST, ALL IN SECTION 6-17-11, STATES THAT **HE FOUND THE STONE AT THE TOWNSHIP CORNER** AT THE NORTHWEST CORNER OF SECTION 6-17-11 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 1,020' EAST ON THE TOWNSHIP LINE TO THE STONE HE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE NW1/4 OF SECTION 6-17-11
  - 2) 2,340' EAST ON THE TOWNSHIP LINE TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 6-17-11
  - 3) 3,660' EAST ON THE TOWNSHIP LINE TO THE STONE HE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE NE1/4 OF SECTION 6-17-11
  - 4) 4,980' EAST ON THE TOWNSHIP LINE TO THE STONE HE RESET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 6-17-11
  
- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 28 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 110 TO 112 PETITIONED BY W. R. COLGAN AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 16-10 AND 17-10 [PACKET 116 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 13, 1879, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON JULY 7, 1879, AND WAS RECORDED ON JULY 15, 1879 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 1-17-10 AT THE TOWNSHIP CORNER ON THE RANGE LINE ON THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS ROAD EXTENDS NORTH ON THE RANGE LINE TO THE NORTHEAST CORNER OF SECTION 6-16-10 ON THE 3<sup>RD</sup> STANDARD PARALLEL TO COMMENCE THIS ROAD SURVEY
  - 2) THIS ROAD EXTENDS SOUTH ON THE RANGE LINE TO THE NORTHEAST CORNER OF SECTION 24-17-10 FOR THE TERMINUS OF THIS ROAD SURVEY
  
- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 62 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 250 TO 252 PETITIONED BY JOHN R. MAYS AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 17-10 AND 17-11 ON THE TOWNSHIP LINES [PACKET 329 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MARCH 22, 1880, WAS

ESTABLISHED AS A 50 FOOT WIDE ROAD ON APRIL 12, 1880, AND WAS RECORDED ON APRIL 20, 1880 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 6-17-11 ON THE RANGE LINE ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE TOWNSHIP LINE FOR 6 MILES TO THE NORTHWEST CORNER OF SECTION 6-17-10 ON THE RANGE LINE AND THE LYON AND MORRIS COUNTY LINE FOR THE TERMINUS OF THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS EAST ON THE TOWNSHIP LINE FOR 6 MILES TO THE NORTHEAST CORNER OF SECTION 1-17-11 ON THE RANGE LINE TO COMMENCE THIS ROAD SURVEY

- 5) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN AN AGREEMENT SURVEY DATED APRIL 15, 1880 FILED IN THE REGISTER OF SEEDS OFFICE ON PAGE 553 FOR HORN R. MAYS, JESSE FOSTER, AND REBECCA M. CURTIS TO ESTABLISH THE LINE BETWEEN THE EAST 1/2 OF THE SOUTHEAST 1/4 AND THE WEST 1/2 OF THE SOUTHEAST 1/4, ALSO THE SOUTHEAST CORNER OF THE WEST 1/2 OF THE SOUTHEAST 1/4, AND THE NORTHEAST CORNER OF THE WEST 1/2 OF THE SOUTHEAST 1/4, ALSO THE NORTHWEST CORNER OF THE SOUTHWEST 1/4, ALL IN SECTION 31-16-11, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 31-16-11 AT THE TOWNSHIP CORNER ON THIS AGREEMENT SURVEY. THIS SURVEY IS FILED AT SURVEY F31001 IN THE SURVEY FILE FOR TOWNSHIP 16-11.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 40.06-1/4 CHAINS NORTH ON THE RANGE LINE TO THE GOVERNMENT 1/4 CORNER SECTION STONE HE FOUND AND **HE RESET** FOR THE WEST 1/4 CORNER OF SECTION 31-16-11
- 2) 80.12-1/2 CHAINS NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 31-16-11

- 6) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 171, A CONSENT SURVEY OF ALL INTERESTED PARTIES RECORDED IN SURVEY BOOK "E" ON PAGE 171 DATED JUNE 9, 1887 TO LOCATED THE CENTER AND EAST 1/4 CORNERS OF SECTION 1-17-10, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 1-17-10 AT THE TOWNSHIP CORNER ON THIS CONSENT SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,645-2/3' WEST ON THE TOWNSHIP LINE TO THE TEMPORARY STAKE HE SET FOR THE NORTH 1/4 CORNER OF SECTION 1-17-10
- 2) 5,291-1/3' WEST ON THE TOWNSHIP LINE TO THE THEORETICAL LOCATION FOR THE NORTHWEST CORNER OF SECTION 1-17-10
- 3) 7,937' WEST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 2-17-10
- 4) 2,640-3/4' SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 1-17-10
- 5) 5,281-1/2' SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 1-17-10

- 7) REA BOOK NUMBER 30 ON PAGE 16 SHOWS A **STONE** AT THE SOUTHWEST CORNER OF SECTION 31-16-11 AT THE TOWNSHIP CORNER.

- 1) FOUND THIS STONE AT 1' DEEP
- 2) 33' SW TO A WITNESS PIN
- 3) 33' SW TO A WITNESS PIN
- 4) 39.3' NW TO A 24" MAPLE TREE
- 5) 34.2' SW TO A TELEPHONE POLE

CONTINUED ON PAGE 3

- 8) REA BOOK 30 ON PAGE 16 SAYS THAT **THEY FOUND THE STONE AT 1 FOOT DEEP** AT THE SOUTHWEST CORNER OF SECTION 31-16-11 AT THE TOWNSHIP CORNER.
  - 1) 33' SW TO A WITNESS PIN 2' NORTH OF A TELEPHONE POLE
  - 2) 33' NW TO A WITNESS PIN 7' OR 8' SOUTH OF A TREE
  
- 9) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 16-11 SHOWS A **STONE** AT THE "SW CORNER SECTION 31-16-11" AT THE TOWNSHIP CORNER.
  - 1) 39.3' NW TO A 24" MAPLE TREE
  - 2) 34.2' SW TO A TELEPHONE POLE
  
- 10) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 17-10 SHOWS A **STONE & PIN** AT THE "NE CORNER SECTION 01-17-10" AT THE TOWNSHIP CORNER.
  - 1) 18.65' WEST TO A STONE CORNER POST
  - 2) 34.95' SE TO A SPIKE IN A CORNER POST
  - 3) 38.95' NE TO A SPIKE IN A CORNER POST
  
- 11) SURVEY F07001 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR A SURVEY IN THE NORTHEAST 1/4 OF SECTION 7-17-11, SHOWS A **STONE** AT THE NORTHWEST CORNER OF SECTION 6-17-11 AT THE TOWNSHIP CORNER. THERE IS NO NAME OR DATE ON THIS SURVEY.
  - 1) 40.7' NW TO A SPIKE PO
  - 2) 40.3' NW TO A SPIKE PO
  - 3) 42.5' SW TO A SPIKE PO
  
- 12) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN LAND SURVEY REFERENCE REPORT DATED OCTOBER 2, 2006 FOR PROJECT NUMBER 06292-02 TO SURVEY THE NORTH LINE OF SECTION 1-17-10 AND THE SOUTH LINE OF SECTION 36-16-10 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT FOR BRIDGE REPLACEMENT PROJECT NUMBER 06-KT, SURVEY F01001 IN THE SURVEY FILE FOR TOWNSHIP 17-10 AND SURVEY F36001 IN THE SURVEY FILE FOR TOWNSHIP 16-10, SAID THAT **HE FOUND THE STONE AT ABOUT 2 FEET DEEP AT THE PLACE INDICATED BY OLD TIES HE FOUND AT THE OFFICE OF THE COUNTY ENGINEER AT THE NORTHEAST CORNER OF SECTION 1-17-10 AT THE TOWNSHIP CORNER. HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP ON THE NORTH AND SOUTH SIDES OF THE STONE, AND HE SET A 5/8" REBAR WITH A LYON COUNTY CAP OVER THE TOP CENTER OF THE STONE AT THE NORTHEAST CORNER OF SECTION 1-17-10.**
  - 1) 40.70' NE TO A 60 D NAIL & WASHER IN A POWER POLE
  - 2) 49.25' NE TO A 40 D NAIL & WASHER IN THE SIDE OF A BRACE POST
  - 3) 48.25' SSW TO THE NEAR FACE OF A CORNER PIPE POST
  - 4) 48.35' WSW TO THE NEAR FACE OF A CORNER PIPE POST
  - 5) IN THE TRAVELED WAY OF GRAVEL COUNTY ROAD "G" NORTH-SOUTH
  - 6) IN THE TRAVELED WAY OF GRAVEL COUNTY ROAD 310 EAST-WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

  - 1) 600.00' WEST ON THE TOWNSHIP LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR A P.O.T.
  - 2) 1,400.00' WEST ON THE TOWNSHIP LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR A P.O.T.
  - 3) 2,650.31' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 1-17-10
  - 4) 5,300.62' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 1-17-10

CONTINUED ON PAGE 4

- 13) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 25, 2008 FOR PROJECT NUMBER 08191-02, A SURVEY OF THE EAST LINE OF SECTION 1-17-10 AND THE WEST LINE OF SECTION 6-17-11 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT FOR BRIDGE REPLACEMENT PROJECT NUMBER 08-QW, SURVEY F01002 IN THE SURVEY FILE FOR TOWNSHIP 17-10 AND SURVEY F06002 IN THE SURVEY FILE FOR TOWNSHIP 17-11, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP OVER THE STONE** AT THE NORTHWEST CORNER OF SECTION 6-17-11 AT THE TOWNSHIP CORNER FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE DATED OCTOBER 2006.
- 1) 40.7' NE TO A 60 D NAIL & WASHER IN A POWER POLE
  - 2) 49.25' NE TO A 40 D NAIL & WASHER IN THE SIDE OF A BRACE POST
  - 3) 48.25' SSW TO THE NEAR FACE OF A CORNER PIPE POST
  - 4) 48.35' WSW TO THE NEAR FACE OF A CORNER PIPE POST
  - 5) IN THE TRAVELED-WAY OF GRAVEL COUNTY ROAD "G" NORTH-SOUTH
  - 6) IN THE TRAVELED-WAY OF GRAVEL COUNTY ROAD 310 EAST-WEST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 299.79' SOUTH ON THE RANGE LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR A P.O.T.
  - 2) 1,099.79' SOUTH ON THE RANGE LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR A P.O.T.
  - 3) 2,643.95' SOUTH ON THE RANGE LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 6-17-11
  - 4) 5,287.91' SOUTH ON THE RANGE LINE TO THE 1/2" REBAR FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 6-17-11
- 14) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 12, 2009 FOR PROJECT NUMBER 09119-02 TO ESTABLISH THE NORTH LINE OF THE NORTHEAST 1/4 OF FRACTIONAL SECTION 6-17-11 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT FOR BRIDGE REPLACEMENT PROJECT NUMBER 04-EP, SURVEY F06003 IN THE SURVEY FILE FOR TOWNSHIP 17-11, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP OVER THE STONE** AT THE NORTHWEST CORNER OF SECTION 6-17-11 AT THE TOWNSHIP CORNER FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE.
- 1) 40.7' NE TO A 60D NAIL & WASHER IN A POWER POLE
  - 2) 49.25' NE TO A 40 D NAIL & WASHER IN THE SIDE OF A BRACE POST
  - 3) 48.25' SSW TO THE NEAR FACE OF A CORNER PIPE POST
  - 4) 48.35' WSW TO THE NEAR FACE OF A CORNER PIPE POST
  - 5) IN THE TRAVELED WAY OF GRAVEL COUNTY ROAD "G" NORTH-SOUTH
  - 6) IN THE TRAVELED WAY OF GRAVEL COUNTY ROAD 310 EAST-WEST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,346.53' EAST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP SET FOR THE NORTHWEST CORNER OF THE NE1/4 OF FRACTIONAL SECTION 6-17-11
  - 2) 4,993.90' EAST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP SET AT THE POSITION OF A FOUND STONE AT THE NORTHEAST CORNER OF THE NE1/4 OF FRACTIONAL SECTION 6-17-11
- 15) RICHARD J. IMAN, L.S. 1450, OF BG CONSULTANTS, INC. IN A LAND SURVEY REFERENCE REPORT DATED JUNE 5, 2009 FOR PROJECT NUMBER 09-1119E FOR THE LYON COUNTY HIGHWAY DEPARTMENT FOR BRIDGE REPLACEMENT PROJECT NUMBER 04-EP, SAID THAT **HE FOUND THE 5/8" LYON COUNTY CAPPED BAR AT 1" BELOW THE SURFACE [OVER THE STONE]** AT THE SOUTHWEST CORNER OF SECTION 31-16-11 AT THE TOWNSHIP CORNER FROM THE TIES BY STEVEN S.

BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, DATED JUNE 25, 2008 AND MAY 6, 2009.

- 1) 40.7' NE TO A FOUND 60 D NAIL & WASHER IN A POWER POLE
- 2) 49.2' NE TO A FOUND 40 D NAIL & WASHER IN THE SIDE OF A BRACE POST
- 3) 48.2' SSW TO THE NEAR FACE OF A CORNER PIPE POST AT GROUND LEVEL
- 4) 48.3' WSW TO THE NEAR FACE OF A CORNER PIPE POST AT GROUND LEVEL
- 5) 45.9' SE TO THE TOP CENTER OF USGS STAMPED "9JK 1971" STANDARD DISC
- 6) ON THE TRAVEL WAY OF THE NORTH-SOUTH-EAST-WEST GRAVEL ROADS

16) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 3, 2010 FOR PROJECT NUMBER 10164-02 TO ESTABLISH THE NORTHWEST CORNER OF THE EAST 1/2 OF THE NORTHWEST 1/4 AND THE NORTHWEST CORNER OF THE EAST 1/2 OF THE NORTHEAST 1/4 OF SECTION 6-17-11 FOR THE LYON COUNTY HIGHWAY DEPARTMENT FOR BRIDGE REPLACEMENT PROJECT NUMBER 04-EP, SURVEY F06005 IN THE SURVEY FILE FOR TOWNSHIP 17-11, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP OVER THE STONE** AT THE NORTHWEST CORNER OF SECTION 6-17-11 AT THE TOWNSHIP CORNER FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE. HE NOTED ON HIS SURVEY THAT THE 1/16<sup>TH</sup> CORNERS WERE RESET BY RETRACING A SURVEY BY MILLIKEN RECORDED IN PERMANENT SURVEY BOOK "C" ON PAGE 62 (1874

- 1) 40.7' NE TO A 60 D NAIL & WASHER IN A POWER POLE
- 2) 49.25' NE TO A 40 D NAIL & WASHER IN THE SIDE OF A BRACE POST
- 3) 48.25' SSW TO THE NEAR FACE OF A CORNER PIPE POST
- 4) 48.33' WSW TO THE NEAR FACE OF A CORNER PIPE POST
- 5) IN THE TRAVELED WAY OF GRAVEL COUNTY ROAD "G" NORTH-SOUTH
- 6) IN THE TRAVELED WAY OF GRAVEL COUNTY ROAD 310 EAST-WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,023.02' EAST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE E1/2 OF THE NW1/4 OF SECTION 6-17-11 [MILLIKEN = 1,020']
- 2) 2,346.90' EAST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 6-17-11 [MILLIKEN = 2,340]
- 3) 3,670.44' EAST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 6-17-11 [MILLIKEN = 3,660']
- 4) 4,993.98' EAST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 6-17-11 [MILLIKEN = 4,980]

NORTHWEST CORNER SECTION 06-17-11