

**WEST 1/4 CORNER SECTION 06, TOWNSHIP 17 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 54 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 13" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 1 & 6 ON THE WEST TOWNSHIP BOUNDARY ON JANUARY 7, 1861.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.00 CHAINS NORTH ON THE RANGE LINE TO THE 20" X 10" X " LIMESTONE THEY SET FOR THE CORNER TO TOWNSHIPS 16 & 17 SOUTH, RANGES 10 & 11 EAST, AT THE NORTHWEST CORNER OF SECTION 6-17-11
  - 2) 40.00 CHAINS SOUTH ON THE RANGE LINE TO THE 24" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 6 & 7-17-11
  
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 7 OF THE 8<sup>TH</sup> TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 62 DATED MARCH 5, 1874 TO ESTABLISH THE CENTER CORNER, TO SUBDIVIDE THE SOUTHWEST 1/4 BY A LINE NORTH & SOUTH, THE SOUTHEAST 1/4 BY A LINE NORTH & SOUTH, THE EAST 1/2 OF THE NORTHWEST 1/4 BY A LINE EAST & WEST, THE NORTHEAST 1/4 BY A LINE NORTH & SOUTH, AND THE WEST 1/2 BY A LINE EAST & WEST, ALL IN SECTION 6-17-11, STATES THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 6-17-11 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 1,003' EAST TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE NW1/4 OF SECTION 6-7-11
  - 2) 2,323' EAST TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 6-17-11
  - 3) 2,630-1/2' EAST TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE NE1/4 OF SECTION 6-17-11
  - 4) 4,938' EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SEC. 6-17-11
  
- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 171, A **CONSENT SURVEY** OF ALL INTERESTED PARTIES RECORDED IN SURVEY BOOK "E" ON PAGE 171 DATED JUNE 9, 1887 TO LOCATED THE CENTER CORNER AND EAST 1/4 CORNER OF SECTION 1-17-10, SAID THAT **HE SET A 4" X 10" X 18" LIMESTONE** FOR THE EAST 1/4 CORNER OF SECTION 1-17-10 ON THE RANGE LINE AT HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 1-17-10 AND THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 1-17-10 ON THIS **CONSENT SURVEY**.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,640-3/4' NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 1-17-10 AT THE TOWNSHIP CORNER
  - 2) 2,640-3/4' SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 1-17-10
  
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 25, 2008 FOR PROJECT NUMBER 08191-02, A SURVEY OF THE EAST LINE OF SECTION 1-17-10 AND THE WEST LINE OF SECTION 6-17-11 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT FOR BRIDGE REPLACEMENT PROJECT NUMBER 08-QW, SURVEY F01002 IN THE SURVEY FILE FOR TOWNSHIP 17-10 AND SURVEY F06002 IN THE SURVEY FILE FOR TOWNSHIP 17-11, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE AT THE WEST 1/4 CORNER OF SECTION 6-17-11, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **LOST**. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE WEST 1/4 CORNER OF SECTION 6-17-11 ON THE

RANGE LINE AT HALFWAY BETWEEN THE NORTHWEST CORNER OF SECTION 6-17-11 AT THE TOWNSHIP CORNER AND THE SOUTHWEST CORNER OF SECTION 6-17-11.

- 1) 28.5' ENE TO A CONCRETE NAIL & BOTTLE CAP IN A POWER POLE
- 2) 70.35' SSE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
- 3) 18' SOUTH TO A DRIVEWAY TO THE EAST
- 4) 3' SOUTH TO A LINE OF FENCE TO THE WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,544.15' NORTH ON THE RANGE LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR A P.O.T.
- 2) 2,344.16' NORTH ON THE RANGE LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP SET FOR A P.O.T.
- 3) 2,643.95' NORTH ON THE RANGE LINE TO THE 5/8" REBAR OVER THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 6-17-11 AT THE TOWNSHIP CORNER
- 4) 2,643.96' SOUTH ON THE RANGE LINE TO THE 1/2" REBAR HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 6-17-11

- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 25, 2014 FOR PROJECT NUMBER 14020-02, A SURVEY OF A TRACT IN THE SOUTHWEST 1/4 OF SECTION 6-17-11 FOR ANDREW SMART, SURVEY F06007 IN THE SURVEY FILE FOR TOWNSHIP 17-11, SAID THAT **HE FOUND THE 5/8" IRON PIN WITH A LYON COUNTY CAP** AT THE WEST 1/4 CORNER OF SECTION 6-17-11 ON THE RANGE LINE FROM HIS EXISTING REFERENCE TIES ON FILE AT THE LYON COUNTY SURVEYORS OFFICE FROM JUNE 2008.

- 1) 28.4' EAST TO A CONCRETE NAIL & BOTTLECAP IN A POWER POLE
- 2) 27.2' WSW TO THE TOP CENTER OF A 5" PIPE CORNER FENCE POST
- 3) 27.8' WNW TO THE TOP CENTER OF A 5" PIPE BRACE POST
- 4) 6' SOUTH TO A LINE OF FENCE TO THE WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 20.00' EAST ON THE 1/2 SECTION LINE TO THE 1/2" IRON PIN WITH HIS "LS 752" CAP HE SET FOR A **WITNESS CORNER**
- 2) 900.00' EAST TO THE 1/2" IRON PIN WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST TRACT CORNER
- 3) 2,313.70' EAST TO THE 5/8" IRON PIN WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 6-17-11
- 4) 580.00' SOUTH ON THE RANGE LINE TO THE SOUTHWEST TRACT CORNER, AS WITNESSED BY THE 1/2" IRON PIN WITH HIS "LS 752" CAP HE SET AT 20.00' EAST
- 5) 2,644.07' SOUTH ON THE RANGE LINE TO THE 1/2" IRON PIN HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 6-17-11

WEST QUARTER CORNER 06-17-11