

NORTH 1/16TH CORNER OF SOUTHEAST 1/4 SECTION 07, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 130 RECORDED IN SURVEY BOOK "A" ON PAGES 214 & 215 DATED JULY 3, 1869 TO SURVEY THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 7-17-11, SAID THAT **HE SET A STONE** FOR THE NORTH 1/2/4 CORNER OF THE SOUTHEAST 1/4 OF SECTION 7-16-11 EQUIDISTANT BETWEEN THE STONE THAT HE SET FOR THE CENTER CORNER OF SECTION 7-16-11 AND THE STONE THAT HE FOUND AT THE EAST 1/4 CORNER OF SECTION 7-16-11 ON THIS SURVEY.

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 98 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 20 DATED APRIL 18, 1873 TO SUBDIVIDE THE NORTHEAST 1/4 OF SECTION 7-17-11 INTO EAST AND WEST HALVES, SAID THAT **HE SET A STONE** FOR PERMANENT SOUTH 1/2/4 CORNER OF THE NORTHEAST 1/4 OF SECTION 7-17-11 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE CENTER CORNER OF SECTION 7-17-11 AND THE STONE THAT HE FOUND AT THE EAST 1/4 CORNER OF SECTION 7-16-11 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 1,324-1/2' WEST TO THE STONE HE FOUND AT THE CENTER CORNER OF SECTION 7-16-11
 - 2) 1,324-1/2' EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 7-16-11

- 3) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 10, 2001, FOR PROJECT NUMBER 99476-02, SURVEY F07004 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR THREE TRACTS OF LAND LYING IN THE NORTHEAST 1/4 OF SECTION 7-17-11, SAID THAT SHE CONSIDERED THAT THE SOUTH 1/16TH CORNER OF THE NORTHEAST 1/4 OF SECTION 7-17-11 WAS **LOST**. **SHE SET A 1/2" X 24" REBAR WITH HER "LS 1130" CAP** FOR THE SOUTH 1/16TH CORNER OF THE NORTHEAST 1/4 OF SECTION 7-16-11 AT ONE-HALF THE DISTANCE AND ON LINE BETWEEN THE EAST 1/4 CORNER AND THE CENTER CORNER OF SECTION 7-16-11.
 - 1) 31.95' SSE TO A MASONRY NAIL & BOTTLE CAP IN A TRIPLE 30" HEDGE TREE
 - 2) 29.95' SSW TO A MASONRY NAIL & BOTTLE CAP IN A DOUBLE 48" HEDGE TREEHER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 330.00' WEST TO THE SOUTHWEST CORNER OF TRACT #1, AS WITNESSED BY THE 1/2" REBAR WITH HER "LS 752" CAP SHE SET AT 60.00' WEST AND AT 175.00' EAST
 - 2) 1,322.17' WEST TO THE STONE SHE FOUND AT THE SOUTHWEST CORNER OF THE NE1/4 OF SECTION 7-16-11
 - 3) 887.17' EAST TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE SOUTHWEST CORNER OF TRACT #3
 - 4) 1,322.17' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 7-16-11
 - 5) 330.00' NORTH TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE NORTHEAST CORNER OF TRACT #1
 - 6) 1,312.60' NORTH TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE NORTHWEST CORNER OF THE SE1/4 OF THE NE1/4 OF SECTION 7-16-11
 - 7) 2,625.17' NORTH TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE NORTH 1/16TH CORNER OF THE NE1/4 OF SECTION 7-16-11

NORTH SIXTEENTH CORNER SOUTHEAST QUARTER 07-17-11