

**WEST 1/16<sup>TH</sup> CORNER OF NORTHEAST 1/4 SECTION 07, TOWNSHIP 17 SOUTH, RANGE 11 EAST**

1) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 10, 2001, FOR PROJECT NUMBER 99476-02, SURVEY F07004 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR THREE TRACTS OF LAND LYING IN THE NORTHEAST 1/4 OF SECTION 7-17-11, SAID THAT **SHE SET A 1/2" X 24" REBAR WITH HER "LS 1130" CAP** FOR THE WEST 1/16<sup>TH</sup> CORNER OF THE NORTHEAST 1/4 OF SECTION 7-17-11 ON LINE AND AT ONE-HALF THE DISTANCE BETWEEN THE CENTER CORNER OF SECTION 7-17-11 AND THE NORTH 1/4 CORNER OF SECTION 7-17-11. SHE NOTED THAT THIS CORNER FALLS IN THE EAST SHOULDER OF COUNTY ROAD "G5" ALONG THE GRASS LINE OF THE SHOULDER

- 1) 43.60' NW TO A 5/8" REBAR OFF THE WEST SHOULDER OF COUNTY ROAD "G5" [REFERENCE POINT]
- 2) 64.65' SW TO A MASONRY NAIL & BOTTLECAP IN A 12" STUMP
- 3) 112.80' SSE TO A MASONRY NAIL & BOTTLECAP IN A POWER POLE
- 4) 10.80' WEST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "G5" [DIRT ROAD]

**HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 1,309.29' NORTH TO THE 1/2" REBAR SHE FOUND AT THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 7-21-11
- 2) 1,309.29' SOUTH TO THE STONE SHE FOUND AT THE SOUTHWEST CORNER OF THE NE1/4 OF SECTION 7-21-11
- 3) 1,323.26' EAST TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE NORTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 7-17-11
- 4) 2,646.52' EAST TO THE 1/2" REBAR WITH HER "LS 11130" SHE SET FOR THE EAST 1/16<sup>TH</sup> CORNER OF THE NE1/4 OF SECTION 7-17-11

WEST SIXTEENTH CORNER NORTHEAST QUARTER 07-17-11