

NORTH 1/4 CORNER SECTION 08, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) ON PAGE 327 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 5 & 8-17-11 AT 40.00 CHAINS EAST OF THE NORTHWEST CORNER AND 18.00 CHAINS WEST OF THE FRACTIONAL CORNER TO SECTIONS 5 & 8-17-11 ON THE EAST BOUNDARY OF THE KANSAS INDIAN RESERVATION. THIS FRACTIONAL CORNER IS MARKED BY A LIMESTONE 20" X 14" X 3" AND IS LOCATED 21.54 CHAINS WEST OF THE NORTHEAST CORNER OF SECTION 8-17-11 AS SET ON PAGE 321 OF THESE FIELD NOTES.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS WEST TO THE 18" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5, 6, 7 & 8
 - 2) 18.00 CHAINS EAST TO THE 20" X 14" X 3" LIMESTONE THEY SET ON THE EAST BOUNDARY OF THE KANSAS INDIAN RESERVATION
 - 3) 39.54 CHAINS EAST TO THE 22" X 13" X 7" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4, 5, 8 & 9

- 2) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 130 DATED MAY 2 & 3, 1882 AT THE REQUEST OF H. T. SWARNER TO SURVEY AND ESTABLISH IN TOWNSHIP 17, RANGE 11, THE CENTER OF SECTION 5, THE CORNER ON THE INDIAN RESERVE LINE, AND THE SOUTH LINE OF SECTION 5, AND THE 1/2 MILE CORNER ON THE INDIAN RESERVE LINE IN SECTION 5, AND SUCH OTHER LINES AND CORNERS AS MAY BE NECESSARY TO COMPLETE THE SURVEY, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 5-17-11 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 39.90 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 5-17-11
 - 2) 77.39 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 5-17-11 ON THE TOWNSHIP LINE

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 37, A **ROAD/PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 218 DATED FEBRUARY 18, 1902 FOR A COUNTY ROAD IN TOWNSHIP 17-11 PETITIONED BY W. B. DeBAUN AND OTHERS TO ESTABLISH THE ROAD BETWEEN SECTIONS 5 & 6 IN 17-11, AND ORDERED BY THE BOARD OF COUNTY COMMISSIONERS TO LOCATE THE SECTION LINE BETWEEN SECTIONS 5 & 6 IN 17-11 ON OCTOBER 2, 1902, SAID THAT **HE FOUND THE STONE** AT THE SOUTH CORNER OF SECTION 5-17-11 ON THIS **ROAD/PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 24.14 CHAINS EAST TO THE STONE HE FOUND ON THE INDIAN RESERVE LINE ON THE SOUTH SIDE OF THE SE1/4 OF SECTION 5-17-11
 - 2) 39.92 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 5-17-11
 - 3) 39.90 CHAINS WEST TO THE STONE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 5-17-11
 - 4) 114.73 CHAINS WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 6-17-11 ON THE RANGE LINE

- 4) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 10, 2001, FOR PROJECT NUMBER 99476-02, SURVEY F08002 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR A SURVEY OF TWO TRACTS IN THE NORTHWEST 1/4 OF SECTION 8-17-11, SAID THAT SHE CONSIDERED THAT THE NORTH 1/4 CORNER OF SECTION 8-17-11 WAS BOTH **OBLITERATED** AND **LOST**. SHE RESET THIS CORNER AT THE PRORATED GLO DISTANCE FROM THE

NORTHWEST CORNER OF SECTION 8-17-11 FOR THE EAST-WEST POSITION, AND IN HARMONY WITH PHYSICAL EVIDENCE FOR THE NORTH-SOUTH POSITION: I.E. SHE CONSIDERED IT **LOST** IN EAST-WEST POSITION AND **OBLITERATED** IN NORTH-SOUTH POSITION. **SHE SET A 5/8" REBAR WITH A LYON COUNTY CAP** FOR THE NORTH 1/4 CORNER OF SECTION 8-17-11.

- 1) 28.60' NW TO A MASONRY NAIL & BOTTLE CAP IN A POWER POLE
- 2) 21.0' NORTH TO THE TOP CENTER OF A STONE POST
- 3) 35.5' SW TO A MASONRY NAIL & BOTTLE CAP IN THE WEST GATE POST
- 4) 24.2' NE TO A MASONRY NAIL & BOTTLE CAP IN A TIE POST OF AN EAST-WEST FENCE
- 5) 20.05' SOUTH TO A MASONRY NAIL & BOTTLE CAP IN A CORNER POST
- 6) IN THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 300 EAST-WEST
- 7) IN LINE WITH A FENCE RUNNING TO THE SOUTH [EXTENDED]

HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,632.84' WEST TO THE STONE SHE FOUND WITH 1/2" REBARS WITH "LS 752" CAPS ON THE NORTH & SOUTH SIDES OF THE STONE AT THE NORTHWEST CORNER OF SECTION 8-17-11
- 2) 1,212.17' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE NORTHEAST CORNER OF LOT 5 ON THE NORTH LINE OF THE NE1/4 OF SECTION 8-17-11 ON THE EAST BOUNDARY OF THE KANSAS INDIAN RESERVATION
- 3) 2,634.29' EAST TO THE STONE SHE FOUND AT THE NORTHEAST CORNER OF SECTION 8-17-11
- 4) 2,648.39' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE CENTER CORNER OF SECTION 8-17-11
- 5) 5,282.71' SOUTH TO THE 1/2" REBAR WITH "LS 752" CAP SHE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 8-17-11

- 5) AARON C. DAVIS, L.S. 1368, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 22, 2003, FOR PROJECT NUMBER 03455-02, SURVEY F08003 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR A 7.20 ACRE TRACT OF LAND, BEING PART OF LOT 5 OF THE FRACTIONAL NORTHEAST 1/4 OF SECTION 8-17-11, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE NORTH 1/4 CORNER OF SECTION 8-17-11 [AKA NORTHWEST CORNER OF LOT 5] FROM EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE.

- 1) 28.60' NW TO A MASONRY NAIL & BOTTLE CAP IN A POWER POLE
- 2) 21.0' NORTH TO THE TOP CENTER OF A STONE POST
- 3) 35.5' SW TO A MASONRY NAIL & BOTTLE CAP IN THE WEST GATE POST
- 4) 24.2' NE TO A MASONRY NAIL & BOTTLE CAP IN A TIE POST OF AN EAST-WEST FENCE
- 5) 20.05' SOUTH TO A MASONRY NAIL & BOTTLE CAP IN A CORNER POST
- 6) IN THE CENTERLINE OF COUNTY ROAD 300 EAST-WEST
- 7) IN LINE WITH A FENCE RUNNING TO THE SOUTH [EXTENDED]

THE SURVEY DRAWING SIGNED BY STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, SHOWS THE FOLLOWING INFORMATION:

- 1) 347.88' EAST TO THE 1/2" REBAR WITH "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE 7.20 ACRE TRACT
- 2) 1,212.17' EAST TO THE 5/8" CAPPED REBAR HE FOUND AT THE NORTHEAST CORNER OF LOT 5 ON THE NORTH LINE OF THE FRACTIONAL NORTHEAST 1/4 OF SECTION 8-17-11
- 3) 761.20' SOUTH TO THE 1/2" REBAR WITH "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE 7.20 ACRE TRACT
- 4) 2,648.39' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE CENTER CORNER OF SECTION 8-17-11

CONTINUED ON PAGE 3

- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 12, 2010 FOR PROJECT NUMBER 10112-02, SURVEY F05001 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR A SURVEY OF THE WEST HALF OF THE FRACTIONAL NORTHWEST 1/4 AND THE EAST HALF OF THE FRACTIONAL NORTHWEST 1/4; [AKA GOVERNMENT LOT 7 AND THE WEST HALF OF GOVERNMENT LOT 8 AND GOVERNMENT LOT 6 AND THE EAST HALF OF GOVERNMENT LOT 8] ALL IN SECTION 5-17-11 FOR EK REALTY, SAID THAT **HE FOUND THE 5/8" REBAR WITH THE LYON COUNTY CAP** AT THE SOUTH 1/4 CORNER OF SECTION 5-17-11 [AKA SOUTHEAST CORNER OF GOVERNMENT LOT 12 IN THE FRACTIONAL SW1/4 OF SECTION 5-17-11] FROM EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE.
- 1) 20.25' SOUTH TO A SPIKE & BOTTLE CAP IN THE TOP OF A CORNER FENCE POST
 - 2) 16.5' SSW TO THE TOP CENTERLINE OF THE EAST END OF AN 18" CMP
 - 3) 27.0' WSW TO THE TOP CENTERLINE OF THE WEST END OF AN 18" CMP
 - 4) IN LINE WITH THE FENCE AND HEDGE TO THE SOUTH EXTENDED
 - 5) IN THE CENTERLINE TRAVELED WAY OF ROAD 300 EAST-WEST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,632.85' WEST TO THE LIMESTONE, WITH 1/2" REBARS WITH HIS "LS 752" CAPS ON THE NORTH AND SOUTH SIDES OF THE LIMESTONE, HE FOUND AT THE SOUTHWEST CORNER OF THE FRACTIONAL SW1/4 OF SECTION 5-17-11 [AKA SOUTHWEST CORNER OF GOVERNMENT LOT 12]
 - 2) 2,647.48' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE FRACTIONAL NW1/4 OF SECTION 5-17-11 [AKA NORTHEAST CORNER OF GOVERNMENT LOT 12 AND SOUTHEAST CORNER OF GOVERNMENT LOT 8]
 - 3) 5,111.84' NORTH TO THE #5 SQUARE REBAR HE FOUND AT THE NORTHEAST CORNER OF THE FRACTIONAL NW1/4 OF SECTION 5-17-11 [AKA NORTHEAST CORNER OF GOVERNMENT LOT 6]
- 7) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 22, 2012 FOR PROJECT 12-B3, THE REPLACEMENT OF TIMBER CULVERT 939.8-494.0 WITH A 30 FOOT ALL STEEL BRIDGE, **FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE NORTH 1/4 CORNER OF SECTION 8-17-11 FROM THE TIES OF AARON C. DAVIS, L.S. 1368, DEPUTY COUNTY SURVEYOR, DATED OCTOBER 22, 2003 AND THE TIES OF STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, DATED MAY 12, 2010 ON FILE IN THE COUNTY SURVEYOR'S OFFICE.
- 1) 24.2' NE TO A FOUND MASONRY NAIL & BOTTLECAP IN A TIE POST OF AN EAST-WEST FENCE
 - 2) 16.6' SSW TO THE TOP CENTERLINE OF THE EAST END OF AN 18" CMP
 - 3) 27.2' WSW TO THE TOP CENTERLINE OF THE WEST END OF AN 18" CMP
 - 4) 20.6' SOUTH TO A FOUND NAIL & BOTTLE CAP IN THE TOP OF A CORNER FENCE POST
 - 5) 20.1' SOUTH TO A FOUND NAIL & BOTTLECAP IN THE WEST FACE OF THE SAME CORNER FENCE POST
 - 6) 28.7' NW TO A FOUND NAIL & BOTTLECAP IN THE SOUTHWEST FACE OF A POWER POLE
 - 7) IN LINE WITH THE FENCE AND HEDGE TO THE SOUTH EXTENDED
 - 8) IN THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD 300 EAST-WEST

NORTH QUARTER CORNER 08-17-11