

NORTHWEST CORNER SECTION 08, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) ON PAGE 326 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 12" X 3"** FOR THE CORNER TO SECTIONS 5, 6, 7 & 8-17-11.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH TO THE 20" X 10" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 5 & 6-17-11
- 2) 78.90 CHAINS NORTH TO THE 18" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5, 6, 31 & 32 ON THE TOWNSHIP LINE
- 3) 40.00 CHAINS EAST TO THE 16" X 14" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTION 5 & 8-17-11
- 4) 58.00 CHAINS EAST TO THE 20" X 14" X 3" LIMESTONE THEY SET FOR ON THE EAST BOUNDARY OF THE KANSAS INDIAN RESERVATION
- 5) 79.54 CHAINS EAST TO THE 22" X 13" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4, 5, 8 & 9-17-11

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 100 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 402 TO 404 PETITIONED BY WILLIAM GRIMSLEY AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 17-11 [PACKET 393 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 18, 1880, WAS ESTABLISHED AS A 60 FOOT WIDE ROAD ON JANUARY 10, 1881 AS NOTED BY J. M. GRIFFITH, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 10, 1881 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST OF SECTION 8-17-11 TO COMMENCE THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 9-17-11 AT THE TERMINATION OF THIS ROAD SURVEY
- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT PAGE 194 DATED SEPTEMBER 18, 1880, FOR A ROAD SURVEY IN TOWNSHIP 17-11 APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 8-17-11 TO COMMENCE THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 9-17-11 AT THE TERMINUS OF THIS ROAD SURVEY

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 37, A **ROAD/PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 218 DATED FEBRUARY 18, 1902 FOR A COUNTY ROAD IN TOWNSHIP 17-11 PETITIONED BY W. B. DeBAUN AND OTHERS TO ESTABLISH THE ROAD BETWEEN SECTIONS 5 & 6-17-11, AND ORDERED BY THE BOARD OF COUNTY COMMISSIONERS TO LOCATE THE SECTION LINE BETWEEN SECTIONS 5 & 6-17-11 ON OCTOBER 2, 1902, SAID THAT **HE SET A 15" X 10" X 5" STONE MARKED "R" ON THE NORTH SIDE** FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 5-17-11, BASED ON THE AFFIDAVIT OF WILLIAM GRIMSLEY, TO BEGIN THIS ROAD SURVEY FOR A 40 FOOT WIDE ROAD, LAYING 20 FEET EACH SIDE OF THE SURVEYED LINE ON THIS **ROAD/PERMANENT SURVEY**. SEE THE AFFIDAVIT MADE AS PART OF THIS ROAD/PERMANENT SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) 74.83 CHAINS WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 6-17-11 ON THE RANGE LINE
 - 2) 39.90 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 5-17-11
 - 3) 64.04 CHAINS EAST TO THE STONE HE FOUND ON THE INDIAN RESERVE LINE ON THE SOUTH SIDE OF THE SE1/4 OF SECTION 5-17-11
 - 4) 79.82 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 5-17-11
 - 5) THIS ROAD EXTENDS ONE MILE NORTH TO THE 18" X 10" X 3" STONE MARKED "R" ON THE SOUTH FACE HE SET FOR THE NORTHWEST CORNER OF SECTION 5-17-11 ON THE TOWNSHIP LINE AT THE TERMINUS OF THIS ROAD SURVEY
- 5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER RECORDED IN ROAD RECORD BOOK "D" ON PAGES 141 THROUGH 144 PETITIONED BY W. D. DeBAUN AND OTHERS FOR A ROAD IN TOWNSHIP 17-11 [PACKET 721 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON FEBRUARY 18, 1902, WAS ESTABLISHED AND OPENED AS A 40 FOOT WIDE ROAD, 20 FEET ON EACH SIDE OF THE SECTION LINE, AND RECORDED ON MARCH 15, 1902 BY ALVA J. SMITH, COUNTY SURVEYOR, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 5-17-11 TO BEGIN THIS ROAD SURVEY.
- HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 5-17-11 ON THE TOWNSHIP LINE AT THE TERMINUS OF THIS ROAD SURVEY
- 6) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 17-11 SHOWS A **STONE** AT THE "NE CORNER SECTION 7-17-11".
- 1) 33.0' NW TO A SPIKE IN A GUY POLE
 - 2) 33.6' NE TO A CORNER FENCE POST
 - 3) 26.6' SE TO A SPIKE IN A TELEPHONE POLE
- 7) COMMISSIONER'S ROAD JOURNAL BOOK "B", PAGE 182
ON APRIL 8, 1982, A PETITION SIGNED BY LORIS LUGINSLAND AND OTHERS FOR THE VACATION OF A ROAD IN TOWNSHIP 17-11 WAS PRESENTED TO ROSEMARY SPALDING, COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS ON APRIL 29, 1982 AND THE FINAL ORDER DATED APRIL 29, 1982 ORDERED THE FOLLOWING ROAD VACATED:
- 1) BEGINNING AT THE SOUTHWEST CORNER OF SECTION 5-17-11 THENCE RUNNING NORTH ONE (1) MILE TO THE NORTHWEST CORNER OF SECTION 5-17-11, BEING ALONG THE EAST SIDE OF SECTION 6-17-11.
- 8) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 17, 1989, SAID THAT **HE FOUND A 6" X 6" LIMESTONE AT 8" DEEP** AT THE NORTHEAST CORNER OF SECTION 7-15-11. **HE SET 1/2" REBARS WITH HIS "LS 752" CAPS ON THE NORTH AND SOUTH SIDES OF THE STONE.**
- 1) 32.0' NW TO A SPIKE IN A POWER POLE
 - 2) 27.3' SE TO A SPIKE IN A TELEPHONE POLE
 - 3) 26.3' SW TO A PK NAIL & WASHER IN A CORNER POST
 - 4) 4.0' EAST TO THE CENTERLINE TRAVELED WAY OF THE ROAD TO THE SOUTH
- 9) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 10, 2001, FOR PROJECT NUMBER 99476-02, SURVEY F07004 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR THREE TRACTS OF LAND LYING IN THE NORTHEAST 1/4 OF SECTION 7-17-11, SAID THAT **SHE FOUND**

THE STONE WITH THE 1/2" REBARS WITH "LS 752" CAPS ON THE NORTH AND SOUTH SIDES OF THE STONE AT THE NORTHEAST CORNER OF SECTION 7-17-11 FROM EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE.

- 1) 33.0' NW TO A 40 D SPIKE IN A GUY POLE
- 2) 26.3' SW TO A PK NAIL & WASHER IN A CORNER FENCE POST
- 3) 31.5' NW TO A MASONRY NAIL & WASHER IN A CORNER FENCE POST
- 4) 45.4' SE TO THE BASE OF THE SIGN FOR RURAL WATER DISTRICT #1
- 5) 40.7' WSW TO THE TOP CENTER OF THE TELEPHONE PEDESTAL
- 6) 28.35' SE TO A MASONRY NAIL & WASHER IN A CORNER FENCE POST
- 7) 4.9' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 300 EAST-WEST
- 8) 4.0' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "H" TO THE SOUTH ONLY

HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,324.36' WEST TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE NORTH 1/16TH CORNER OF THE NE1/4 OF SECTION 7-17-11
- 2) 2,648.72' WEST TO THE 1/2" REBAR SHE FOUND AT THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 7-17-11
- 3) 1,315.86' SOUTH TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE FOUND AT THE EAST 1/16TH CORNER OF THE NE1/4 OF SECTION 7-17-11
- 4) 1,635.72' SOUTH TO THE 1/2" REBAR SHE SET FOR THE P.O.B. OF TRACT #2
- 5) 2,631.72' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 7-17-11
- 6) 5,281.09' SOUTH TO THE SQUARE 1/2" REBAR SHE FOUND AT THE SOUTHEAST CORNER OF SECTION 7-17-11

- 10) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 10, 2001, FOR PROJECT NUMBER 99476-02, SURVEY F08002 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR A SURVEY OF TWO TRACTS IN THE NORTHWEST 1/4 OF SECTION 8-17-11, SAID THAT **SHE FOUND THE STONE WITH THE 1/2" REBARS WITH "LS 752" CAPS ON THE NORTH AND SOUTH SIDES OF THE STONE AT THE NORTHWEST CORNER OF SECTION 8-17-11 FROM HER EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE.**

- 1) 33.0' NW TO A 40 D SPIKE IN A GUY POLE
- 2) 26.3' SW TO A PK NAIL & WASHER IN A CORNER FENCE POST
- 3) 31.5' NW TO A MASONRY NAIL & WASHER IN A CORNER FENCE POST
- 4) 45.4' SE TO THE BASE OF THE SIGN FOR RURAL WATER DISTRICT #1
- 5) 40.7' WSW TO THE TOP CENTER OF THE TELEPHONE PEDESTAL
- 6) 28.35' SE TO A MASONRY NAIL & WASHER IN A CORNER FENCE POST
- 7) 4.9' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 300 EAST-WEST
- 8) 4.0' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "H" TO THE SOUTH ONLY

HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,315.86' SOUTH TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE FOUND AT THE WEST 1/16TH CORNER OF THE NW1/4 OF SECTION 8-17-11 FROM A PREVIOUS SURVEY
- 2) 2,631.72' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE FOUND AT THE WEST 1/4 CORNER OF SECTION 8-17-11 FROM A PREVIOUS SURVEY
- 3) 5,281.08' SOUTH TO THE SQUARE 1/2" REBAR SHE FOUND AT THE SOUTHWEST CORNER OF SECTION 8-17-11
- 4) 2,632.84' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE NORTH 1/4 CORNER OF SECTION 8-17-11

HER INFORMATION IS CONTINUED ON PAGE 4

- 5) 3,845.01' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE NORTHEAST CORNER OF LOT 5, ON THE EAST BOUNDARY OF THE KANSAS INDIAN RESERVATION
 - 6) 5,267.13' EAST TO THE STONE SHE FOUND AT THE NORTHEAST CORNER OF SECTION 8-17-11, WITH THE 5/8" REBAR WITH A LYON COUNTY CAP SHE PLACED OVER THE CENTER OF THE STONE
- 11) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 12, 2009 FOR PROJECT NUMBER 09119-02 TO ESTABLISH THE NORTH LINE OF THE NORTHEAST 1/4 OF FRACTIONAL SECTION 6-17-11 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT FOR BRIDGE REPLACEMENT PROJECT NUMBER 04-EP, SURVEY F06003 IN THE SURVEY FILE FOR TOWNSHIP 17-11, SAID THAT **HE FOUND THE LIMESTONE WITH HIS "LS 752" CAPPED REBARS** AT THE SOUTHEAST CORNER OF SECTION 6-17-11 FROM EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE.
- 1) **1/2" REBARS WITH RED CAPS ON THE NORTH AND SOUTH SIDES OF STONE**
 - 2) 32.15' SE TO A CONCRETE NAIL & BOTTLE CAP IN A FENCE POST
 - 3) 26.2' SW TO A PK NAIL & WASHER IN THE BASE OF A CORNER POST
 - 4) 31.35' NW TO A PK NAIL & WASHER IN THE EAST SIDE OF A POWER POLE
 - 5) 4' EAST TO THE TRAVELED WAY OF COUNTY ROAD "H" TO THE SOUTH
 - 6) 4' NORTH TO THE TRAVELED WAY OF COUNTY ROAD 300 EAST-WEST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
- 1) 5,205.06' NORTH TO THE 5/8" CAPPED REBAR HE SET AT THE LOCATION OF THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SEC. 6-17-11
- 12) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 12, 2010 FOR PROJECT NUMBER 10112-02, SURVEY F05001 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR A SURVEY OF THE WEST HALF OF THE FRACTIONAL NORTHWEST 1/4 AND THE EAST HALF OF THE FRACTIONAL NORTHWEST 1/4; [AKA GOVERNMENT LOT 7 AND THE WEST HALF OF GOVERNMENT LOT 8 AND GOVERNMENT LOT 6 AND THE EAST HALF OF GOVERNMENT LOT 8] ALL IN SECTION 5-17-11 FOR EK REALTY, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 5-17-11 FROM EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE. [AKA SOUTHWEST CORNER OF GOVERNMENT LOT 12]
- 1) 28.0' ESE TO A CONCRETE NAIL & BOTTLECAP IN THE WEST FACE OF A NEW CORNER FENCE POST
 - 2) 31.9' SE TO A CONCRETE NAIL & BOTTLECAP IN THE WEST FACE OF A BRACE POST
 - 3) 26.0' SW TO A 40 D NAIL & WASHER IN THE NORTH FACE OF A CORNER FENCE POST
 - 4) 40.35' WSW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 5) 5.0' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 300 EAST-WEST
 - 6) 4.0' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "H" TO THE SOUTH
- NOTE:** 1/2" CAPPED REBARS ARE ON THE NORTH & SOUTH SIDES OF THE STONE
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,632.85' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP AT THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE FRACTIONAL SW1/4 OF SECTION 5-17-11 [AKA SOUTHEAST CORNER OF GOVERNMENT LOT 12]
 - 2) 2,650.56' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE FRACTIONAL NW1/4 OF SECTION 5-17-11
 - 3) 5,205.40' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP AT THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE FRACTIONAL NW1/4 OF SECTION 5-17-11 [AKA NORTHWEST CORNER OF GOVERNMENT LOT 7]

NORTHWEST CORNER 08-17-11