

WEST 1/4 CORNER SECTION 08, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) ON PAGE 326 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 7 & 8-17-11.

 - 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 130 RECORDED IN SURVEY BOOK "A" ON PAGES 214 & 215 DATED JULY 3, 1869 TO SURVEY THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 7-17-11, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 7-17-11 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 80 RODS, 3-3/4 LINKS SOUTH TO THE STONE HE SET FOR THE EAST 1/2/4 CORNER OF THE SE1/4 OF SECTION 7-17-11
 - 2) 160 RODS, 7-1/2 LINKS SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 7-17-11

 - 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 98 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 20 DATED APRIL 18, 1873 TO SUBDIVIDE THE NORTHEAST 1/4 OF SECTION 7-17-11 INTO EAST AND WEST HALVES, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 OF SECTION 7-17-11 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 1,324-1/2' WEST TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE NE1/4 OF SECTION 7-17-11
 - 2) 2,649' WEST TO THE STONE HE FOUND AT THE CENTER CORNER OF SEC. 7-17-11

 - 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 3 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 58 DATED FEBRUARY 12 & 13, 1874 TO ESTABLISH THE CENTER CORNER AND SUBDIVIDE THE SOUTHEAST 1/4 OF SECTION 7-17-11 EQUALLY BY A LINE EAST AND WEST, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 7-17-11 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION
 - 1) 1,324' SOUTH TO THE STONE HE FOUND LYING ON THE GROUND AND **HE RESET** FOR THE PERMANENT EAST 1/2/4 CORNER OF THE SE1/4 OF SEC. 7-17-11
 - 2) 2,648' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 7-17-11

 - 5) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 10, 2001, FOR PROJECT NUMBER 99476-02, SURVEY F07004 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR THREE TRACTS OF LAND LYING IN THE NORTHEAST 1/4 OF SECTION 7-17-11, SAID THAT SHE CONSIDERED THAT THE EAST 1/4 CORNER OF SECTION 7-17-11 WAS BOTH **LOST** AND **OBLITERATED**. SHE CONSIDERED THE NORTH-SOUTH POSITION **LOST**, AND SHE RESET IT AT ONE-HALF THE DISTANCE BETWEEN THE SOUTHEAST AND NORTHEAST CORNERS OF SECTION 7-17-11, WHICH WAS SUPPORTED BY THE PHYSICAL EVIDENCE OF A FENCE TO THE EAST. SHE SAID THAT IT WAS **OBLITERATED** IN EAST-WEST POSITION, AND SHE SET THIS POSITION BY THE PHYSICAL EVIDENCE THAT SHE FOUND AT THIS CORNER. **SHE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE EAST 1/4 CORNER OF SECTION 7-17-11.
 - 1) IN LINE WITH A FENCE TO THE EAST
 - 2) 23.35' EAST TO A MASONRY NAIL & BOTTLE CAP IN A CORNER FENCE POST
- HER TIES ARE CONTINUED ON PAGE 2

- 3) 62.25' SE TO A MASONRY NAIL & BOTTLE CAP IN A TWIN HEDGE TREE
- 4) 24.60' WEST TO THE BASE OF RURAL WATER DISTRICT #1 SIGN
- 5) 105.05' NNW TO A MASONRY NAIL & BOTTLE CAP IN A POWER POLE
- 6) 1.5' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "H" NORTH-SOUTH

HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,315.86' NORTH TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE WEST 1/16TH CORNER OF THE NW1/4 OF SECTION 8-17-11
- 2) 2,631.72' NORTH TO THE STONE SHE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 7-17-11, WITH 1/2" REBARS WITH "LS 752" CAPS ON THE NORTH & SOUTH SIDES OF THE STONE
- 3) 1,322.17' WEST TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE SOUTH 1/16TH CORNER OF THE NE1/4 OF SECTION 7-17-11
- 4) 2,644.34' WEST TO THE STONE SHE FOUND AT THE SOUTHWEST CORNER OF THE NE1/4 OF SECTION 7-17-11
- 5) 319.86' SOUTH TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE P.O.B. OF TRACT #2
- 6) 2,649.36' SOUTH TO THE SQUARE 1/2" REBAR SHE FOUND AT THE SOUTHEAST CORNER OF SECTION 7-17-11

- 8) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 10, 2001, FOR PROJECT NUMBER 99476-02, SURVEY F08002 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR A SURVEY OF TWO TRACTS IN THE NORTHWEST 1/4 OF SECTION 8-17-11, SAID THAT **SHE FOUND THE 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE WEST 1/4 CORNER OF SECTION 8-17-11 FROM HER PREVIOUS SURVEY.

- 1) 23.35' EAST TO A MASONRY NAIL & BOTTLECAP IN A CORNER FENCE POST
- 2) 62.25' SE TO A MASONRY NAIL & BOTTLECAP IN A TWIN HEDGE TREE
- 3) 24.60' WEST TO THE BASE OF THE RURAL WATER DISTRICT #1 SIGN
- 4) 105.05' NNW TO A MASONRY NAIL & BOTTLECAP IN A POWER POLE
- 5) IN LINE WITH A FENCE TO THE EAST
- 6) 1.5' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "H" NORTH-SOUTH

HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,315.86' NORTH TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE FOUND AT THE 1/16TH CORNER ON THE WEST SIDE OF THE NW1/4 OF SECTION 8-17-11, FROM HER PREVIOUS SURVEY
- 2) 2,631.72' NORTH TO THE STONE SHE FOUND AT THE NORTHWEST CORNER OF SECTION 8-17-11, WITH 1/2" REBARS WITH "LS 752" CAPS ON THE NORTH & SOUTH SIDES
- 3) 2,649.36' SOUTH TO THE SQUARE 1/2" REBAR SHE FOUND AT THE SOUTHWEST CORNER OF SECTION 8-17-11
- 4) 2,630.75' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE CENTER CORNER OF SECTION 8-17-11
- 5) 3,842.32' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE SOUTHEAST CORNER OF LOT 6 ON THE EAST BOUNDARY OF THE KANSAS INDIAN RESERVATION

WEST QUARTER CORNER 08-17-11