

WEST 1/16TH CORNER OF NORTHWEST 1/4 SECTION 08, TOWNSHIP 17 SOUTH, RANGE 11 EAST

1) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 10, 2001, FOR PROJECT NUMBER 99476-02, SURVEY F07004 IN THE SURVEY FILE FOR TOWNSHIP 17-11, SAID THAT **SHE SET A 1/2" X 24" REBAR WITH HER "LS 1130" CAP** FOR THE EAST 1/16TH CORNER OF THE NORTHEAST 1/4 OF SECTION 7-17-11 AT ONE-HALF THE DISTANCE BETWEEN THE EAST 1/4 CORNER OF SECTION 7-17-11 AND THE NORTHEAST CORNER OF SECTION 7-17-11, AND ON LINE BETWEEN SAID CORNERS.

- 1) 22.85' WNW TO A MASONRY NAIL & WASHER IN A CORNER FENCE POST
- 2) 32.35' NW TO THE BASE OF A BURIED CABLE SIGN
- 3) 41.30' SE TO A MASONRY NAIL & WASHER IN THE SOUTH GATE POST
- 4) 123.35' SSW TO A MASONRY NAIL & WASHER IN A POWER POLE
- 5) 2.5' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "H" [NORTH-SOUTH]
- 6) 17.5' SOUTH TO A LINE OF FENCE TO THE EAST

HER DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,315.86' NORTH TO THE STONE SHE FOUND WITH 1/2" REBARS WITH "LS 752" CAPS ON THE NORTH & SOUTH SIDES AT THE NORTHEAST CORNER OF SECTION 7-17-11
- 2) 1,315.86' SOUTH TO THE 5/8" CAPPED REBAR SHE SET FOR THE EAST 1/4 CORNER OF SECTION 7-17-11
- 3) 3,965.22' SOUTH TO THE SQUARE 1/2" REBAR SHE FOUND AT THE SOUTHEAST CORNER OF SECTION 7-17-11
- 4) 1,323.26' WEST TO THE 1/2" REBAR WITH HER "LS 1130 CAP" SHE SET FOR THE CENTER OF THE NORTHEAST 1/4 OF SECTION 7-17-11
- 5) 2,646.52' WEST TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE WEST 1/16TH CORNER OF THE NORTHEAST 1/4 OF SECTION 7-17-11

2) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE DATED APRIL 10, 2001, FOR PROJECT NUMBER 99476-02, SURVEY F08002 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR A SURVEY OF TWO TRACTS IN THE NORTHWEST 1/4 OF SECTION 8-17-11, SAID THAT **SHE FOUND THE 1/2" X 24" REBAR WITH HER "LS 1130" CAP** AT THE WEST 1/16TH CORNER OF THE NORTHWEST 1/4 OF SECTION 8-17-11 FROM HER PREVIOUS SURVEY.

- 1) 22.85' WNW TO A MASONRY NAIL & WASHER IN A CORNER FENCE POST
- 7) 32.35' NW TO THE BASE OF A BURIED CABLE SIGN
- 8) 41.30' SE TO A MASONRY NAIL & WASHER IN THE SOUTH GATE POST
- 9) 123.35' SSW TO A MASONRY NAIL & WASHER IN A POWER POLE
- 10) 2.5' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "H" [NORTH-SOUTH]
- 11) 17.5' SOUTH TO A LINE OF FENCE TO THE EAST

HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,315.86' NORTH TO THE STONE SHE FOUND WITH 1/2" REBARS WITH "LS 752" CAPS ON THE NORTH & SOUTH SIDES OF THE STONE AT THE NORTHWEST CORNER OF SECTION 8-17-11
- 2) 1,315.86' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE FOUND AT THE WEST 1/4 CORNER OF SECTION 8-17-11 FROM A PREVIOUS SURVEY
- 3) 3,965.22' SOUTH TO THE SQUARE 1/2" REBAR SHE FOUND AT THE SOUTHWEST CORNER OF SECTION 8-17-11

WEST SIXTEENTH CORNER NORTHWEST QUARTER 08-17-11