

NORTHWEST CORNER SECTION 09, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) ON PAGE 320 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 13" X 7"** FOR THE CORNER TO SECTIONS 4, 5, 8 & 9-17-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS NORTH TO THE 27" X 11" X 5" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 4 & 5-17-11
 - 2) 78.05 CHAINS NORTH TO THE 19" X 10" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4, 5, 32 & 33 ON THE TOWNSHIP LINE
 - 3) 39.91 CHAINS EAST TO THE 24" X 12" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 4 & 9-17-11
 - 4) 79.82 CHAINS EAST TO THE 22" X 18" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3, 4, 9 & 10-17-11
 - 5) 21.54 CHAINS WEST TO THE 20" X 14" X 3" LIMESTONE THEY SET ON THE EAST BOUNDARY OF THE KANSAS INDIAN RESERVATION

- 2) IN ROAD RECORD BOOK "A" ON PAGE 126 [PACKET 243 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE] ON A PETITION FOR SECTION LINE ROADS WITHOUT A SURVEY, THE BOARD OF COUNTY COMMISSIONERS ORDERED THE SECTION LINES DECLARED PUBLIC HIGHWAYS AT A SPECIAL MEETING ON MAY 12, 1869 TO WIT: COMMENCING AT THE NEW BRIDGE ON ALLEN CREEK AND RUNNING THENCE NORTH ON THE SECTION LINES TO THE NORTHEAST CORNER OF SECTION 4-18-11; THENCE WEST ONE MILE; THENCE NORTH TO THE NORTHEAST CORNER OF SECTION 5-17-11. A NOTE IN THE LEFT MARGIN STATES: THE LAW OF 1869 PROVIDES 40 FEET WIDTH ON SECTION LINE ROADS. SEE COMMISSION RECORD PAGE 263.
 - 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES TO THE NORTHEAST CORNER OF SECTION 5-17-11 ON THE TOWNSHIP LINE TO THE END OF THIS ROAD
 - 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES TO THE NORTHWEST CORNER OF SECTION 4-18-11 AT A TURN TO THE EAST FOR 1 MILE TO THE NORTHEAST CORNER OF SECTION 4-18-11; THEN CONTINUES SOUTH ON THE SECTION LINES TO THE NEW BRIDGE ON ALLEN CREEK TO COMMENCE THIS ROAD

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 100 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 402 TO 404 PETITIONED BY WILLIAM GRIMSLEY AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 17-11 [PACKET 393 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 18, 1880, WAS ESTABLISHED AS A 60 FOOT WIDE ROAD ON JANUARY 10, 1881 AS NOTED BY J. M. GRIFFITH, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 10, 1881 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST OF SECTION 8-17-11 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 1 MILE TO THE NORTHWEST CORNER OF SECTION 8-17-11 TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 1 MILE TO THE NORTHEAST CORNER OF SECTION 9-17-11 AT THE TERMINATION OF THIS ROAD SURVEY

- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT PAGE 194 DATED SEPTEMBER 18,

1880, FOR A ROAD SURVEY IN TOWNSHIP 17-11 APPARENTLY **FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 8-17-11 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINE FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 8-17-11 TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINE FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 9-17-11 AT THE TERMINUS OF THIS ROAD SURVEY
- 5) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 130 DATED MAY 2 & 3, 1882 AT THE REQUEST OF H. T. SWARNER TO SURVEY AND ESTABLISH IN TOWNSHIP 17, RANGE 11, THE CENTER OF SECTION 5, THE CORNER ON THE INDIAN RESERVE LINE, AND THE SOUTH LINE OF SECTION 5, AND THE 1/2 MILE CORNER ON THE INDIAN RESERVE LINE IN SECTION 5, AND SUCH OTHER LINES AND CORNERS AS MAY BE NECESSARY TO COMPLETE THE SURVEY, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 5-17-11 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
- 1) 39.90 CHAINS WEST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 5-17-11
- 6) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY, IN SURVEY NUMBER 69, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 69 DATED AUGUST 1 THROUGH NOVEMBER 15, 1884 AT THE ORDER OF A. S. STEADMAN, J. H. COURTNEY, AND M. WILLIAMSON TO ESTABLISH THE SOUTHEAST CORNER OF THE WEST 1/2 (FRACTIONAL) OF THE SOUTHEAST 1/4 OF SECTION 17-17-11 AND THE NORTHEAST CORNER OF THE SAME WEST 1/2 OF THE SOUTHWEST CORNER OF SAME SECTION, AND WILLIAM McNABNEY, W. L. DAVIES, H. L. ADAMS, WILLIAM H. ADAMS, JAMES WASHINGTON, J. W. REEDER, AND C. H. DABBS TO PERMANENTLY ESTABLISH ALL OF THE CORNERS NECESSARY TO MAKE ALL SUBDIVISIONS IN SECTION 16-17-11, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 9-17-11 ON THIS **PERMANENT SURVEY**. HE SAID THAT THIS SURVEY WAS SUBJECT TO A CORRECTED SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 79 DATED DECEMBER 20-25, 1884. THIS SURVEY IS RECORDED IN VOLUME 41 ON PAGE 27 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 27, 1887 AND SURVEY F17001 IN THE SURVEY FILE FOR TOWNSHIP 17-11.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 5,317' SOUTH TO THE STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 16-17-11
 - 2) 6,646' SOUTH TO THE STONE HE SET FOR THE PERMANENT WEST 1/4/4 CORNER OF THE NW1/4 OF SECTION 16-17-11
 - 3) 7,975.5' SOUTH TO THE STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 16-17-11
 - 4) 10,634' SOUTH TO THE STONE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 16-17-11
 - 5) 15,951' SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 21-17-11
- 7) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 37, A **ROAD/PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 218 DATED FEBRUARY 18, 1902 FOR A COUNTY ROAD IN TOWNSHIP 17-11 PETITIONED BY W. B. DeBAUN AND OTHERS TO ESTABLISH THE ROAD BETWEEN SECTIONS 5 & 6 IN 17-11, AND ORDERED BY THE BOARD OF COUNTY COMMISSIONERS TO LOCATE THE SECTION LINE BETWEEN SECTIONS 5 & 6 IN 17-

11 ON OCTOBER 2, 1902, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 5-17-11 ON THIS **ROAD/PERMANENT SURVEY**.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 15.78 CHAINS WEST TO THE STONE HE FOUND ON THE INDIAN RESERVE LINE ON THE SOUTH SIDE OF THE SE1/4 OF SECTION 5-17-11
- 2) 39.92 CHAINS WEST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 5-17-11
- 3) 79.82 CHAINS WEST TO THE 15" X 10" X 5" STONE MARKED "R" ON THE SOUTH FACE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 5-17-11 TO BEGIN THIS ROAD SURVEY FOR A 40 FOOT WIDE ROAD TO THE NORTH TO THE 18" X 10" X 5" STONE HE SET FOR THE NORTHWEST CORNER OF SECTION 5-17-11 TO END THIS ROAD SURVEY
- 4) 154.65' CHAINS WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 6-17-11

- 8) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE DATED APRIL 10, 2001, FOR PROJECT NUMBER 99476-02, SURVEY F08002 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR A SURVEY OF TWO TRACTS IN THE NORTHWEST 1/4 OF SECTION 8-17-11, SAID THAT **SHE FOUND THE GLO STONE** AT THE NORTHEAST CORNER OF SECTION 8-17-11 BY EXCAVATING WITH A COUNTY MOTOR GRADER AT THE POSITION INDICATED BY MEASUREMENTS RESULTING FROM HER TRAVERSE OF SECTIONS 7 & 8-17-11. **SHE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP OVER THE TOP CENTER OF THE GLO STONE.**

- 1) 34.90' NE TO A MASONRY NAIL & BOTTLECAP IN A POWER POLE
- 2) 42.60' NW TO A MASONRY NAIL & BOTTLECAP IN A GATE POST
- 3) 37.25' SW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
- 4) 26.50' WEST TO A LINE OF HEDGE TO THE NORTH - EXTENDED
- 5) IN THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 300 TO THE WEST
- 6) 1.5' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "J" NORTH-SOUTH

HER DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,422.12' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE NORTHEAST CORNER OF LOT 5 ON THE EAST BOUNDARY OF THE KANSAS INDIAN RESERVATION IN THE NE1/4 OF SECTION 8-17-11
- 2) 2,634.29' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE NORTH 1/4 CORNER OF SECTION 8-17-11
- 3) 5,267.13' WEST TO THE STONE SHE FOUND AT THE NORTHWEST CORNER OF SECTION 8-17-11, WITH 1/2" REBARS WITH "LS 752" CAPS ON THE NORTH & SOUTH SIDES OF THE STONE
- 4) 5,315.15' SOUTH TO THE 1/2" REBAR SHE FOUND AT THE SOUTHEAST CORNER OF SECTION 8-17-11

- 9) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 13, 2001, FOR PROJECT NUMBER 99480-02, SURVEY F03001 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR A SURVEY OF A 54.76 ACRE TRACT OF LAND IN THE SOUTHEAST 1/4 OF SECTION 3-17-11 FOR EK REALTY, SAID THAT **SHE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP OVER THE TOP CENTER OF THE GOVERNMENT STONE** AT THE NORTHEAST CORNER OF SECTION 8-17-11 FROM HER PREVIOUS TIES DATED APRIL 2001.

- 1) 34.90' NE TO A MASONRY NAIL & BOTTLECAP IN A POWER POLE
- 2) 42.60' NW TO A MASONRY NAIL & BOTTLECAP IN A GATE POST
- 3) 37.25' SW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
- 4) 26.50' WEST TO A LINE OF HEDGE TO THE NORTH-EXTENDED
- 5) IN THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 300 TO THE WEST
- 6) 1.5' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "J" NORTH-SOUTH

HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 5,269.74' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE SOUTHWEST CORNER OF SECTION 3-17-11
 - 2) 7,900.66' EAST TO THE CONCRETE NAIL SHE SET IN A DRILL HOLE WITH HER "LS 1130" CAP IN A CONCRETE LOW WATER CROSSING FOR THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 3-17-11
 - 3) 8,794.97' EAST TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE SOUTH-EAST CORNER OF THE 54.76 ACRE TRACT
 - 4) 10,531.58' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE SOUTHEAST CORNER OF SECTION 3-17-11
- 10) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 22, 2012 FOR PROJECT 12-B3, THE REPLACEMENT OF TIMBER CULVERT 939.8-494.0 WITH A 30 FOOT ALL STEEL BRIDGE, **FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP OVER THE TOP CENTER OF THE GOVERNMENT STONE AT 7" DEEP** AT THE NORTHWEST CORNER OF SECTION 9-19-11 FROM THE TIES OF POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, DATED APRIL 10, 2001 AND JULY 13, 2001 ON FILE IN THE COUNTY SURVEYOR'S OFFICE.
- 1) 34.80' NE TO A FOUND MASONRY NAIL & BOTTLE CAP IN A POWER POLE
 - 2) 37.50' SW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 3) 52.25' NW TO THE TOP CENTERLINE OF THE WESTERN 4" PIPE GATE POST
 - 4) 27.0' WEST TO A LINE OF HEDGE TO THE NORTH—EXTENDED
 - 5) IN THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD 300 TO THE WEST
 - 6) 1.5' EAST TO THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD "J" NORTH-SOUTH

NORTHWEST CORNER 09-17-11