

NORTHWEST CORNER SECTION 10, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) ON PAGE 316 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 18" X 3"** FOR THE CORNER TO SECTIONS 3, 4, 9 & 10-17-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS NORTH TO THE 18" X 18" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 3 & 4-17-11
 - 2) 78.25 CHAINS NORTH TO THE 16" X 11" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3, 4, 33 & 34 ON THE TOWNSHIP LINE
 - 3) 39.85 CHAINS EAST TO THE 15" X 13" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 3 & 10-17-11
 - 4) 79.70 CHAINS EAST TO THE 24" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 2, 3, 10 & 11-17-11

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT PAGE 155 DATED MAY 10, 1878, APPARENTLY **FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 4-17-11 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS 5 MILES SOUTH ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 33-17-11 ON THE TOWNSHIP LINE
 - 2) THIS ROAD EXTENDS 1 MILE NORTH ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 4-17-11 ON THE TOWNSHIP LINE

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 100 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 402 TO 404 PETITIONED BY WILLIAM GRIMSLEY AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 17-11 [PACKET 393 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 18, 1880, WAS ESTABLISHED AS A 60 FOOT WIDE ROAD ON JANUARY 10, 1881 AS NOTED BY J. M. GRIFFITH, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 10, 1881 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST OF SECTION 9-17-11 AT THE TERMINUS OF THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 2 MILES TO THE NORTHWEST CORNER OF SECTION 8-17-11 TO COMMENCE THIS ROAD SURVEY

- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT PAGE 194 DATED SEPTEMBER 18, 1880, FOR A ROAD SURVEY IN TOWNSHIP 17-11 APPARENTLY **FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 9-17-11 AT THE TERMINUS OF THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 8-17-11 TO COMMENCE THIS ROAD SURVEY

- 5) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 266 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 14 TO 17 PETITIONED BY JOHN BRAMHILL AND OTHERS FOR THREE ROADS IN TOWNSHIPS 17-11 AND 17-12 [PACKET 516 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 5, 1884, WERE ESTABLISHED AS 50 FOOT WIDE ROADS ON JULY 10, 1884 AS NOTED BY P. Y. HALLBERG, CHAIRMAN OF THE

BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON NOVEMBER 19, 1884 BY ROLAND LAKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 3-17-11 AT THE TERMINUS OF THE SECOND ROAD ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS SECOND ROAD EXTENDS EAST ON THE SECTION LINES FOR 3 MILES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 1-17-11 ON THE RANGE LINE TO COMMENCE THE SECOND ROAD ON THIS ROAD SURVEY
- 6) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY, IN SURVEY NUMBER 69, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 69 DATED AUGUST 1 THROUGH NOVEMBER 15, 1884 AT THE ORDER OF A. S. STEADMAN, J. H. COURTNEY, AND M. WILLIAMSON TO ESTABLISH THE SOUTHWEST CORNER OF THE WEST 1/2 (FRACTIONAL) OF THE SOUTHWEST 1/4 OF SECTION 17-17-11 AND THE NORTHEAST CORNER OF THE SAME WEST 1/2 OF THE SOUTHWEST CORNER OF SAME SECTION, AND WILLIAM McNABNEY, W. L. DAVIES, H. L. ADAMS, WILLIAM H. ADAMS, JAMES WASHINGTON, J. W. REEDER, AND C. H. DABBS TO PERMANENTLY ESTABLISH ALL OF THE CORNERS NECESSARY TO MAKE ALL SUBDIVISIONS IN SECTION 16-17-11, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 9-18-11 ON THIS **PERMANENT SURVEY**. HE SAID THAT THIS SURVEY WAS SUBJECT TO A CORRECTED SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 79 DATED DECEMBER 20-25, 1884. THIS SURVEY IS RECORDED IN VOLUME 41 ON PAGE 27 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 27, 1887 AND SURVEY F17001 IN THE SURVEY FILE FOR TOWNSHIP 17-11.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 5,287' SOUTH TO THE STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 16-17-11
 - 2) 6,609' SOUTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/4/4 CORNER OF THE NE1/4 OF SECTION 16-17-11
 - 3) 7,930.5' SOUTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 16-17-11
 - 4) 10,574' SOUTH TO THE STONE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 16-17-11
 - 5) 15,861' SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 21-17-11
- 7) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 44, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 225 DATED APRIL 23, 1902 ORDERED BY LOUIS NELSON TO ESTABLISH THE NORTHEAST CORNER OF SECTION 10-17-11, SAID THAT **HE SET A STAKE** FOR THE PERMANENT NORTHWEST CORNER OF SECTION 10-17-11 ON THIS **PERMANENT SURVEY**. HE SET THIS STAKE ON LINE WITH THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 10-17-11 AND THE STONE THAT HE FOUND AT THE WEST 1/4 CORNER OF SECTION 10-17-11, AND AT THE SAME DISTANCE THAT HE FOUND BETWEEN THESE TWO STONES. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGES 24 AND 47, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 46" IN MISCELLANEOUS DRAWER 2 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 40.18 CHAINS SOUTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 10-17-11
- 2) 80.36 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 10-17-11

CONTINUED ON PAGE 3

- 8) COMMISSIONER'S ROAD JOURNAL BOOK "B", PAGE 84
 ON DECEMBER 12, 1951 A PETITION SIGNED BY NELS MUNSON FOR THE VACATION OF A ROAD IN TOWNSHIP 17-11 WAS PRESENTED TO GEORGE K. JACKSON, COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS ON JANUARY 22, 1952 AND THE FINAL ORDER OF THE BOARD OF COUNTY COMMISSIONERS ON JANUARY 22, 1952 VACATED THE FOLLOWING ROAD:
 1) BEGINNING AT A POINT ON THE SECTION LINE AT THE NW1/4 (NORTHWEST CORNER?) OF SECTION 10-17-11, THENCE SOUTH 1 MILE AND THERE ENDING
- 9) COMMISSIONER'S ROAD JOURNAL BOOK "B", PAGE 88
 ON MAY 2, 1952 A PETITION SIGNED BY JOHN H. REIDEL AND OTHERS FOR THE VACATION OF A ROAD IN TOWNSHIP 17-11 WAS PRESENTED TO GEORGE K. JACKSON, COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS ON MAY 27, 1952 AND THE FINAL ORDER OF THE BOARD OF COUNTY COMMISSIONERS ON MAY 27, 1952 VACATED THE FOLLOWING ROAD:
 2) BEGINNING AT THE SOUTHWEST CORNER OF SECTION 3-17-11 AND NORTH ONE MILE BETWEEN SECTION 3 AND 4-17-11 AND ENDING THERE.
- 10) COMMISSIONER'S ROAD JOURNAL BOOK "B", PAGE 145
 ON MARCH 29, 1964 A PETITION SIGNED BY VIRGIL MARCOTT AND OTHERS FOR THE VACATION OF A ROAD IN TOWNSHIP 17-11 WAS PRESENTED TO W. A. STOLFUS, COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS AND W. D. KRETSINGER, COUNTY ENGINEER, ON APRIL 15, 1964 RECOMMENDING THAT THE FOLLOWING ROAD BE VACATED:
 1) BEGINNING AT 1,980 FEET MORE OR LESS EAST OF THE SOUTHWEST CORNER OF SECTION 4-17-11, THENCE EAST TO THE SOUTHEAST CORNER OF SAID SECTION 4-17-11 AND THERE ENDING.
- 11) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 13, 2001, FOR PROJECT NUMBER 99480-02, SURVEY F03001 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR A SURVEY OF A 54.76 ACRE TRACT OF LAND IN THE SOUTHEAST 1/4 OF SECTION 3-17-11 FOR EK REALTY, SAID THAT SHE DEEMED THAT THE SOUTHWEST CORNER OF SECTION 3-17-11 WAS LOST IN EAST-WEST POSITION, AND SHE SET IT AT THE PRORATION OF THE GLO DISTANCE. SHE DEEMED THAT THE CORNER WAS OBLITERATED IN NORTH-SOUTH POSITION, AND SHE SET IT BASED UPON THE PHYSICAL EVIDENCE THAT SHE FOUND AT THIS CORNER, WHICH IS SUPPORTED BY MEASUREMENT. **SHE SET A 5/8" REBAR WITH A LYON COUNTY CAP FOR THE SOUTHEAST CORNER OF SECTION 3-17-11.**
 1) 4.65' WNW TO A MASONRY NAIL & BOTTLE CAP IN A BRACE POST
 2) 3.90' ENE TO A MASONRY NAIL & BOTTLE CAP IN THE WEST GATE POST
 3) 20.20' SE TO A MASONRY NAIL & BOTTLE CAP IN A BRACE POST
 4) 1.70' NORTH TO A FENCE RUNNING EAST & WEST
 5) 21.30' EAST TO A FENCE RUNNING NORTH & SOUTH
 6) 2.5' SOUTH TO THE NORTH BANK OF A RAVINE
HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 1) 5,269.74' WEST TO THE GLO STONE SHE FOUND, WITH THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET OVER THE CENTER OF THE STONE AT THE SOUTHWEST CORNER OF SECTION 4-17-11
 2) 2,639.38' SOUTH TO THE CORNER POST SHE FOUND AT THE WEST 1/4 CORNER OF SECTION 10-17-11
 3) 2,639.14' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP DRIVEN THROUGH THE CENTER OF TWO HALVES OF THE STONE SHE FOUND AT THE WEST 1/4 CORNER OF SECTION 3-17-11

HER INFORMATION IS CONTINUED ON PAGE 4

- 4) 5,164.74' NORTH TO THE SQUARE #4 REBAR SHE FOUND AT THE NORTHWEST CORNER OF SECTION 3-17-11 ON THE TOWNSHIP LINE
- 5) 2,630.92' EAST TO THE CONCRETE NAIL SHE SET IN A DRILL HOLE WITH HER "LS 1130" CAP IN A CONCRETE LOW WATER CROSSING FOR THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 10-17-11
- 6) 3,525.23' EAST TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE SOUTHEAST CORNER OF THE 54.76 ACRE TRACT
- 7) 5,261.84' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 3-17-11

NORTHWEST CORNER 10-17-11