

NORTHWEST CORNER SECTION 11, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) ON PAGE 313 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 12" X 3"** FOR THE CORNER TO SECTIONS 2, 3, 10 & 11-17-11.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH TO THE 23" X 9" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 2 & 3-17-11
 - 2) 78.35 CHAINS NORTH TO THE 15" X 10" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 2, 3, 34 & 35 ON THE TOWNSHIP LINE
 - 3) 40.05 CHAINS EAST TO THE 16" X 13" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 2 & 11-17-11
 - 4) 80.10 CHAINS EAST TO THE 21" X 11" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 1, 2, 11 & 12-17-11
- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 230 & 231 FOR A PETITION BY D. S. AVERY AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 15-11, 16-11 AND 17-11 [PACKET 190 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON NOVEMBER 21 THROUGH 24, 1875, AND WAS ESTABLISHED ON JANUARY 3, 1876 AS A 50 FOOT WIDE ROAD, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 11-17-11 ON THIS ROAD SURVEY. HE NOTED THAT THE TOTAL LENGTH OF THIS ROAD IS "11 MILES, 41 CHAINS, 5 RODS AND 7-1/2 FEET".

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINE TO THE SOUTHWEST CORNER OF SECTION 2-16-11, AND THEN TURNS NORTHEASTERLY TO THE SOUTHWEST CORNER OF SECTION 36-15-11 ON THE 3RD STANDARD PARALLEL, AND THEN CONTINUES NORTH ON THE SECTION LINES TO THE NORTHEAST CORNER OF SECTION 23-15-11 ON THE LYON AND WABAUNSEE COUNTY LINE AT THE TERMINUS OF THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 15-17-11 TO BEGIN THIS ROAD SURVEY

- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 266 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 14 TO 17 PETITIONED BY JOHN BRAMHILL AND OTHERS FOR THREE ROADS IN TOWNSHIPS 17-11 AND 17-12 [PACKET 516 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 5, 1884, WERE ESTABLISHED AS 50 FOOT WIDE ROADS ON JULY 10, 1884 AS NOTED BY P. Y. HALLBERG, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON NOVEMBER 19, 1884 BY ROLAND LAKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 2-17-11 ON THE SECOND ROAD ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS SECOND ROAD EXTENDS WEST ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 3-17-11 AT THE TERMINUS OF THE SECOND ROAD ON THIS ROAD SURVEY
 - 2) THIS SECOND ROAD EXTENDS EAST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 1-17-11 ON THE RANGE LINE TO COMMENCE THE SECOND ROAD ON THIS ROAD SURVEY
- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A **PERMANENT SURVEY** COMPLETED ON APRIL 8, 1886 TO LOCATE THE SOUTHEAST CORNER AND SOUTH 1/4 CORNER OF SECTION 2-17-11, SURVEY F20001 IN THE SURVEY FILE FOR TOWNSHIP 17-11 AND RECORDED IN VOLUME 36 ON PAGE 356 AT THE REGISTER OF

DEEDS OFFICE ON APRIL 16, 1886, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 2-17-11 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,640-1/2' EAST TO THE ORIGINAL STONE HE FOUND AND **HE RESET** FOR THE SOUTH 1/4 CORNER OF SECTION 2-17-11 [DRAWING SHOWS 2,641' BUT 1/2 THE DISTANCE OF 5,281' IS 2,640-1/2']
- 2) 5,281' EAST TO THE STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 2-17-11
- 3) 10,562' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 1-17-11

- 5) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN **PERMANENT SURVEYS** NUMBER 38 AND 105 RECORDED IN SURVEY BOOK "F" ON PAGE 96 DATED MAY 3, 4, 5 & 12, 1886, FOR A SURVEY TO ESTABLISH THE CENTER CORNER OF SECTION 6-17-12 AND THE CORNERS TO THE NORTHEAST 1/4 AND THE SOUTHWEST 1/4 OF SECTION 1-17-11, SAID THAT **HE FOUND THE STONE LAYING DOWN** AT THE SOUTHWEST CORNER OF SECTION 2-17-11 ON THESE **PERMANENT SURVEYS**. HE SAID THAT PIECES OF THE STONE WERE FOUND IN THE GROUND SO THAT THE PLACE COULD BE EASILY IDENTIFIED AS BEING IN ITS ORIGINAL PLACE. THIS SURVEY WAS RECORDED IN VOLUME 36 ON PAGE 497 IN THE REGISTER OF DEEDS OFFICE ON SEPTEMBER 2, 1886 AND SURVEY F01001 IN THE SURVEY FILE FOR TOWNSHIP 17-11.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 80.0-9/10 CHAINS EAST TO THE 18" X 9" X 2" STONE WITH 1 NOTCH ON THE EAST SIDE, 5 NOTCHES ON THE WEST SIDE, 1 NOTCH ON THE NORTH SIDE, AND 5 NOTCHES ON THE SOUTH SIDE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 1-17-11

- 6) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 44, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 225 DATED APRIL 23, 1902 ORDERED BY LOUIS NELSON FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE NORTHEAST CORNER OF SECTION 10-17-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE SET A 15" X 8" X 3" STONE MARKED WITH A PLUS ("+") ON THE SIDE AT 20 FEET SOUTH AND 25 FEET WEST OF A CORNER POST AT THE NORTHEAST CORNER OF THE CROSS ROADS, AND ABOUT 20 FEET NORTH OF A HEDGE RUNNING WEST** FOR THE PERMANENT NORTHEAST CORNER OF SECTION 10-17-11 ON THIS **PERMANENT SURVEY**. HE TOOK THE AFFIDAVITS OF D. G. SMITH, W. R. SUDDOCK, LOUIS NELSON AND J. H. OGLESBY THAT THIS LOCATION WAS WITHIN 3 FEET OF WHERE THE STONE ORIGINALLY STOOD AT THE SOUTHEAST CORNER OF SECTION 3-17-11. HE SAID THAT HE ALSO HAD THE WRITTEN STATEMENT OF LEVI EARHART ON THE LOCATION FOR THIS STONE. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGES 24 AND 47, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 46" IN MISCELLANEOUS DRAWER 2 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 77.73 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 2-17-11 ON THE TOWNSHIP LINE
- 2) 40.41 CHAINS EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 11-17-11
- 3) 80.67 CHAINS EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 11-17-11, AT 4 FEET SOUTH AND 8 FEET EAST OF THE CORNER POST AT THE NORTHWEST CORNER OF THE CROSS ROADS
- 4) 19.91 CHAINS SOUTH TO THE STONE HE FOUND IN THE ROAD THAT WAS SET BY "UNKNOWN PARTIES" AT 20 FEET EAST OF A STONE POST

HIS INFORMATION IS CONTINUED ON PAGE 3

- 5) 80.46 CHAINS SOUTH TO THE STONE HE FOUND AND **HE RESET** FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 10-17-11
- 6) 160.92 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 15-16-11

- 7) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 46, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 227 DATED MARCH 18 & 21 AND CLOSED MAY 8, 1902 ORDERED BY ROBERT MOUNKES FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE NORTHEAST CORNER, THE 1/4 CORNER ON THE EAST LINE, AND THE CENTER CORNER OF SECTION 15-17-11 AND RUN SUCH LINES AS ARE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE AT 30 LINKS WEST OF A STONE POST AT THE SOUTHEAST CORNER OF THE CROSSROADS** AT THE NORTHEAST CORNER OF SECTION 10-17-11 AS ESTABLISHED BY THE NELSON SURVEY NUMBER 44 IN SURVEY BOOK "E" ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 26, AND ADDITIONAL INFORMATION IS IN PACKET "M 66" IN MISCELLANEOUS DRAWER NUMBER 4 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 80.46 CHAINS SOUTH TO THE 24" X 12" X 4" STONE WITH A DRILL HOLE ON THE BOTTOM HE SET FOR THE PERMANENT NORTHEAST CORNER OF SEC. 15-17-11
 - 2) 120.69 CHAINS SOUTH TO THE 18" X 6" X 6" LIMESTONE MARKED "X" ON THE NORTH FACE HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SEC. 15-17-11
 - 3) 160.92 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 15-17-11

- 8) COMMISSIONER'S ROAD JOURNAL BOOK "B", PAGE 119
ON JULY 9, 1959, A PETITION SIGNED BY C. G. KARR AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 16-11 WAS PRESENTED TO W. A. STOLFUS, COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS AND W. D. KRETSINGER, COUNTY ENGINEER, ON SEPTEMBER 4, 1959 AND THE FINAL ORDER WAS NOT DATED BUT SIGNED BY ALL THREE MEMBERS OF THE BOARD OF COUNTY COMMISSIONERS **VACATED** THE FOLLOWING ROAD BY SECTION 68-102 OF THE GENERAL STATUTES OF KANSAS AND 68-102 OF THE 1957 SUPPLEMENT TO THE GENERAL STATUTES OF KANSAS 1949:
 - 1) NOW THEREFORE BE IT RESOLVED, THAT IN THE JUDGMENT OF SAID BOARD OF COUNTY COMMISSIONERS THE ROAD HEREINAFTER DESCRIBED IS NOT A PUBLIC UTILITY BY REASON OF NEGLECT, NONUSE AND INCONVENIENCE
 - 2) BE IT FURTHER RESOLVED, IT IS HEREBY ORDERED THAT THE FOLLOWING DESCRIBED ROAD IS HEREBY **VACATED**:
 - 3) COMMENCING AT THE NORTHWEST CORNER OF SECTION 11-17-11, THENCE ONE (1) MILE EAST TO THE SOUTHEAST CORNER OF SECTION 2-17-11; THENCE ONE-HALF (1/2) MILE NORTH AND TERMINATING AT THE ONE-HALF (1/2) MILE POINT OF SECTION 2-17-11.

- 9) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 13, 2001, FOR PROJECT NUMBER 99480-02, SURVEY F03001 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR A SURVEY OF A 54.76 ACRE TRACT OF LAND IN THE SOUTHEAST 1/4 OF SECTION 3-17-11 FOR EK REALTY, SAID THAT SHE CONSIDERED THAT THE SOUTHEAST CORNER OF SECTION 3-17-11 WAS **LOST**. **SHE SET A 5/8" REBAR WITH A LYON COUNTY CAP** FOR THE SOUTHEAST CORNER OF SECTION 3-17-11 BASED ON A PRORATED DISTANCE FROM A RETRACEMENT OF A SURVEY BY ALVA J. SMITH ON FILE IN THE COUNTY ENGINEER'S OFFICE.

HER TIES ARE ON PAGE 4

- 1) 33.15' EAST TO A CONCRETE NAIL & BOTTLECAP IN A CORNER POST
- 2) 32.55' SW TO A CONCRETE NAIL & BOTTLECAP IN A POWER POLE [DEADMAN]
- 3) 39.85' NW TO A CONCRETE NAIL & BOTTLECAP IN A POWER POLE
- 4) IN THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 300 TO THE WEST
- 5) 2.3' WEST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "L"
- 6) 2.8' NORTH TO A FENCE LINE TO THE EAST EXTENDED

HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,736.61' WEST TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE SOUTHEAST CORNER OF THE 54.76 ACRE TRACT
 - 2) 2,630.92' WEST TO THE CONCRETE NAIL WITH HER "LS 1130" CAP SHE SET IN A DRILL HOLE IN A CONCRETE LOW WATER CROSSING FOR THE SOUTH 1/4 CORNER OF SECTION 3-17-11
 - 3) 5,261.84' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE SOUTHWEST CORNER OF SECTION 3-17-11
 - 4) 10,531.58' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET OVER THE CENTER OF THE GLO STONE THAT SHE FOUND AT THE SOUTHWEST CORNER OF SECTION 4-17-11
 - 5) 2,642.80' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 3-17-11
 - 6) 5,126.65' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE NORTHEAST CORNER OF SECTION 3-17-11 ON THE TOWNSHIP LINE
 - 7) 5,311.00' SOUTH TO THE 1/2" REBAR WITH A LYON COUNTY CAP SHE FOUND AT THE SOUTHEAST CORNER OF SECTION 10-17-11
- 10) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 1, 2001, FOR JOB NUMBER 01-59, SETTING COUNTY MONUMENT BOXES OVER SECTION CORNERS ON COUNTY ASPHALT ROADS, **FOUND THE 5/8" X 12" REBAR AT 2" BELOW THE ROAD SURFACE** AT THE NORTHWEST CORNER OF SECTION 11-17-11 FROM EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE BY POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, DATED JULY 13, 2001. **I REPLACED THIS FOUND REBAR WITH A 5/8" X 24" REBAR WITH A LYON COUNTY CAP AND I SET A COUNTY MONUMENT BOX FLUSH WITH THE SURFACE OF COUNTY ASPHALT ROAD "L" [THE ALLEN ROAD]** FOR THE NORTHWEST CORNER OF SECTION 11-17-11.
- 1) 33.2' EAST TO A FOUND CONCRETE NAIL & BOTTLE CAP IN A CORNER POST
 - 2) 32.6' SW TO A FOUND CONCRETE NAIL & BOTTLE CAP IN A DEADMAN
 - 3) 39.9' NW TO A FOUND NAIL & BOTTLE CAP IN A POWER POLE
 - 4) 49.0' SE TO A SET MAG NAIL & WASHER IN THE WEST FACE OF A POWER POLE
 - 5) 2' WEST TO THE CENTERLINE TRAVELED WAY OF ASPHALT COUNTY ROAD "L" [THE ALLEN ROAD] NORTH-SOUTH
- 11) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 1, 2009 FOR PROJECT NUMBER 09301-02, A SURVEY OF THE SOUTH HALF AND THREE TRACTS IN THE SOUTH HALF OF SECTION 2-17-11 FOR CHARLES & JANET LAIRD AND JAMES & SANDRA LAIRD, SURVEY F02002 IN THE SURVEY FILE FOR TOWNSHIP 17-11, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL** AT THE SOUTHWEST CORNER OF SECTION 2-17-11 FROM EXISTING REFERENCE TIES ON FILE AT THE COUNTY SURVEYOR'S OFFICE FROM POLLY JONES, L.S. 1130, SET IN 1999.
- 1) 33.2' EAST TO A CONCRETE NAIL & BOTTLECAP IN A CORNER FENCE POST
 - 2) 32.6' WEST TO A CONCRETE NAIL & BOTTLECAP IN A POWER POLE [DEADMAN]
 - 3) 39.9' NW TO A CONCRETE NAIL & BOTTLECAP IN A POWER POLE
 - 4) IN THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 300 TO THE WEST

HIS TIES ARE CONTINUED ON PAGE 5

- 5) 2' WEST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "L" NORTH-SOUTH
- 6) 2.8' NORTH TO A FENCE TO THE EAST – EXTENDED

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,642.80' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE NORTHWEST CORNER OF THE SOUTH 1/2 OF SECTION 2-17-11
- 2) 2,661.37' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 2-17-11
- 3) 5,318.53' EAST TO TUE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE SOUTH 1/2 OF SECTION 2-17-11

- 12) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 1, 2012, SURVEY F02003 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR TWO TRACTS IN THE SOUTH HALF OF SECTION 2-17-11 FOR TERESA SIMMONS FOR PROJECT NUMBER 12031-02, SAID THAT **HE FOUND THE 5/8" IRON PIN WITH A LYON COUNTY CAP IN A MONUMENT BOX** AT THE SOUTHWEST CORNER OF SECTION 2-17-11 FROM EXISTING REFERENCE REPORTS ON FILE AT THE COUNTY SURVEYOR'S OFFICE. HE NOTED THAT POLLY A. JONES, LS. 1130 HAD SET THIS CAPPED REBAR IN 1999.

- 1) 33.2' EAST TO A CONCRETE NAIL & BOTTLECAP IN A CORNER POST
- 2) 32.6' SW TO A CONCRETE NAIL & BOTTLECAP IN A POWER POLE [DEADMAN]
- 3) 39.9' NW TO A CONCRETE NAIL & BOTTLECAP IN A POWER POLE
- 4) 2.8' NORTH TO A FENCE TO THE EAST [EXTENDED]
- 5) IN THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 300 TO THE WEST
- 6) 2' WEST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "L" NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,321.30' NORTH TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE N1/2 OF THE SOUTH 1/2 OF SECTION 2-17-11
- 2) 2,642.61' NORTH TO THE 5/8" IRON PIN WITH A LYON COUNTY CAP HE FOUND IN A MONUMENT BOX AT THE NORTHWEST CORNER OF THE SOUTH 1/2 OF SECTION 2-17-11
- 3) 5,318.48' EAST TO THE 1/2" IRON PIN WITH HIS "LS 752" CAP HE FOUND AT THE SOUTHEAST CORNER OF THE SOUTH 1/2 OF SECTION 2-17-11

NORTHWEST CORNER 11-17-11