

NORTH 1/4 CORNER SECTION 12, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) ON PAGE 309 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 15" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 1 & 12-17-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.08 CHAINS WEST TO THE 21" X 11" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 1, 2, 11 & 12
 - 2) 40.07 CHAINS EAST TO THE 14" X 11" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 1, 6, 7 & 12 ON THE RANGE LINE

- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN **PERMANENT SURVEYS** NUMBER 38 AND 105 RECORDED IN SURVEY BOOK "F" ON PAGE 96 DATED MAY 3, 4, 5 & 12, 1886, FOR A SURVEY TO ESTABLISH THE CENTER CORNER OF SECTION 6-17-12 AND THE CORNERS TO THE NORTHEAST 1/4 AND THE SOUTHWEST 1/4 OF SECTION 1-17-11, SAID THAT **HE SET A 28" X 12" X 2" STONE MARKED "1/4" ON THE SOUTH SIDE** FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 1-17-11 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 1-17-11 AND THE STAKE THE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 1-17-11 ON THE RANGE ON THESE **PERMANENT SURVEYS**. THIS SURVEY WAS RECORDED IN VOLUME 36 ON PAGE 497 IN THE REGISTER OF DEEDS OFFICE ON SEPTEMBER 2, 1886 AND SURVEY F01001 IN THE SURVEY FILE FOR TOWNSHIP 17-11.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00-11/20 CHAINS WEST TO THE 18" X 9" X 2" STONE MARKED WITH 1 NOTCH ON THE EAST SIDE, 5 NOTCHES ON THE WEST SIDE, 1 NOTCH ON THE NORTH SIDE AND 5 NOTCHES ON THE SOUTH SIDE, HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 1-17-11
 - 2) 40.00-11/20 CHAINS EAST TO THE STAKE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 1-18-11 ON THE RANGE LINE

NORTH QUARTER CORNER 12-17-11