

NORTH 1/4 CORNER SECTION 13, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) ON PAGE 309 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 10" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 12 & 13-17-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS WEST TO THE 24" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 11, 12, 13 & 14
 - 2) 40.00 CHAINS EAST TO THE 17" X 11" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7, 12, 13 & 18 ON THE RANGE LINE

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 46, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 227 DATED MARCH 18 & 21 AND CLOSED MAY 8, 1902 ORDERED BY ROBERT MOUNKES FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE NORTHEAST CORNER, THE 1/4 CORNER ON THE EAST LINE, AND THE CENTER 1/4 CORNER OF SECTION 15-17-11, AND RUN SUCH LINES AS ARE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 13-17-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 26, AND ADDITIONAL INFORMATION IS IN PACKET "M 66" IN MISCELLANEOUS DRAWER NUMBER 4 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 120.73 CHAINS WEST TO THE 24" X 12" X 4" STONE WITH A DRILL HOLE ON THE BOTTOM HE SET FOR THE PERMANENT NORTHEAST CORNER OF SEC. 15-17-11
 - 2) 160.66 CHAINS WEST TO THE LOCATION FOR THE NORTH 1/4 CORNER OF SECTION 15-17-11
 - 3) 200.59 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 15-17-11

- 3) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 17-11 SHOWS A **REA PIN** AT THE "SW CORNER SE1/4 SECTION 12-17-11".
 - 1) 23' NORTH TO A WITNESS [REA]

- 4) LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN A SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 121 DATED APRIL 15, 1955 TO SET AN IRON PIN IN THE SOUTHEAST 1/4 OF THE NORTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 13-17-11, SHOWS ON HIS SURVEY DRAWING THAT **HE SET A TEMPORARY POINT** FOR THE NORTH 1/4 CORNER OF SECTION 13-17-11 ON LINE AND HALFWAY BETWEEN THE NORTHWEST CORNER AND THE NORTHEAST CORNER OF SECTION 13-17-11 ON THIS SURVEY. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,324' EAST TO THE TEMPORARY POINT HE SET FOR THE NORTH 1/16TH CORNER OF THE NE1/4 OF SECTION 13-17-11
 - 2) 2,648' EAST TO THE TEMPORARY POINT HE SET FOR THE NORTHEAST CORNER OF SECTION 13-17-11 ON THE RANGE LINE
 - 3) 2,648' WEST TO THE NORTHWEST CORNER OF SECTION 13-17-11 – NOT IDENTIFIED
 - 4) 1,324.3' SOUTH TO THE TEMPORARY POINT HE SET FOR THE WEST 1/16TH CORNER OF THE NE1/4 OF SECTION 13-17-11
 - 5) 2,648.6' SOUTH TO THE IRON PIN HE SET FOR THE CENTER CORNER OF SECTION 13-17-11

CONTINUED ON PAGE 2

- 5) STEVEN S. BROSEMER, L.S. 752, IN A SURVEY F14002 IN THE SURVEY FILE FOR TOWNSHIP 17-11, DATED AUGUST 4, 1987, FOR PROJECT NUMBER 87169 FOR A SURVEY TO LOCATE THE NORTHWEST CORNER OF SECTION 14-17-11, SAID THAT HE DUG FOR THE STONE AT THE NORTHEAST CORNER OF SECTION 14-17-11 WITH A COUNTY MAINTAINER, BUT HE DID **NOT** FIND THE STONE. **HE SET A 1/2" X 24" REBAR WITH A CAP** FOR THE NORTH 1/4 CORNER OF SECTION 13-17-11. HIS *REPORT OF SURVEY* SAID THAT HE REESTABLISHED THIS CORNER BASED ON THE PHYSICAL EVIDENCE THAT HE FOUND AT THIS CORNER, I.E., IN LINE WITH A HEDGE TO THE SOUTH AND A FENCE TO THE NORTH AND IN THE CENTER OF THE SECTION LINE ROAD.
- 1) 32.5' NORTH TO A CORNER POST & FENCES TO THE NORTH & WEST
 - 2) 32.5' SSE TO A CORNER POST & FENCES TO THE SOUTH & WEST
 - 3) 32.5' SSE TO A SPIKE & WASHER IN A POWER POLE
 - 4) IN LINE WITH A FENCE TO THE NORTH AND A HEDGE TO THE SOUTH
 - 5) IN THE CENTERLINE TRAVELED WAY OF THE ROAD EAST-WEST
 - 6) 5.0' WEST TO A LINE OF FENCE TO THE SOUTH
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,649.34' WEST TO THE 60 D SPIKE HE FOUND AT THE NORTHWEST CORNER OF SECTION 13-17-11
 - 2) 7,960.95' WEST TO THE 1/2" CAPPED REBAR HE SET FOR THE NORTHWEST CORNER OF SECTION 14-17-11
 - 3) 13,226.92' WEST TO THE GLO STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 15-17-11

NORTH QUARTER CORNER 13-17-11