

NORTHWEST CORNER SECTION 13, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) ON PAGE 308 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 12" X 3"** FOR THE CORNER TO SECTIONS 11, 12, 13 & 14-17-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS EAST TO THE 18" X 10" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 12 & 13-17-11
 - 2) 80.00 CHAINS EAST TO THE 17" X 11" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7, 12, 13 & 18 ON THE EAST TOWNSHIP BOUNDARY

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY OR ROAD NUMBER 139 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 142 TO 144 PETITIONED BY JOHN C. WHEELER AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 16-1 & 17-11 [PACKET 383 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 5, 1881, WAS ESTABLISHED AS A 60 FOOT WIDE ROAD ON OCTOBER 5, 1881 AS NOTED BY J. M. GRIFFITH, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND WAS RECORDED ON OCTOBER 15, 1881 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 11-17-11 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 3 MILES TO THE NORTHEAST CORNER OF SECTION 35-16-11 TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTEND SOUTH ON THE SECTION LINES FOR 1 MILE TO THE SOUTHEAST CORNER OF SECTION 14-17-11 AT THE TERMINUS OF THIS ROAD SURVEY

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE LEFT PAGE 227 DATED SEPTEMBER 6, 1881, FOR A ROAD SURVEY IN TOWNSHIPS 16-11 & 17-11, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 11-17-11 ON THIS ROAD SURVEY
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 3 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 35-16-11 TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 14-17-11 AT THE TERMINUS OF THIS ROAD SURVEY

- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "D" ON PAGE 14 DATED FEBRUARY 23, 1882 FOR A ROAD IN TOWNSHIP 17-11, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER COMMON OF SECTION 13-17-11 AT AN ANGLE POINT ON THIS ROAD SURVEY.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS EAST ON THE SECTION LINE FOR 320 RODS TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 13-17-11 TO END THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINE FOR 320 RODS TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 13-17-11 TO BEGIN THIS ROAD SURVEY

- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 180 RECORDED IN ROAD RECORD

BOOK "B" ON PAGES 306 TO 308 PETITIONED BY EDWARD AYERS AND OTHERS FOR THE VACATION AND RELOCATION OF A COUNTY ROAD IN TOWNSHIP 17-11 [PACKET 445 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON FEBRUARY 23, 1882, AND WAS ESTABLISHED AS A 50 FOOT ROAD ON APRIL 23, 1882 AS NOTED BY HUGH F. HOLMES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 13-17-11 ON THIS ROAD SURVEY. THE FOLLOWING PART OF THE COUNTY ROAD RUNNING THROUGH SECTIONS 13 & 24-17-11 WAS VACATED: BEGINNING AT A POINT ON THE WEST LINE OF SECTION 24-17-11 AT 69.2 RODS NORTH OF THE SOUTHWEST CORNER OF SECTION 24-17-11; THENCE NORTHEAST VARIANCE 55° TO THE POINT WHERE SAID ROAD INTERSECTS THE RANGE LINE ABOUT 40 RODS SOUTH OF THE NORTHEAST CORNER OF SECTION 13-17-11.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION FOR THE RELOCATED ROAD:

- 1) THIS RELOCATED ROAD EXTENDS EAST ON THE SECTION LINES FOR 320 RODS TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 13-17-11 ON THE RANGE LINE AT THE TERMINUS OF THE RELOCATED ROAD
 - 2) THIS RELOCATED ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 320 RODS TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 13-17-11 TO COMMENCE THIS ROAD RELOCATION SURVEY
- 6) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 134, A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 134 FOR A COUNTY ROAD IN TOWNSHIP 17-11 AND 17-12 FOR C. E. SAFFER, PRINCIPAL PETITIONER. DATED DECEMBER 7, 1885, **APPARENTLY FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 13-17-11 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 14-17-11 TO BEGIN THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 24-17-11, THEN EAST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 19-17-12 TO END THIS ROAD SURVEY
- 7) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER RECORDED IN ROAD RECORD BOOK "C" ON PAGES 206 TO 298 PETITIONED BY C. E. SAFFER FOR A ROAD IN TOWNSHIPS 17-11 AND 17-12 [PACKET 578 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON DECEMBER 7, 1885, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON JANUARY 6, 1886 AS NOTED BY JOHN L. BUTLER, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON FEBRUARY 6, 1886 BY ROLAND LAKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 13-17-11 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 14-17-11 TO BEGIN THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 24-17-11, THEN EAST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 19-17-12 TO END THIS ROAD SURVEY
- 8) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A **PERMANENT SURVEY** COMPLETED ON APRIL 8, 1886 TO LOCATE THE SOUTHEAST CORNER AND

SOUTH 1/4 CORNER OF SECTION 2-17-11, SURVEY F20001 IN THE SURVEY FILE FOR TOWNSHIP 17-11 AND RECORDED IN VOLUME 36 ON PAGE 356 AT THE REGISTER OF DEEDS OFFICE ON APRIL 16, 1886, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 12-17-11 ON THIS **PERMANENT SURVEY**.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 5,280' NORTH TO THE STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 2-17-11
- 2) 7,920' NORTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 2-17-11
- 3) 10,462' NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 2-17-11 ON THE TOWNSHIP LINE

- 9) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN **PERMANENT SURVEYS** NUMBER 38 AND 105 RECORDED IN SURVEY BOOK "F" ON PAGE 96 DATED MAY 3, 4, 5 & 12, 1886, FOR A SURVEY TO ESTABLISH THE CENTER CORNER OF SECTION 6-17-12 AND THE CORNERS TO THE NORTHEAST 1/4 AND THE SOUTHWEST 1/4 OF SECTION 1-17-11, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 11-17-11 ON THESE **PERMANENT SURVEYS**. HE USED THIS STONE TO SET THE PERMANENT SOUTHWEST CORNER OF SECTION 1-17-11 AND THE PERMANENT CENTER CORNER OF SECTION 1-17-11. THIS SURVEY WAS RECORDED IN VOLUME 36 ON PAGE 497 IN THE REGISTER OF DEEDS OFFICE ON SEPTEMBER 2, 1886 AND SURVEY F01001 IN THE SURVEY FILE FOR TOWNSHIP 17-11.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 79.88 CHAINS NORTH TO THE 18" X 9" X 2" STONE MARKED WITH 1 NOTCH ON THE SOUTH SIDE, 5 NOTCHES ON THE WEST SIDE, ONE NOTCH ON THE NORTH SIDE, AND 5 NOTCHES ON THE EAST SIDE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 1-17-11
- 2) 119.82 CHAINS NORTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 1-17-11

- 10) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 46, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 227 DATED MARCH 18 & 21 AND CLOSED MAY 8, 1902 ORDERED BY ROBERT MOUNKES FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE NORTHEAST CORNER, THE 1/4 CORNER ON THE EAST LINE, AND THE CENTER 1/4 CORNER OF SECTION 15-17-11 AND RUN SUCH LINES AS ARE NECESSARY TO PROPERLY COMPLETE THE WORK, APPARENTLY DID **NOT** FIND THE STONE AT THE NORTHWEST CORNER OF SECTION 13-17-11. HE RAN THE SECTION LINES FROM THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 13-17-11 TO THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 15-17-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 28, AND ADDITIONAL INFORMATION IS IN PACKET "M 66" IN MISCELLANEOUS DRAWER NUMBER 3 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

- 11) COMMISSIONER'S ROAD JOURNAL BOOK "B", PAGE 29

ON OCTOBER 28, 1944 A PETITION SIGNED BY PERRY J. TAYLOR AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 17-11 WAS PRESENTED TO GEORGE K. JACKSON, COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS AND E. C. GOLDSMITH, COUNTY ENGINEER, ON NOVEMBER 17, 1944 AND THE FINAL ORDER OF THE BOARD OF COUNTY COMMISSIONERS ON NOVEMBER 18, 1944 **VACATED** THE FOLLOWING ROAD:

- 1) BEGINNING AT THE SOUTHWEST CORNER OF SECTION 12-17-11; THENCE NORTH ONE (1) MILE; THENCE EAST ONE (1) MILE ALONG THE NORTH SIDE OF

SAID SECTION 12; THENCE SOUTH ONE (1) MILE TO THE SOUTHEAST CORNER OF THE SOUTHEAST QUARTER OF SAID SECTION 12 AND THERE ENDING

- 2) THIS ROAD BEGINNING AT THE SOUTHWEST CORNER OF SECTION 12-17-11; THENCE NORTH ONE (1) MILE; THENCE EAST ONE (1) MILE ALONG THE NORTH SIDE OF SAID SECTION 12; THENCE SOUTH ONE (1) MILE TO THE SOUTHEAST CORNER OF THE SOUTHEAST QUARTER OF SAID SECTION 12 IS OF NO PRACTICAL BENEFIT AS A PUBLIC HIGHWAY AND AS IT HAS NOT BEEN USED FOR SEVERAL YEARS, WE RECOMMEND THAT SAID ROAD BE VACATED AS PETITIONED.

- 12) LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN A SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 121 DATED APRIL 15, 1955 TO SET AN IRON PIN IN THE SOUTHEAST 1/4 OF THE NORTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 13-17-11, SHOWS ON HIS SURVEY DRAWING THE NORTHWEST CORNER OF SECTION 13-17-11. HE DOES NOT LABEL THE SECTION CORNER OR IDENTIFY IT. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,648' EAST TO THE TEMPORARY POINT HE SET FOR THE NORTH 1/4 CORNER OF SECTION 13-17-11
- 2) 3,972' EAST TO THE TEMPORARY POINT HE SET FOR THE NORTH 1/16TH CORNER OF THE NORTHEAST 1/4 OF SECTION 13-17-11
- 3) 5,296' EAST TO THE TEMPORARY POINT HE SET FOR THE NORTHEAST CORNER OF SECTION 13-17-11

- 13) STEVEN S. BROSEMER, L.S. 752, IN A SURVEY F14002 IN THE SURVEY FILE FOR TOWNSHIP 17-11, DATED AUGUST 04, 1987, FOR PROJECT NUMBER 87169 FOR A SURVEY TO LOCATE THE NORTHWEST CORNER OF SECTION 14-17-11, SAID THAT HE DUG FOR THE STONE AT THE NORTHEAST CORNER OF SECTION 14-17-11 WITH A COUNTY MAINTAINER, BUT HE DID **NOT** FIND THE STONE. HE DID FIND A **60 D NAIL**, POSSIBLY ATTRIBUTED TO LESLIE M. GOULD, BUT HE DID **NOT** ACCEPT OR REFERENCE THE NAIL. HE NOTED IN HIS *REPORT OF SURVEY* THAT "THIS AREA SHOWS EVIDENCE OF GLO FRAUD".

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,649.34' EAST TO THE 1/2" CAPPED REBAR HE SET FOR THE NORTH 1/4 CORNER OF SECTION 13-17-11
- 2) 5,311.61' WEST TO THE 1/2" CAPPED REBAR HE SET IN THE ASPHALT SURFACE FOR THE NORTHWEST CORNER OF SECTION 14-17-11
- 3) 10,577.58' WEST TO THE GLO STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 15-17-11

- 14) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 3, 2011 FOR PROJECT NUMBER 11098-02, A SURVEY OF 3 TRACTS IN THE NORTHEAST 1/4 OF SECTION 14-17-11 FOR BETTY DUNN, SURVEY F14003 IN THE SURVEY FILE FOR TOWNSHIP 17-11, SAID THAT HE HAD PREVIOUSLY EXCAVATED FOR THE STONE AT THE NORTHEAST CORNER OF SECTION 14-17-11, AND HE DID **NOT** FIND THE STONE. HE RESET THIS CORNER FROM THE PHYSICAL EVIDENCE THAT HE FOUND AT THIS CORNER. **HE SET A 5/8" X 30" REBAR WITH A LYON COUNTY CAP** FOR THE NORTHEAST CORNER OF SECTION 14-17-11.

- 1) 38.1' WSW TO A SPIKE & BOTTLECAP IN THE EAST FACE OF A POWER POLE
- 2) 34.45' SE TO THE TOP CENTER OF A 4" PIPE CORNER FENCE POST
- 3) 35.2' NNW TO A SPIKE & WASHER IN THE TOP OF A GATE POST
- 4) IN THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD "M" TO THE SOUTH

HIS TIES ARE CONTINUED ON PAGE 5

5) IN THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD 290 EAST-WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 400.01' WEST TO THE NORTHWEST CORNER OF THE EAST 400 FEET OF THE NE1/4 OF THE NE1/4 OF SECTION 14-17-11, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 25.00' SOUTH
- 2) 649.21' WEST TO THE NORTHEAST CORNER OF TRACT 1, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 25.00' SOUTH
- 3) 2,133.01' WEST TO THE NORTHWEST CORNER OF TRACT 1, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 25.00' SOUTH
- 4) 2,669.88' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 14-17-11
- 5) 5,311.38' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE NORTHWEST CORNER OF SEC. 14-17-11
- 6) 1,326.70' SOUTH TO THE DETERMINED POSITION FOR THE SOUTHEAST CORNER OF THE NE1/4 OF THE NE1/4 OF SECTION 14-17-11
- 7) 1,970.85' SOUTH TO THE P.O.B. OF TRACTS 2 & 3, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 25.00' WEST
- 8) 2,391.40' SOUTH TO THE NORTHEAST CORNER OF THE 10 ACRE TRACT FOR PHILLIP H. & PAMELA S. DUNN TRACT RECORDED IN DOC #2009-05242, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752 CAP HE SET AT 25.00' WEST
- 9) 2,653.40' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 14-17-11
- 10) 5,314.60' SOUTH THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE SOUTHEAST CORNER OF SECTION 14-17-11

NORTHWEST CORNER 13-17-11