

NORTHWEST CORNER SECTION 15, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) ON PAGE 316 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 12" X 3"** FOR THE CORNER TO SECTIONS 9, 10, 15 & 16-17-11.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS EAST TO THE 19" X 14" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 10 & 15-17-11
- 2) 80.00 CHAINS EAST TO THE 24" X 12" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 10, 11, 14 & 15-17-11

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT PAGE 155 DATED MAY 10, 1878, APPARENTLY **FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 9-17-11 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS 4 MILES SOUTH ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 33-17-11 ON THE TOWNSHIP LINE
- 2) THIS ROAD EXTENDS 2 MILES NORTH ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 4-17-11 ON THE TOWNSHIP LINE

- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY, IN SURVEY NUMBER 69, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 69 DATED AUGUST 1 THROUGH NOVEMBER 15, 1884 AT THE ORDER OF A. S. STEADMAN, J. H. COURTNEY, AND M. WILLIAMSON TO ESTABLISH THE SOUTHEAST CORNER OF THE WEST 1/2 (FRACTIONAL) OF THE SOUTHEAST 1/4 OF SECTION 17-17-11 AND THE NORTHEAST CORNER OF THE SAME WEST 1/2 OF THE SOUTHWEST CORNER OF SAME SECTION, AND WILLIAM McNABNEY, W. L. DAVIES, H. L. ADAMS, WILLIAM H. ADAMS, JAMES WASHINGTON, J. W. REEDER, AND C. H. DABBS TO PERMANENTLY ESTABLISH ALL OF THE CORNERS NECESSARY TO MAKE ALL SUBDIVISIONS IN SECTION 16-17-11, SAID THAT **HE SET A STONE** FOR THE PERMANENT NORTHEAST CORNER OF SECTION 16-17-11 ON LINE AND AT THE PRORATED DISTANCE BETWEEN THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 9-17-11 AND THE STONE THAT FOUND AT THE SOUTHEAST CORNER OF SECTION 21-17-11 ON THIS **PERMANENT SURVEY**. HE SAID THAT THIS SURVEY WAS SUBJECT TO A CORRECTED SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 79 DATED DECEMBER 20-25, 1884. THIS SURVEY IS RECORDED IN VOLUME 41 ON PAGE 27 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 27, 1887 AND SURVEY F17001 IN THE SURVEY FILE FOR TOWNSHIP 17-11.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 5,287' NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 9-17-11
- 2) 1,322' SOUTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/4/4 CORNER OF THE NE1/4 OF SECTION 16-17-11
- 3) 2,643' SOUTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 16-17-11
- 4) 5,287' SOUTH TO THE STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 16-17-11
- 5) 10,574' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 21-17-11
- 6) 1,322.5' WEST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/8TH CORNER OF THE NE1/4 OF SECTION 16-17-11

HIS INFORMATION IS CONTINUED ON PAGE 2

- 7) 2,645' WEST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 16-17-11
 - 8) 3,967.5' WEST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/8TH CORNER OF THE NW1/4 OF SECTION 16-17-11
 - 9) 5,290' WEST TO THE STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 16-17-11
 - 10) 6,717.5' WEST TO THE STONE HE SET MARKED "RI" AT THE INDIAN RESERVE LINE IN NE1/4 OF SECTION 17-17-11
- 4) ROAD NUMBER 331 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 274 TO 276 [PACKET 587 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE].
ON JULY 13, 1886 A PETITION SIGNED BY JOSEPH FROST AND 12 OTHERS WAS PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS FOR A ROAD COMMENCING AT THE NORTHWEST CORNER OF SECTION 16-17-11, THENCE EAST ON THE SECTION LINE FOR ONE MILE TO THE NORTHEAST CORNER OF SECTION 16-21-11, SAID ROAD TO BE FORTY-FIVE FEET WIDE. ON JULY 13, 1886, THE BOARD OF COUNTY COMMISSIONERS ISSUED THE FOLLOWING ORDER: WHEREAS NO LEGAL OBJECTIONS HAVE BEEN MADE TO THE WITHIN PETITION FOR A ROAD WITHOUT VIEW OR SURVEY, AND WHEREAS, IT APPEARS THAT THERE ARE THE LEGAL NUMBER OF PETITIONERS REQUIRED BY LAW, AND WHEREAS, ALL THE LAND OWNERS TOUCHING SAID ROAD HAVE SIGNED SAID PETITION, AND WHEREAS, THE BOARD OF COUNTY COMMISSIONERS ARE SATISFIED SAID ROAD WILL BE OF PUBLIC UTILITY, IT IS HEREBY ORDERED THAT THE WITHIN PETITION BE GRANTED, AND THE ROAD DESCRIBED THEREIN BE DECLARED A PUBLIC HIGHWAY, AND ORDERED OPENED FORTY-FIVE FEET WIDE. IT WAS SIGNED BY T. E. McMILLAN, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS AND ATTESTED BY ROLAND LAKIN, COUNTY CLERK, AND RECORDED ON DECEMBER 10, 1886 IN ROAD RECORD BOOK "C".
- 5) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A ROAD SURVEY FOR ROAD NUMBER 425 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 602 TO 604 PETITIONED BY JAMES OGLESBY AND OTHERS FOR A ROAD IN TOWNSHIP 17-11 [PACKET 663 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON DECEMBER 4, 1895, WAS ESTABLISHED AS A 40 FOOT ROAD ON OCTOBER 9, 1895 AS NOTED BY JACOB JACOB, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS AND ATTESTED BY C. W. WILHITE, COUNTY CLERK, AND RECORDED BY MATTHEW BROWN, COUNTY SURVEYOR, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 10-17-11 AT THE TERMINUS OF THIS ROAD SURVEY FOR A 40 FOOT WIDE ROAD.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES TO THE ROAD STONE MARKED "R" HE SET AT 11.65 CHAINS WEST OF THE SOUTHEAST CORNER OF SECTION 10-17-11, THEN SOUTH 44°20' E. FOR 7.09 CHAINS TO THE ROAD STONE MARKED "R" ON THE EAST SIDE WITH PIECES OF CAST IRON BESIDE IT HE SET, THEN S. 81°55' W. FOR 6.70 CHAINS TO THE ROAD STONE MARKED "R" HE SET ON THE SECTION LINE STANDING 1.32 CHAINS SOUTH OF THE SOUTH ABUTMENT OF A BRIDGE, THEN NORTH ON THE SECTION LINE FOR 6.00 CHAINS TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 10-17-11 TO BEGIN THIS ROAD SURVEY
 - 2) THE ROAD IS 40 FEET WIDE, BEING 20 FEET ON EACH SIDE OF EH LINE DESCRIBED IN THE PLAT AND FIELD NOTES
- 6) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 44, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 225 AND DATED APRIL 23, 1902 ORDERED BY LOUIS NELSON FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE NORTHEAST CORNER OF

SECTION 10-17-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 10-17-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGES 24 AND 47, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 46" IN MISCELLANEOUS DRAWER 2 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 40.18 CHAINS NORTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 10-17-11
 - 2) 80.36 CHAINS NORTH TO THE STAKE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 10-17-11
- 7) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 46, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 227 DATED MARCH 18 & 21 AND CLOSED MAY 8, 1902 ORDERED BY ROBERT MOUNKES FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE NORTHEAST CORNER, THE 1/4 CORNER ON THE EAST LINE, AND THE CENTER 1/4 CORNER OF SECTION 15-17-11 AND RUN SUCH LINES AS ARE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 15-17-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 26, AND ADDITIONAL INFORMATION IS IN PACKET "M 66" IN MISCELLANEOUS DRAWER NUMBER 4 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 39.93 CHAINS EAST TO THE LOCATION FOR THE NORTH 1/4 CORNER OF SECTION 15-17-11
- 2) 79.86 CHAINS EAST TO THE 24" X 12" X 4" STONE WITH A DRILL HOLE ON THE BOTTOM HE SET FOR THE PERMANENT NORTHEAST CORNER OF SEC. 15-17-11
- 3) 200.59 CHAINS EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 13-17-11

- 8) COMMISSIONER'S ROAD JOURNAL BOOK "B", PAGE 84

ON DECEMBER 12, 1951 A PETITION SIGNED BY NELS MUNSON FOR THE **VACATION** OF A ROAD IN TOWNSHIP 17-11 WAS PRESENTED TO GEORGE K. JACKSON, COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS ON JANUARY 22, 1952 AND THE FINAL ORDER OF THE BOARD OF COUNTY COMMISSIONERS ON JANUARY 22, 1952 **VACATED** THE FOLLOWING ROAD:

- 1) BEGINNING AT A POINT ON THE SECTION LINE AT THE NW1/4 (NORTHWEST CORNER?) OF SECTION 10-17-11, THENCE SOUTH 1 MILE AND THERE ENDING

- 9) STEVEN S. BROSEMER, L.S. 752, IN A SURVEY F14002 IN THE SURVEY FILE FOR TOWNSHIP 17-11, DATED AUGUST 04, 1987, FOR PROJECT NUMBER 87169 FOR A SURVEY TO LOCATE THE NORTHWEST CORNER OF SECTION 14-17-11, SAID THAT **HE FOUND THE GLO STONE LAID OVER** AT THE NORTHWEST CORNER OF SECTION 14-17-11. HE SET THE STONE BACK UP AND **HE DROVE 1/2" REBARS WITH HIS "LS 752" CAPS ON THE EAST AND WEST SIDES** OF THE STONE. HE NOTED THAT THIS AREA OF THIS TOWNSHIP SHOWS EVIDENCE OF GLO FRAUD.

- 1) 40.5' NE TO A PK NAIL & WASHER IN A FENCE POST
- 2) 36.1' NW TO A PK NAIL & WASHER IN A GATE POST
- 3) 28.0' NORTH TO A LINE OF FENCE EAST-WEST
- 4) 1.0' NORTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD EAST-WEST
- 5) IN LINE WITH A FENCE TO THE NORTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 5,265.97' EAST TO THE 1/2" CAPPED REBAR HE SET FOR THE NORTHWEST CORNER OF SECTION 14-17-11

HIS INFORMATION IS CONTINUED ON PAGE 4

- 2) 10,577.58' EAST TO THE 60 D SPIKE HE FOUND AT THE NORTHWEST CORNER OF SECTION 13-16-11
 - 3) 13,226.92' EAST TO THE 1/2" CAPPED REBAR HE SET FOR THE NORTH 1/4 CORNER OF SECTION 13-16-11
- 10) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 13, 2001, FOR PROJECT NUMBER 99480-02, SAID THAT **SHE FOUND THE 1/2" REBAR WITH A "LS 752" CAP** AT THE SOUTHWEST CORNER OF SECTION 10-17-11 FROM TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE. **[NOTE: THE CAPPED REBARS ARE ON THE EAST AND WEST SIDES OF THE GLO STONE AT THIS CORNER ACCORDING TO THE PREVIOUS TIES OF DEPUTY COUNTY SURVEYOR STEVEN S. BROSEMER, L.S. 752. HER TIES INDICATE THAT SHE USED THE GLO STONE FOR THE SOUTHWEST CORNER OF SECTION 10-17-11 – WARREN CHIP WOODS, L.S 603, COUNTY SURVEYOR]**
- 1) 40.50' NW TO A MASONRY NAIL & WASHER IN A FENCE POST
 - 2) 36.10' NW TO A MASONRY NAIL & WASHER IN A FENCE POST
 - 3) 28.0' NORTH TO A LINE OF FENCE EAST-WEST
 - 4) IN LINE WITH A FENCE TO THE NORTH – EXTENDED
 - 5) 1.0' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 290 EAST-WEST
 - 5) IN LINE WITH A FENCE TO THE NORTH-EXTENDED

NORTHWEST CORNER 15-17-11