

WEST 1/4 CORNER SECTION 15, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) ON PAGE 315 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 16" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 15 & 16-17-11.

- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY, IN SURVEY NUMBER 69, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 69 DATED AUGUST 1 THROUGH NOVEMBER 15, 1884 AT THE ORDER OF A. S. STEADMAN, J. H. COURTNEY, AND M. WILLIAMSON TO PERMANENTLY ESTABLISH THE SOUTHEAST CORNER OF THE WEST 1/2 (FRACTIONAL) OF THE SOUTHEAST 1/4 OF SECTION 17-17-11 AND THE NORTHEAST CORNER OF THE SAME WEST 1/2 OF THE SOUTHWEST CORNER OF SAME SECTION, AND WILLIAM McNABNEY, W. L. DAVIES, H. L. ADAMS, WILLIAM H. ADAMS, JAMES WASHINGTON, J. W. REEDER, AND C. H. DABBS TO PERMANENTLY ESTABLISH ALL OF THE CORNERS NECESSARY TO MAKE ALL SUBDIVISIONS IN SECTION 16-17-11, SAID THAT **HE SET A STONE MARKED "1/4"** FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 16-17-11 ON LINE AND HALFWAY BETWEEN THE STONES THAT HE SET FOR THE PERMANENT NORTHEAST AND SOUTHEAST CORNERS OF SECTION 16-17-11 ON THIS **PERMANENT SURVEY**. HE SAID THAT THIS SURVEY WAS SUBJECT TO A CORRECTED SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 79 DATED DECEMBER 20-25, 1884. THIS SURVEY IS RECORDED IN VOLUME 41 ON PAGE 27 IN THE REGISTER OF DEEDS OFFICE ON JANUARY 27, 1887 AND SURVEY F17001 IN THE SURVEY FILE FOR TOWNSHIP 17-11.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,321.5' NORTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/4 CORNER OF THE NE1/4 OF SECTION 16-17-11
 - 2) 2,643.5' NORTH TO THE STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 16-17-11
 - 3) 7,930.5' NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 9-17-11
 - 4) 2,643.5' SOUTH TO THE STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 16-17-11
 - 5) 7,931.5' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 21-17-11

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 46, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 227 DATED MARCH 18 & 21 AND CLOSED MAY 8, 1902 ORDERED BY ROBERT MOUNKES FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE NORTHEAST CORNER, THE 1/4 CORNER ON THE EAST LINE, AND THE CENTER 1/4 CORNER OF SECTION 15-17-11 AND RUN SUCH LINES AS ARE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 15-17-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 26, AND ADDITIONAL INFORMATION IS IN PACKET "M 66" IN MISCELLANEOUS DRAWER NUMBER 4 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

WEST QUARTER CORNER 15-17-11