

NORTH 1/16TH CORNER OF NORTHWEST 1/4 SECTION 17, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 15 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 37 DATED AUGUST 5, 1873 FOR A COUNTY ROAD IN SECTION 17-17-11, SAID THAT **HE SET A 12" X 6" X 2" STONE** FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE NORTHWEST 1/4 OF SECTION 17-17-11 ON LINE AND HALFWAY BETWEEN THE STONE HE THAT FOUND AT THE NORTHWEST CORNER OF SECTION 17-17-11 AND THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 17-17-11 ON THIS **PERMANENT SURVEY**. SEE ALSO PACKET 77 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE FOR ADDITIONAL INFORMATION.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 1,307-1/2 WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 17-17-11
- 2) 1,307-1/2' EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 17-17-11
- 3) 2,668' SOUTH TO THE STONE HE FOUND AT THE 1/2/4 CORNER ON THE SOUTH SIDE OF THE NW1/4 OF SECTION 17-17-11
- 4) 5,317' SOUTH TO THE STONE HE FOUND AT THE 1/2/4 CORNER ON THE SOUTH SIDE OF THE SW1/4 OF SECTION 17-17-11

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 209 [PACKET 77 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY M. J. WILLIAMS AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 17-11, THAT HE SURVEYED ON AUGUST 5, 1873 AND WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON NOVEMBER 28, 1873 AS ATTESTED BY DAVID S. GILMORE, COUNTY CLERK, SAID THAT **HE SET A 12" X 6" X 3" STONE** FOR THE PERMANENT NORTH 1/16TH CORNER OF THE NORTHWEST 1/4 OF SECTION 17-17-11 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 17-17-11 AND THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 17-17-11 TO BEGIN THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 79-1/4 RODS WEST TO THE 12" X 6" X 3" STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 17-17-11
- 2) 79-1.4 RODS EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 17-17-11
- 3) THIS ROAD EXTENDS SOUTH FOR 1 MILE AND 1-1/2 RODS TO THE SOUTH 1/16TH CORNER ON THE SW1/4 OF SECTION 17-17-11 TO END THIS ROAD SURVEY

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 29, 1998, FOR JOB NUMBER 97034 FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT FOR BRIDGE REPLACEMENT PROJECT NUMBER 97-8R, SAID THAT HE CONSIDERED THAT THAT THE NORTH 1/16TH CORNER OF THE NORTHWEST 1/4 OF SECTION 17-17-11 WAS **LOST. HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE NORTH 1/16TH CORNER OF THE NORTHWEST 1/4 OF SECTION 17-17-11 ON TRUE LINE AND HALF-WAY BETWEEN THE NORTHWEST CORNER OF SECTION 17-17-11 AND THE NORTH 1/4 CORNER OF SECTION 17-17-11.

- 1) 42.7' SW TO A 40 D SPIKE & WASHER IN A CORNER FENCE POST
- 2) 49.5' NNE TO A 40 D SPIKE & WASHER IN THE WEST GATE POST
- 3) 67.9' NE TO A 40 D SPIKE & WASHER IN THE EAST GATE POST
- 4) 33.4' SE TO A 40 D SPIKE & WASHER IN A WOOD STOP SIGN POST

HIS INFORMATION IS CONTINUED ON PAGE 2

HIS DRAWING ON HIS REFERENCE REPORT SHOWS THE FOLLOWING:

- 1) 1,310.85' WEST TO THE SQUARE #4 REBAR HE FOUND AT THE NORTHWEST CORNER OF SECTION 17-17-11
 - 2) 1,310.85' EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 17-17-11
 - 3) 2,699.10' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/16TH CORNER OF THE NW1/4 OF SECTION 17-17-11
- 4) LYON COUNTY HIGHWAY DEPARTMENT PLANS FOR PROJECT 97-8R, REPLACING 17' TIMBER CULVERT 939.2-496.2 WITH A 35 FOOT ALL STEEL BRIDGE SIGNED BY WARREN CHIP WOODS, P.E. 7268 ON JUNE 26, 1998, SHOWS THE FOLLOWING INFORMATION ON THE PROJECT PLANS: A 1/2" REBAR WITH A RED CAP AT THE NORTHWEST CORNER OF THE NORTHEAST 1/4 OF THE NORTHWEST 1/4 OF SECTION 17-17-11 AT BASELINE STATION 36+74.22.
- 1) 49.5' NNE TO A 40 D SPIKE & WASHER IN WEST GATE POST
 - 2) 67.9' NE TO A 40 D SPIKE & WASHER IN EAST GATE POST
 - 3) 33.4' SE TO A 40 D SPIKE & WASHER IN WOOD STOP SIGN POST
 - 4) 42.7' SW TO A 40 D SPIKE & WASHER IN A CORNER FENCE POST
- 5) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN SURVEY F08001 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR PROJECT NUMBER 99476-02 DATED APRIL 10, 2001 FOR A SURVEY OF TWO TRACTS IN THE NORTHWEST 1/4 OF SECTION 8-17-11, SHOWS ON HER DRAWING THAT **SHE FOUND THE 1/2" REBAR WITH "LS 752" CAP AT THE SOUTH 1/16TH CORNER OF THE SOUTHWEST 1/4 OF SECTION 8-17-11.**
- HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,310.83' WEST TO THE SQUARE 1/2" REBAR SHE FOUND AT THE SOUTHWEST CORNER OF SECTION 17-17-11
 - 2) 1,310.87' EAST TO THE 1/2" REBAR WITH "LS 752" CAP SHE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 17-17-11
 - 3) 2,521.53' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE SOUTHEAST CORNER OF LOT 8 ON THE SOUTH LINE OF THE SOUTHEAST 1/4 OF SECTION 8-17-11 ON THE EAST BOUNDARY OF THE KANSAS INDIAN RESERVATION
 - 4) 3,951.22' EAST TO THE 1/2" REBAR SHE FOUND AT THE SOUTHEAST CORNER OF SECTION 8-17-11

NORTH SIXTEENTH CORNER NORTHWEST QUARTER 17-17-11