

NORTH 1/4 CORNER SECTION 18, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) ON PAGE 326 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 7 & 18-17-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 35.54 CHAINS WEST TO THE 10" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7, 12, 13 & 18 ON THE WEST TOWNSHIP BOUNDARY
 - 2) 40.00 CHAINS EAST TO THE 16" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7, 8, 17 & 18

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 109 RECORDED IN SURVEY BOOK "A" ON PAGE 200 DATED APRIL 28, 1869 FOR A SURVEY OF LAND OWNED BY J. TILTS, TO SURVEY THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 17, AND ALSO THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 18, ALL IN TOWNSHIP 17, RANGE 11, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 18-17-11 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 317 RODS, 3 LINKS SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 18-17-11

- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 130 RECORDED IN SURVEY BOOK "A" ON PAGES 214 & 215 DATED JULY 3, 1869 TO SURVEY THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 7-17-11, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 7-17-11 ON THIS SURVEY.

- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 99 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 21 DATED APRIL 18, 1873 TO PERMANENTLY ESTABLISH THE 1/4 CORNER ON THE LINE BETWEEN SECTION 7 & 18-17-11, SAID THAT HE FOUND THE POINT AT WHICH THE STONE FORMERLY SAT AND WHICH IS SUPPOSED TO BE THE POINT OF THE NORTH 1/4 CORNER OF SECTION 18-17-11. AFTER RUNNING THE SECTION LINE BETWEEN SECTIONS 7 & 18-17-11, **HE SET A STONE** FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 18-17-11 ON THIS **PERMANENT SURVEY** FROM THE "EVIDENCE OF CHARLES DRAKE, SET THE CORNER BY MEASURING 22-1/2 FEET WEST AND THE SAME SOUTH OF THE CORNER OF A HEDGE AND SET A STONE FOR THE PERMANENT 1/4 CORNER IN ACCORDANCE WITH HIS STATEMENT THAT THE FENCE WAS BUILT WHILE THE STONE WAS STILL STANDING, AND THAT IT WAS SET AT THAT DISTANCE FROM THE STONE".
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 5,293' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 18-17-11

- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 56 DATED MAY 30, 1883 FOR A ROAD IN TOWNSHIP 17, RANGES 10 & 11 AT THE REQUEST OF WILLIAM McNABNEY, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF SECTION 18-17-11 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 1-1/2 MILES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 12-17-10 TO COMMENCE THIS ROAD SURVEY

- 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 1,621 FEET TO AN ANGLE STONE MARKED "R+" HE SET TO BEGIN A SERIES OF ANGLES AND INTERSECTS THE SECTION LINE AT AN ANGLE STONE MARKED "R+" HE SET AT 196 FEET WEST OF THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 7-17-11; THEN CONTINUES EAST ON THE SECTION LINE FOR 196 FEET TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 7-17-11 AT THE TERMINUS OF THIS ROAD
- 6) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 225 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 486 TO 488 PETITIONED BY WILLIAM McNABNEY AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 17-10 AND 18-10 [PACKET 448 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MAY 30, 1883, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD, **EXCEPT** FROM THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 7-17-11 EAST TO THE CREEK, ABOUT 97 RODS, THE ROAD SHALL BE 30 FEET WIDE AND SHALL LIE WHOLELY SOUTH OF THE HEDGE ON THE NORTH SIDE OF THE LINE AND SAID HEDGE SHALL BE THE NORTH LIMIT OF THE ROAD, ON JULY 6, 1883 AS NOTED BY JOHN E. JONES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND ATTESTED TO BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF THE SOUTHEAST 1/4 OF SECTION 7-17-11 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 3) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 1-1/2 MILES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 12-17-10 TO COMMENCE THIS ROAD SURVEY
- 4) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 1,621 FEET TO AN ANGLE STONE MARKED "R+" HE SET TO BEGIN A SERIES OF ANGLES AND INTERSECTS THE SECTION LINE AT AN ANGLE STONE MARKED "R+" HE SET AT 196 FEET WEST OF THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 7-17-11; THEN CONTINUES EAST ON THE SECTION LINE FOR 196 FEET TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 7-17-11 AT THE TERMINUS OF THIS ROAD
- 7) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 3 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 58 DATED FEBRUARY 12 & 13, 1874 TO PERMANENTLY ESTABLISH THE CENTER CORNER AND SUBDIVIDE THE SOUTHEAST 1/4 OF SECTION 7-17-11 EQUALLY BY A LINE EAST AND WEST, SAID THAT HE FOUND "THE STONE ESTABLISHED APRIL 18TH 1873 [SEE NUMBER 99 IN 7TH TERM] NOT BEING CORRECT, I PROCEEDED TO CHANGE THE CORNER TO CORRESPOND WITH THE FIELD NOTES". **HE SET AN 18" X 10" X 2-1/2" LIMESTONE** FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 18-17-11 ON THIS **PERMANENT SURVEY**. HE SAID THAT HE MADE CORRESPONDING CHANGES TO THE CENTER CORNER AND THE 1/2/4 CORNER IN SECTION 18-17-11 TO THE STONE HE JUST SET FOR THE NORTH 1/4 CORNER OF SECTION OF 18-17-11, AND **HE RESET** THOSE STONES ON THIS **PERMANENT SURVEY**.
- 8) REA BOOK 30 ON PAGE 17 SAYS THAT THEY DUG FOR THE STONE AT THE NORTH 1/4 CORNER OF SECTION 18-17-11 BUT DID **NOT** FIND ANYTHING. **THEY DROVE AN IRON PIN** FOR THE NORTH 1/4 CORNER OF SECTION 18-17-11. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
- 1) 35' NE TO A WITNESS PIN 2' NW OF AN ELM TREE
- 2) 37' NW TO A WITNESS PIN 3' SE OF A REA POLE

- 9) REA BOOK 30 ON PAGE 19.5 SAYS THAT **THEY FOUND THE IRON PIN** AT THE NORTH 1/4 CORNER OF SECTION 18-17-11 “AS MARKED BY ME A DAY OR TWO AGO”. THEY SAID THAT THE DISTANCE TO THE NORTHEAST CORNER OF SECTION 18-17-11 IS 2,649 FEET. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
- 10) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 17-11 SHOWS A **REA PIN** AT THE “SW CORNER SE1/4 SECTION 7-17-11”. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
- 1) 37' NW TO A WITNESS [REA]
 - 2) 35' NE TO A WITNESS [REA]
- 11) K. E. RECTOR, CONSULTING ENGINEER, FOR PROJECT S-573 (2) SHOWS A **3/4” SQUARE REBAR** AT THE NORTH 1/4 CORNER OF SECTION 18-17-11 THAT IS 21.4’ NORTH OF A 1/2” REBAR THEY SET AT P. I. STATION 76 + 56.6. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS REBAR MAY HAVE BEEN “HEELED-IN” FOR THE BRIDGE SURVEY! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
- 12) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 10, 2001, FOR PROJECT NUMBER 99476-02, SAID THAT **SHE FOUND A 3/4” SQUARE REBAR** AT THE SOUTH 1/4 CORNER OF SECTION 7-18-11 FROM THE REA FIELD NOTES. THE POSITION WAS FOUND AFTER EXCAVATING WITH A COUNTY MOTOR GRADER AND WAS 2.7’ DEEP. **SHE SET A 5/8” REBAR WITH LYON COUNTY CAP TO REFERENCE THIS REBAR, WHICH WAS NOT USED ON THE SURVEY. SHE SAID THAT THIS MONUMENT SHOULD BE VERIFIED PRIOR TO USE!**
- 1) 42.00’ NW TO A MASONRY NAIL & WASHER SET IN THE EAST FACE OF A CORNER FENCE POST
 - 2) 40.95’ NE TO A MASONRY NAIL & WASHER SET IN A GUY POLE
 - 3) 40.65’ SW TO A MASONRY NAIL & WASHER SET IN A CORNER FENCE POST
 - 4) 40.35’ SE TO A MASONRY NAIL & WASHER SET IN A CORNER FENCE POST
 - 5) 1’ NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 290 EAST-WEST

NORTH QUARTER CORNER 18-17-11