

NORTHWEST CORNER SECTION 18, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) ON PAGE 54 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 14" X 3"** FOR THE CORNER TO SECTIONS 7 & 18-21-11 ON THE WEST TOWNSHIP BOUNDARY ON JANUARY 7, 1861.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 35.54 CHAINS EAST TO THE 16" X 14" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 7 & 18-17-11
 - 2) 75.54 CHAINS EAST TO THE 16" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7, 8, 17 & 18-17-11
 - 3) 40.00 CHAINS SOUTH ON THE RANGE LINE TO THE 16" X 12" X 3" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 18-17-11
 - 4) 80.00 CHAINS SOUTH ON THE RANGE LINE TO THE 24" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 18 & 19-17-11

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 99 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 21 DATED APRIL 18, 1873 TO PERMANENTLY ESTABLISH THE 1/4 CORNER ON THE LINE BETWEEN SECTIONS 7 & 18-17-11, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 18-17-11 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 1,318-7/8' SOUTH ON THE RANGE LINE TO THE STONE HE SET FOR THE PERMANENT WEST 1/2/4 CORNER OF THE NW1/4 OF SECTION 18-17-11
 - 2) 2,637-3/4' SOUTH ON THE RANGE LINE TO THE STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 18-17-11
 - 3) 5,275-1/2' SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 18-17-11
 - 4) 4,936' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 18-17-11

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 3 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 58 DATED FEBRUARY 12 & 13, 1874 TO PERMANENTLY ESTABLISH THE CENTER CORNER AND SUBDIVIDE THE SOUTHEAST 1/4 OF SECTION 7-17-11 EQUALLY BY A LINE EAST AND WEST, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 18-17-11 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**.

- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 28 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 110 TO 112 PETITIONED BY W. R. COLGAN AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 16-10 AND 17-10 [PACKET 116 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 13, 1879, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON JULY 7, 1879, AND WAS RECORDED ON JULY 15, 1879 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 12-17-10 ON THE RANGE LINE ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS NORTH ON THE RANGE LINE TO THE NORTHEAST CORNER OF SECTION 6-16-10 ON THE 3RD STANDARD PARALLEL TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE RANGE LINE TO THE NORTHEAST CORNER OF SECTION 24-17-10 AT THE TERMINUS OF THIS ROAD SURVEY

CONTINUED ON PAGE 2

- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 56 DATED MAY 30, 1883 FOR A ROAD IN TOWNSHIP 17, RANGES 10 & 11, FOR WILLIAM McNABNEY, PRINCIPAL PETITIONER, APPARENTLY **FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 7-17-11 ON THE RANGE LINE ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 12-17-10 TO COMMENCE THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 18-17-11, THEN CONTINUES EAST ON THE SECTION LINES FOR 1,621 FEET TO AN ANGLE STONE MARKED "R+" HE SET TO BEGIN A SERIES OF ANGLES AND INTERSECTS THE SECTION LINE AT AN ANGLE STONE MARKED "R+" HE SET AT 196 FEET WEST OF THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 7-17-11; THEN CONTINUES EAST ON THE SECTION LINE FOR 196 FEET TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 7-17-11 AT THE TERMINUS OF THIS ROAD SURVEY

- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 225 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 486 TO 488 PETITIONED BY WILLIAM McNABNEY AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 17-10 AND 18-10 [PACKET 448 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MAY 30, 1883, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD, EXCEPT FROM THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 7-17-11 EAST TO THE CREEK, ABOUT 97 RODS, THE ROAD SHALL BE 30 FEET WIDE AND SHALL LIE WHOLELY SOUTH OF THE HEDGE ON THE NORTH SIDE OF THE LINE AND SAID HEDGE SHALL BE THE NORTH LIMIT OF THE ROAD, ON JULY 6, 1883 AS NOTED BY JOHN E. JONES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND ATTESTED TO BY WILLIAM F. EWING, COUNTY CLERK, APPARENTLY **FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 7-17-11 ON THE RANGE LINE ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 12-17-10 TO COMMENCE THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 18-17-11, THEN CONTINUES EAST ON THE SECTION LINES FOR 1,621 FEET TO AN ANGLE STONE MARKED "R+" HE SET TO BEGIN A SERIES OF ANGLES AND INTERSECTS THE SECTION LINE AT AN ANGLE STONE MARKED "R+" HE SET AT 196 FEET WEST OF THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 7-17-11; THEN CONTINUES EAST ON THE SECTION LINE FOR 196 FEET TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 7-17-11 AT THE TERMINUS OF THIS ROAD SURVEY

- 6) REA BOOK 30 ON PAGE 19.5 SAYS THAT THEY BEGAN THIS SURVEY AT THE SOUTHWEST CORNER OF SECTION 7-17-11 ON THE RANGE LINE. THEY DID NOT DESCRIBE THE MONUMENT THEY FOUND OR SET AT THIS CORNER AND THERE ARE NO TIES TO THE MONUMENT ON THIS PAGE.

- 7) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 17-11 SHOWS A **REA PIN** AT THE "SW CORNER SECTION 7-17-11" ON THE RANGE LINE. **VERIFY BEFORE USING AND CHECK FOR THE STONE OF RECORD AS THIS IRON PIN WAS**

PROBABLY "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR

- 1) 34' SW TO A WITNESS [REA]
 - 2) 34' NW TO A WITNESS [REA]
- 8) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 10, 2001, FOR PROJECT NUMBER 99476-02, SAID THAT **SHE FOUND A 3/4" SQUARE IRON PIN THAT IS IN THE VICINITY OF THE NORTHWEST CORNER OF SECTION 18-17-11 ON THE RANGE LINE THAT IS PROBABLY FROM THE REA SURVEY ERA, AND ITS POSITION SHOULD BE VERIFIED PRIOR TO USE.** SHE SAID THAT THIS POSITION WAS NOT NEEDED AND WAS NOT USED ON HER SURVEY. **SHE SAID THAT SHE TIED THIS 3/4" SQUARE IRON PIN OUT FOR REFERENCE ONLY AND IT MUST BE VERIFIED BEFORE ACCEPTING THIS 3/4" SQUARE IRON PIN AS THE TRUE SECTION CORNER!**
- 1) 42.8' NW TO THE CENTER OF A PIPE CORNER POST AT GROUND LEVEL
 - 2) 39.25' NE TO A 40 D NAIL & WASHER IN THE SOUTHEASTERLY FACE OF A POWER POLE
 - 3) 43.0' SE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 4) 47.50' SW TO THE CENTER OF A PIPE CORNER POST AT GROUND LEVEL

NORTHWEST CORNER 18-17-11