

WEST 1/4 CORNER SECTION 18, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) ON PAGE 54 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 12" X 3"** FOR THE WEST 1/4 CORNER OF SECTION 18-17-11 ON THE WEST TOWNSHIP BOUNDARY ON JANUARY 7, 1861.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH ON THE RANGE LINE TO THE 20" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7 & 18-17-11
 - 2) 40.00 CHAINS SOUTH ON THE RANGE LINE TO THE 24" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 18 & 19-17-11
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 99 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 21 DATED APRIL 18, 1873 TO ESTABLISH THE 1/4 CORNER ON THE LINE BETWEEN SECTIONS 7 & 18-17-11, SAID THAT **HE SET A STONE** FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 18-17-11 ON THE RANGE LINE AT HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 18-17-11 AND THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 18-17-11 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 1,318-7/8' NORTH ON THE RANGE LINE TO THE STONE HE SET FOR THE PERMANENT WEST 1/2/4 CORNER OF THE NW1/4 OF SECTION 18-17-11
- 2) 2,637-3/4' NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 18-17-11
- 3) 2,637-3/4' SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 18-17-11

- 3) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 17-11 SHOWS A **REA PIN** AT THE "SW CORNER NW1/4 SECTION 18-17-11" ON THE RANGE LINE. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**

- 1) 19.5' TO A WITNESS [REA]

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 9, 2006, FOR PROJECT NUMBER 06201-02 FOR A SURVEY OF THE SOUTHWEST 1/4 OF SECTION 13-17-10 FOR DOLD/BOYCE, SURVEY F13001 IN THE SURVEY FILE FOR TOWNSHIP 17-10, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE AT THE EAST 1/4 CORNER OF SECTION 13-17-10 ON THE RANGE LINE, BUT HE DID **NOT** FIND THE STONE. HE **ACCEPTED** AI CHAMNESS REA SURVEY POSITION **MARKED BY A SQUARE 5/8" REBAR** FOR THE EAST 1/4 CORNER OF SECTION 13-17-10 ON THE RANGE LINE.

- 1) 24.4' WEST TO A CONCRETE NAIL & WASHER IN A 5" TREE
- 2) 20.0' EAST TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
- 3) 38.7' NE TO A 40 D NAIL & WASHER IN A POWER POLE
- 4) IN LINE WITH A FENCE TO THE EAST
- 5) IN THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD "G" NORTH-SOUTH
- 6) THE FOUND REBAR IS APPROXIMATELY **8" DEEP**

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,636.87' WEST TO THE 5/8" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 13-17-10
- 2) 3,953.84' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE W1/2 OF THE SW1/4 OF SECTION 13-17-10

HIS INFORMATION IS CONTINUED ON PAGE 2

- 3) 5,270.81' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 13-17-10

WEST QUARTER CORNER 18-17-11