

NORTH 1/4 CORNER SECTION 19, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) ON PAGE 325 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 14" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 18 & 19-17-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 35.74 CHAINS WEST TO THE 24" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 13, 18, 19 & 24 ON THE WEST TOWNSHIP BOUNDARY
 - 2) 40.00 CHAINS EAST TO THE 16" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 17, 18 19, & 20

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 109 RECORDED IN SURVEY BOOK "A" ON PAGE 200 DATED APRIL 28, 1869 FOR A SURVEY OF LAND OWNED BY J. TILTS, TO SURVEY THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 17, AND ALSO THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 18, ALL IN TOWNSHIP 17, RANGE 11, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 18-17-11 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 317 RODS, 3 LINKS NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 18-17-11
 - 2) 80 RODS, 11-1/2 LINKS EAST TO THE STONE HE SET FOR THE SOUTH 1/2/4 CORNER OF THE SE1/4 OF SECTION 18-17-11
 - 3) 160 RODS, 23 LINKS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 18-17-11

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 99 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 21 DATED APRIL 18, 1873 TO PERMANENTLY ESTABLISH THE 1/4 CORNER ON THE LINE BETWEEN SECTIONS 7 & 18-17-11, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 18-17-11 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 5,293' NORTH TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 18-17-11

- 4) **REA PIN—MUST VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY JUST "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR** REA BOOK 30 ON PAGE 15 SAYS THAT **THEY SET AN IRON PIN** FOR THE SOUTH 1/4 CORNER OF SECTION 18-17-11 AT 2,640' WEST OF THE STONE THAT THEY FOUND AT THE SOUTHEAST CORNER OF SECTION 18-17-11.
 - 1) 21' SOUTH TO A WITNESS PIN

- 5) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 17-11 SHOWS A **REA PIN** AT THE "SW CORNER SE1/4 SECTION 18-17-11". **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 21' SOUTH TO A WITNESS [REA]

NORTH QUARTER CORNER 19-17-11