

NORTHWEST CORNER SECTION 19, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) ON PAGE 53 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 12" X 4"** FOR THE CORNER TO SECTIONS 18 & 19-17-11 ON THE WEST TOWNSHIP BOUNDARY ON JANUARY 7, 1861.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 35.74 CHAINS EAST TO THE 14" X 14" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 18 & 19-17-11
 - 2) 75.74 CHAINS EAST TO THE 16" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 17, 18, 19 & 20-17-11
 - 3) 40.00 CHAINS SOUTH ON THE RANGE LINE TO THE 20" X 12" X 4" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 19-17-11
 - 4) 80.00 CHAINS SOUTH ON THE RANGE LINE TO THE 14" X 10" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19 & 30-17-11
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 99 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 21 DATED APRIL 18, 1873 TO ESTABLISH THE 1/4 CORNER ON THE LINE BETWEEN SECTION S7 & 18-17-11, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTIONS 18-17-11 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 2,637-3/4' NORTH ON THE RANGE LINE TO THE STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 18-17-11
- 2) 3,956-5/8' NORTH ON THE RANGE LINE TO THE STONE HE SET FOR THE PERMANENT WEST 1/2/4 CORNER OF THE NW1/4 OF SECTION 18-17-11
- 3) 5,275-1/2' NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 18-17-11

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 2 & 3 FOR ROAD NUMBER 1 BY A PETITION BY E. A. LEWIS AND OTHERS FOR A CHANGE IN THE COUNTY ROAD IN SECTION 19-17-11 [PACKET 107 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON AUGUST 30, 1878, AND WAS ESTABLISHED AS A 40 FOOT WIDE ROAD AND RECORDED ON NOVEMBER 25, 1878 WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 19-17-11 ON THE RANGE LINE AT THE TERMINUS OF THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS SOUTH ON THE RANGE LINE FOR 1 MILE TO THE NORTHWEST CORNER OF SECTION 30-17-11 TO COMMENCE THIS ROAD SURVEY

- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" AT THE TOP OF THE RIGHT SIDE OF PAGE 161 DATED AUGUST 30, 1878, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 19-17-11 AT THE TERMINUS OF THIS ROAD SURVEY THAT EXTENDED ONE MILE SOUTH ON THE RANGE LINE TO THE NORTHWEST CORNER OF SECTION 30-19-11.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS SOUTH ON THE RANGE LINE FOR 1 MILE TO THE NORTHWEST CORNER OF SECTION 30-17-11 TO COMMENCE THIS ROAD SURVEY

CONTINUED ON PAGE 2

- 5) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 28 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 110 TO 112 PETITIONED BY W. R. COLGAN AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 16-10 AND 17-10 [PACKET 116 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 13, 1879, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON JULY 7, 1879, AND WAS RECORDED ON JULY 15, 1879 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 24-17-10 ON THE RANGE LINE AT THE TERMINUS OF THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS NORTH ON THE RANGE LINE TO THE NORTHEAST CORNER OF SECTION 6-16-10 ON THE 3RD STANDARD PARALLEL TO COMMENCE THIS ROAD SURVEY
- 6) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A **PERMANENT SURVEY** RECORDED IN VOLUME 3 ON PAGE 561 IN THE REGISTER OF DEEDS OFFICE FOR A SURVEY DATED APRIL 12-14, 1880 AND SURVEY F23001 IN THE SURVEY FILE FOR TOWNSHIP 17-10 TO ESTABLISH THE CORNERS TO THE NORTHEAST 1/4 OF SECTION 26, THE SOUTH CORNERS OF THE NORTHEAST 1/4 OF SECTION 24, ALSO THE NORTH & WEST & SOUTH CORNERS OF THE NORTHWEST 1/4, AND THE NORTHWEST AND SOUTH CORNERS OF THE SOUTHWEST 1/4, AND THE NORTH AND SOUTH CORNERS OF THE NORTH 1/2, AND THE NORTH & WEST CORNERS OF THE SOUTHWEST 1/4 OF SECTION 25, ALSO THE EAST & SOUTH CORNERS OF THE SOUTHEAST 1/4 OF SECTION 24, AND ALSO THE EAST CORNERS TO THE SOUTHEAST 1/4 OF SECTION 23, ALL IN TOWNSHIP 17-10, SAID THAT **HE SET A 19" X 9" X 8" ROCK** FOR THE PERMANENT NORTHEAST CORNER OF SECTION 24-17-10 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 39.88-1/2 CHAINS SOUTH ON THE RANGE LINE TO THE 22" X 12" X 6" ROCK HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 24-17-10
 - 2) 79.77 CHAINS SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 24-17-10
 - 3) 39.65 CHAINS WEST TO THE 18" X 13-1/2" X 5-1/2" ROCK HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 24-17-10
 - 4) 79.30 CHAINS WEST TO THE 25" X 8" X 5" ROCK HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 24-17-10
 - 5) 119.59 CHAINS WEST TO THE 24" X 13" X 2-1/2" ROCK HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 23-7-10
 - 6) 159.88 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 23-17-10
- 7) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 30 DATED AUGUST 30, 1882, FOR A ROAD IN TOWNSHIP 17, RANGE 10 FOR W. P. STEWART, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 24-17-10 ON THE RANGE LINE TO END THIS ROAD SURVEY. THERE IS NO WIDTH RECORDED ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 22-17-10 TO BEGIN THIS ROAD SURVEY
- 8) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 214 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 442 TO 444 PETITIONED BY W. P. STEWART AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 17-10 [PACKET 471 IN THE VAULT IN THE COUNTY

SURVEYOR'S OFFICE] THAT HE SURVEYED ON AUGUST 30, 1883, WAS ESTABLISHED AS A 40 FOOT ROAD ON THE SOUTH SIDE OF SECTION 15-17-10 AND THE REMAINDER TO BE 50 FEET WIDE ON APRIL 145, 1883 AS NOTED BY J. E. JONES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON MAY 23, 1883 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 24-17-10 ON THE RANGE LINE AT THE TERMINUS OF THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES AS A 50 FOOT WIDE ROAD FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 23-17-10; THEN CONTINUES WEST ON THE SECTION LINES AS A 40 FOOT WIDE ROAD FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 22-17-10 TO COMMENCE THIS ROAD SURVEY

- 9) REA BOOK 30 ON PAGE 5 GIVES THE FOLLOWING TIES TO THIS CORNER BUT NO DESCRIPTION OF THE MONUMENT THAT WAS SET FOR THE CORNER COMMON TO SECTIONS 13, 18, 19 & 24 ON THE RANGE LINE: **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS "MONUMENT" WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 30' SW TO CORNER FROM IRON WITNESS PIN AT A STAKE
 - 2) 30' NW FROM WITNESS PIN TO SECTION CORNER
 - 3) 17' NW FROM CORNER TO THE NORTH WALL OF A CONCRETE CULVERT
 - 4) 18.75' SW TO THE SOUTH WALL OF A CONCRETE CULVERT

- 10) REA BOOK 30 ON PAGE 15 SAYS THAT **THEY FOUND THE PIN** MARKING THE SOUTHWEST CORNER OF SECTION 18-17-11 ON THE RANGE LINE. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**

- 11) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 17-11 SHOWS A **REA PIN** AT THE "SW CORNER SECTION 18-17-11 ON THE RANGE LINE. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY "HEELED-IN" FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 30' NE AND 30' SE TO WITNESS PINS [REA]

NORTHWEST CORNER 19-17-11